Introduced 10-4-2021
10-19-2021
Public Hearing
Council Action
Executive Action 1 - 3 - 2021
Effective Date 1-3-2022

County Council of Howard County, Maryland

2021 Legislative Session

Legislative Day No. 16

Bill No. 75-2021

Introduced by: The Chairperson at the request of the County Executive

AN ACT adopting the National Fire Protection Association 1, Fire Code, 2021 Edition as the Howard County Fire Prevention Code, which sets certain fire safety requirements for structures in order to protect life and property; making certain local amendments to the Fire Code which shall include, among other things, the incorporation of certain duties and responsibilities in plan review and inspection; revising and reorganizing certain provisions governing open fires; addressing unit number assignments in certain multi-family residential buildings; requiring certain notice of special events that do not require police permits; amending certain provisions related to the contractor portal; clarifying road widths for fire access roads that access solar facilities; and generally relating to fire safety requirements and fire prevention in Howard County.

Introduced and read first time 2, 2021. Ordered posted and hearing scheduled.
By order
Michelle Harrod, Administrator
Having been posted and notice of time & place of hearing & title of Bill having been published according to Charter, the Bill was read for a
second time at a public hearing on
By order Manuel Coerros
Michelle Harrod, Administrator
This Bill was read the third time on, Passed, Passed with amendments, Failed
By order Michelle Harrod, Administrator
Sealed with the County Seal and presented to the County Executive for approval this 2 day of 0, 2021 at a.m. p.m.
By order Michelle Harrod, Administrator
Witchelle Hairod, Administrator
Approved/Vetoed by the County Executive
Calvin Ball, County Executive

NOTE: [[text in brackets]] indicates deletions from existing law; TEXT IN SMALL CAPITALS indicates additions to existing law; Strike-out indicates material deleted by amendment; Underlining indicates material added by amendment.

1	Sec	tion 1. B	e It End	acted by the County Council of Howard County, Maryland, that the Howard
2	Coi	ınty Code	is amer	nded as follows:
3				
4	Вул	repealing		
5		Title .	17, Publ	ic Protection Services
6		Sectio	on 17.10	4 "Howard County Fire Prevention Code"
7				
8	Ву	adding		
9		Title .	17, Publ	ic Protection Services
10		New S	Section I	17.104 "Howard County Fire Prevention Code"
11				
12				Title 17. Public Protection Services.
13				Subtitle 1. Fire and Rescue Services.
14				
15	SEC	TION 17.	104. Ho	WARD COUNTY FIRE PREVENTION CODE.
16	(A)	ADOPTIC	ON OF NA	TIONAL CODES: EXCEPT AS PROVIDED IN SUBSECTION (B) OF THIS SECTION,
17		THE NFI	PA 1, Fir	re Code 2021 edition (published by the National Fire Protection
18		ASSOCIA	TION), I	s adopted as the Howard County Fire Prevention Code as if the
19		NATIONA	al Code	E IS SET OUT IN FULL IN THIS SUBTITLE.
20	(B)	THE COU	JNTY MA	AY ADOPT REGULATIONS TO ADMINISTER THE PROVISIONS OF THIS SUBTITLE.
21	(C)	LOCAL A.	MENDME	ENTS TO THE HOWARD COUNTY FIRE PREVENTION CODE. THE FOLLOWING
22		AMENDM	IENTS M	ODIFY CERTAIN PROVISIONS OF THE ADOPTED CODE:
23		(1)	GENER	RAL:
24			(I)	THE TERM "CODE OFFICIAL", "ENFORCEMENT OFFICER", OR "FIRE
25				Official" shall mean the Director, Chief or AHJ of the
26				DEPARTMENT OF FIRE AND RESCUE SERVICES OR THE CHIEF'S AUTHORIZED
27				DESIGNEE.
28			(II)	WHEREVER THE NAME OF THE MUNICIPALITY IS TO BE INDICATED, INSERT
29				"Howard County, Maryland".

1		(III) Wherever the term "this Code" is used, it refers to this subtitle,
2		WHICH SHALL BE KNOWN AS THE HOWARD COUNTY FIRE PREVENTION
3		Code.
4		(IV) THE TERM "CODE ENFORCEMENT AGENCY" SHALL MEAN THE DEPARTMENT
5		OF FIRE AND RESCUE SERVICES.
6	(2)	Subsection 1.1.1(2)
7		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
8		Investigation of fires, explosions, potentially explosive devices,
9		HAZARDOUS MATERIAL INCIDENTS, AND OTHER RELATED EMERGENCY INCIDENTS.
10		THESE DUTIES MAY BE PERFORMED IN CONJUNCTION WITH OTHER PUBLIC
11		AGENCIES.
12	(3)	SUBSECTION 1.1.1(3)
13		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
14		In conjunction with the Department of Planning and Zoning, review of
15		SITE DEVELOPMENT PLANS FOR ADEQUATE ACCESS, WATER SUPPLY, AND OTHER
16		LIFE SAFETY ISSUES. IN CONJUNCTION WITH THE DEPARTMENT OF INSPECTIONS,
17		LICENSES AND PERMITS, THE REVIEW OF DESIGN AND CONSTRUCTION DRAWINGS,
18		PLANS, AND SPECIFICATIONS FOR LIFE SAFETY SYSTEMS, FIRE PROTECTION
19		SYSTEMS, AND OTHER FIRE AND LIFE SAFETY ISSUES.
20	(4)	SUBSECTION 1.1.1(5)
21		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
22		THE INSPECTION OF EXISTING OCCUPANCIES, STRUCTURES, AND AREAS. IN
23		CONJUNCTION WITH THE DEPARTMENT OF INSPECTIONS, LICENSES, AND PERMITS,
24		THE DESIGN OF NEW BUILDINGS AND ALTERATIONS AND ADDITIONS TO EXISTING
25		BUILDINGS. THE AHJ MAY INDEPENDENTLY INSPECT NEW AND EXISTING
26		STRUCTURES DURING CONSTRUCTION, ALTERATION, AND DEMOLITION FOR THE
27		PURPOSE OF ASSURING COMPLIANCE WITH NFPA 241, AS AMENDED.
28	(5)	Subsection 1.1.1(6)
29		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
30		THE MAINTENANCE AND TESTING OF EXISTING FIRE PROTECTION SYSTEMS AND
31		EQUIPMENT AND, IN CONJUNCTION WITH THE DEPARTMENT OF INSPECTIONS,

1		LICENSES AND PERMITS, THE DESIGN, ALTERATION, MODIFICATION, AND
2		INSTALLATION OF NEW AND EXISTING FIRE PROTECTION SYSTEMS AND EQUIPMENT.
3	(6)	Subsection 1.1.1(16)
4		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
5		In conjunction with the Department of Inspections, Licenses and Permits
6		THE ARRANGEMENT, DESIGN, CONSTRUCTION AND ALTERATION OF NEW AND
7		EXISTING MEANS OF EGRESS.
8	(7)	SUBSECTION 1.3.3.1
9		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
10		When this Code and any other referenced codes or code sections have
11		CONFLICTING REQUIREMENTS, THE MOST RESTRICTIVE REQUIREMENT SHALL APPLY
12		THE AHJ MAY ACCEPT ALTERNATIVE FEATURES OR REQUIREMENTS THAT PROVIDE
13		THE SAME LEVEL OF FIRE SAFETY AS THE REQUIREMENTS OF THIS CODE. THE AHJ'S
14		ACCEPTANCE OF ALTERNATIVES SHALL BE IN WRITING.
15	(8)	Subsection 1.3.3.1.1
16		ADD NEW SUBSECTION 1.3.3.1.1 AFTER SUBSECTION 1.3.3.1 AS FOLLOWS:
17		If sections of this Code are less restrictive than the latest adopted
18		VERSION OF THE MARYLAND STATE FIRE PREVENTION CODE, THE APPLICABLE
19		PROVISIONS OF THE MARYLAND STATE FIRE PREVENTION CODE SHALL APPLY.
20	(9)	SECTION 1.4.2
21		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
22		THE AHJ MAY ACCEPT ALTERNATE METHODS OF SATISFYING INTENT OF THIS CODE
23		IF THE MATERIAL, METHOD, OR WORK IS AT LEAST THE EQUIVALENT OF THAT
24		required by this Code in quality, effectiveness, durability, and safety
25		AND MEETS OR EXCEEDS THE INTENT OF THIS CODE.
26	(10)	SECTION 1.7.1
27		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
28		Administration. The provisions of this Code and Sections 17.105, 17.106,
29		17.107, AND 17.111 OF THE HOWARD COUNTY CODE SHALL APPLY WITHOUT
30		RESTRICTION, UNLESS SPECIFICALLY EXEMPTED.

1	(11)	SECTION 1.7.5
2		INSERT THE FOLLOWING AT THE END OF THIS SECTION:
3		In addition to the enforcement authority of the AHJ and the
4		ENFORCEMENT AUTHORITY GRANTED TO THE DEPARTMENT OF POLICE AND OTHER
5		APPLICABLE GOVERNMENT AUTHORITIES BY SECTION 1.7.4 AND SECTION 65.1.3 OF
6		THIS CODE, THE DIRECTOR OF THE DEPARTMENT OF INSPECTIONS, LICENSES AND
7		PERMITS, OR THE DIRECTOR'S AUTHORIZED DESIGNEE, MAY ENFORCE THE
8		PROVISIONS OF THIS CODE WHEN:
9		(1) REVIEWING PLANS FOR OR INSPECTING NEW CONSTRUCTION;
10		(2) REQUESTED TO CONDUCT SPECIFIC INSPECTIONS AUTHORIZED BY THE AHJ;
11		OR
12		(3) Inspecting commercial or residential buildings, structures, sites,
13		OR AREAS.
14	(12)	Subsection 1.7.7.1
15		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
16		The AHJ shall designate persons authorized to inspect all buildings,
17		STRUCTURES, SITES, OR AREAS, INCLUDING SINGLE-FAMILY DWELLINGS WHERE
18		REQUIRED BY THIS CODE, FOR THE PURPOSES OF ASCERTAINING AND CAUSING TO BE
19		CORRECTED ANY CONDITIONS LIABLE TO CAUSE FIRE, CONTRIBUTE TO THE SPREAD
20		OF FIRE, INTERFERE WITH FIREFIGHTING OPERATIONS, ENDANGER LIFE OR ANY
21		violations of the provisions or intent of this Code or any other
22		ORDINANCE AFFECTING FIRE SAFETY.
23	(13)	Subsection 1.7.7.1.1
24		ADD NEW SUBSECTION 1.7.7.1.1 AFTER SUBSECTION 1.7.7.1 AS FOLLOWS:
25		PERSONNEL PERFORMING INSPECTIONS MAY DOCUMENT INSPECTIONS THROUGH
26		ANY APPROPRIATE MEANS INCLUDING THE USE OF PHOTOGRAPHY AND VIDEO
27		RECORDING.
28	(14)	Subsection 1.7.7.6
29		ADD NEW SUBSECTION 1.7.7.6 AFTER SUBSECTION 1.7.7.5 AS FOLLOWS:
30		A PERSON WHO REFUSES TO ALLOW AN INSPECTION OF A BUILDING, STRUCTURE,
31		SITE, OR AREA WHEN THE INSPECTION IS AUTHORIZED BY THIS CODE IS GUILTY OF A

1		MISDEMEANOR AND, UPON CONVICTION, IS SUBJECT TO A FINE NOT EXCEEDING
2		\$1,000.00 or imprisonment not exceeding 30 days or both. Alternatively,
3		AND IN ADDITION TO AND CONCURRENT WITH ALL REMEDIES PROVIDED AT LAW OR
4		EQUITY, A FIRE OFFICIAL MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES
5		pursuant to title 24, "civil penalties," of the Howard County Code. A
6		violation of this subsection is a Class $f A$ offense. Each day that a
7		VIOLATION CONTINUES IS A SEPARATE OFFENSE.
8	(15)	Subsection 1.7.9.1
9		ADD NEW SUBSECTION 1.7.9.1 AFTER SECTION 1.7.9 AS FOLLOWS:
10		A PERSON INTERFERING OR CAUSING A CONDITION THAT WOULD INTERFERE WITH
11		THE ENFORCEMENT OF THIS CODE IS GUILTY OF A MISDEMEANOR AND, UPON
12		CONVICTION, IS SUBJECT TO A FINE NOT EXCEEDING \$1,000.00 OR IMPRISONMENT
13		not exceeding 30 days or both. Alternatively, and in addition to and
14		CONCURRENT WITH ALL REMEDIES PROVIDED AT LAW OR EQUITY, A FIRE OFFICIAL
15		MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES PURSUANT TO TITLE 24, "CIVIL
16		PENALTIES," OF THE HOWARD COUNTY CODE. A VIOLATION OF THIS SUBSECTION IS
17		A CLASS $f A$ OFFENSE. EACH DAY THAT A VIOLATION CONTINUES IS A SEPARATE
18		OFFENSE.
19	(16)	Subsection 1.7.10.1
20		ADD NEW SUBSECTION 1.7.10.1 AFTER SECTION 1.7.10 AS FOLLOWS:
21		A person impersonating a Fire Official is guilty of a misdemeanor and,
22		upon conviction, is subject to a fine not exceeding \$1,000.00 or
23		imprisonment not exceeding 30 days or both. Alternatively, and in
24		ADDITION TO AND CONCURRENT WITH ALL REMEDIES PROVIDED AT LAW OR EQUITY
25		A FIRE OFFICIAL MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES PURSUANT TO
26		TITLE 24, "CIVIL PENALTIES," OF THE HOWARD COUNTY CODE. A VIOLATION OF
27		THIS SUBSECTION IS A CLASS A OFFENSE. EACH DAY THAT A VIOLATION CONTINUES
28		IS A SEPARATE OFFENSE.
29	(17)	SUBSECTION 1.7.11.1
30		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:

1		AUTHORITY. THE AHJ MAY INVESTIGATE THE ORIGIN, CAUSE, AND
2		CIRCUMSTANCES OF ANY FIRE, EXPLOSION, POTENTIALLY EXPLOSIVE DEVICE,
3		HAZARDOUS MATERIALS INCIDENT, OR OTHER EMERGENCY SITUATION. THESE
4		DUTIES MAY BE PERFORMED IN CONJUNCTION WITH OTHER PUBLIC AGENCIES.
5	(18)	Subsection 1.7.11.1.1
6		ADD NEW SUBSECTION 1.7.11.1.1 AFTER SUBSECTION 1.7.11.1 AS FOLLOWS:
7		To the extent permitted by law, the County may pursue legal action to
8		SEEK REIMBURSEMENT OF COSTS FOR EMERGENCY SERVICES PROVIDED IN
9		RESPONSE TO ARSON, MALICIOUS BURNS, EXPLOSIVE DEVICE, AND HOAX EXPLOSIVE
10		DEVICE INCIDENTS FROM THE PERSON OR PERSONS WHO COMMITTED THE CRIME(S).
11	(19)	SUBSECTION 1.7.11.2
12		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
13		EVIDENCE. THE AHJ MAY TAKE CUSTODY OF ALL PHYSICAL EVIDENCE RELATING
14		TO A FIRE, EXPLOSION, HAZARDOUS MATERIALS INCIDENT, OR OTHER EMERGENCY
15		OR HAZARDOUS SITUATION.
16	(20)	Subsection 1.7.11.4
17		ADD NEW SUBSECTION 1.7.11.4 AFTER SUBSECTION 1.7.11.3 AS FOLLOWS:
18		A PERSON INTERFERING OR CAUSING A CONDITION THAT WOULD INTERFERE WITH
19		AN INVESTIGATION IS GUILTY OF A MISDEMEANOR AND, UPON CONVICTION, IS
20		subject to a fine not exceeding \$1,000.00 or imprisonment not exceeding
21		30 days or both. Alternatively, and in addition to and concurrent with
22		ALL REMEDIES PROVIDED AT LAW OR EQUITY, A FIRE OFFICIAL MAY ENFORCE THIS
23		SECTION WITH CIVIL PENALTIES PURSUANT TO TITLE 24, "CIVIL PENALTIES," OF THE
24		HOWARD COUNTY CODE. A VIOLATION OF THIS SUBSECTION IS A CLASS A
25		OFFENSE. EACH DAY THAT A VIOLATION CONTINUES IS A SEPARATE OFFENSE.
26	(21)	Subsection 1.7.13.1
27		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
28		The AHJ may inspect structures undergoing construction, alteration,
29		OR DEMOLITION TO ENSURE COMPLIANCE WITH NFPA 241. WHEN REQUESTED BY
30		THE DEPARTMENT OF INSPECTIONS, LICENSES, AND PERMITS, THE DEPARTMENT OF
31		FIRE AND RESCUE SERVICES SHALL ASSIST THE DEPARTMENT OF INSPECTIONS,

1		Licenses and Permits with the inspection of new construction,
2		ALTERATIONS, OR THE INSTALLATION OF PROCESSES OR EQUIPMENT COVERED BY
3		THIS CODE.
4	(22)	Subsection 1.7.13.3
5		AFTER "AHJ", INSERT "OR OTHER APPLICABLE GOVERNMENT AUTHORITY".
6	(23)	Subsection 1.7.15.1
7		ADD NEW SUBSECTION 1.7.15.1 AFTER SECTION 1.7.15 AS FOLLOWS:
8		Work subject to a stop work order by the AHJ shall immediately stop.
9		THE AHJ MAY RESCIND A STOP WORK ORDER AFTER THE SITUATION HAS BEEN
10		CORRECTED AND INSPECTED BY THE AHJ OR AN INSPECTION BY THE DEPARTMENT
11		of Inspections, Licenses and Permits deems the building is safe.
12	(24)	Subsection 1.7.15.2
13		ADD NEW SUBSECTION 1.7.15.2 AFTER SUBSECTION 1.7.15.1 AS FOLLOWS:
14		In addition to any other enforcement action, a person failing to obey an
15		ORDER TO STOP WORK, ABATE A CONDITION, CEASE A USE, OR IMMEDIATELY
16		EVACUATE A BUILDING, STRUCTURE, SITE, OR AREA IS GUILTY OF A MISDEMEANOR
17		and, upon conviction, is subject to a fine not exceeding $\$1,\!000.00$ or
18		imprisonment not exceeding 30 days or both. Alternatively, and in
19		ADDITION TO AND CONCURRENT WITH ALL REMEDIES PROVIDED AT LAW OR EQUITY
20		A FIRE OFFICIAL MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES PURSUANT TO
21		TITLE 24, "CIVIL PENALTIES," OF THE HOWARD COUNTY CODE. A VIOLATION OF
22		THIS SUBSECTION IS A CLASS A OFFENSE. EACH DAY THAT A VIOLATION CONTINUES
23		IS A SEPARATE OFFENSE.
24	(25)	Subsection 1.7.16.5
25		Add new subsection $1.7.16.5$ after subsection $1.7.16.4$ as follows:
26		THE AHJ MAY ORDER THE EVACUATION OF A BUILDING OR STRUCTURE IF THE FIRE
27		DETECTION OR SUPPRESSION SYSTEM IS NOT IN WORKING ORDER, THE BUILDING OR
28		STRUCTURE IS OVERCROWDED, OR THERE IS A VIOLATION OF THIS CODE THAT
29		CREATES A HAZARDOUS CONDITION, EMERGENCY, OR IMMINENT DANGER.
30	(26)	Subsection 1.7.17.4
31		ADD NEW SUBSECTION 1.7.17.4 AFTER SUBSECTION 1.7.17.3 AS FOLLOWS:

1	•	INDIVIDUALS DESIGNATED AS STANDBY FIRE PERSONNEL (FIRE WATCH) MUST:
2		(1) HAVE A FUNCTIONAL KNOWLEDGE OF THE BUILDING LAYOUT AND THE
3		BUILDING'S SYSTEMS;
4		(2) BE ABLE TO OPERATE VALVES, CLIMB STAIRS, DIAL PHONES, AND SPEAK
5		CALMLY AND CLEARLY IN A STRESSFUL SITUATION;
6		(3) Manage people in an emergency; and
7		(4) HAVE THE KNOWLEDGE AND ABILITY TO OPERATE A FIRE EXTINGUISHER.
8	(27)	Subsection 1.7.17.4.1
9		ADD NEW SUBSECTION $1.7.17.4.1$ AFTER SUBSECTION $1.7.17.4$ AS FOLLOWS:
10		STANDBY FIRE PERSONNEL SHALL WALK THE ENTIRE BUILDING AT LEAST ONE TIME
11		EACH HOUR IN ORDER TO CHECK FOR SMOKE OR FIRE AND TO ENSURE THAT ALL
12		MEANS OF EGRESS ARE ACCESSIBLE AND UNOBSTRUCTED.
13	(28)	Subsection 1.7.17.4.2
14		ADD NEW SUBSECTION 1.7.17.4.2 AFTER SUBSECTION 1.7.17.4.1 AS FOLLOWS:
15		STANDBY FIRE PERSONNEL MAY ALSO BE REQUIRED TO OPERATE A FIRE
16		EXTINGUISHER. HOWEVER, THE PRIMARY RESPONSIBILITY OF STANDBY FIRE
17		PERSONNEL IS THE EVACUATION AND SAFETY OF THE BUILDING'S OCCUPANTS.
18	(29)	SUBSECTION 1.7.17.4.3
19		ADD NEW SUBSECTION 1.7.17.4.3 AFTER SUBSECTION 1.7.17.4.2 AS FOLLOWS:
20		STANDBY FIRE PERSONNEL SHALL NOT HAVE ANY OTHER DUTIES WHILE THEY ARE
21		SERVING AS STANDBY FIRE PERSONNEL.
22	(30)	Subsection 1.7.17.4.4
23		ADD NEW SUBSECTION 1.7.17.4.4 AFTER SUBSECTION 1.7.17.4.3 AS FOLLOWS:
24		THE STANDBY FIRE PERSONNEL SHALL HAVE THE ABILITY TO COMMUNICATE WITH
25		THE HOWARD COUNTY POLICE DEPARTMENT, DIVISION OF COMMUNICATIONS (911
26		Center).
27	(31)	SUBSECTION 1.7.17.4.5
28		ADD NEW SUBSECTION 1.7.17.4.5 AFTER SUBSECTION 1.7.17.4.4 AS FOLLOWS:
29		STANDBY FIRE PERSONNEL SHALL MAINTAIN A LOG EVERY HOUR AND SHALL NOTE
30		THE AREA CHECKED, THE TIME IT WAS CHECKED AND BY WHOM. THE LOG SHALL BE

1		MAINTAINED ON THE PREMISES AND, WHERE REQUIRED BY THE AHJ, A COPY
2		FORWARDED TO THE AHJ BY A METHOD PRESCRIBED BY THE AHJ.
3	(32)	Subsection 1.7.17.4.6
4		ADD NEW SUBSECTION 1.7.17.4.6 AFTER SUBSECTION 1.7.17.4.5 AS FOLLOWS:
5		The property owner shall designate the lesser of either (1) one person
6		PER $100,000$ SQ. FT. OF BUILDING SPACE; OR (2) ONE PERSON FOR EVERY FIVE (5)
7		floors. The AHJ may require additional standby fire personnel. When
8		MULTIPLE PERSONNEL ARE REQUIRED, THEY SHALL HAVE THE ABILITY TO
9		COMMUNICATE WITH EACH OTHER.
10	(33)	Subsection 1.7.17.4.7
11		ADD NEW SUBSECTION 1.7.17.4.7 AFTER SUBSECTION 1.7.17.4.6 AS FOLLOWS:
12		In the event of an emergency, the standby fire personnel shall:
1.3		(1) EVACUATE THE OCCUPANTS;
14		(2) CALL 911 AND REPORT THE EMERGENCY AND PROVIDE AN EXACT BUILDING
1.5		ADDRESS AND LOCATION OF SMOKE OR FIRE;
16		(3) NOTIFY OTHER STANDBY FIRE PERSONNEL;
17		(4) ACTIVATE THE IMPAIRED FIRE ALARM AND/OR SPRINKLER SYSTEM IF
18		POSSIBLE; AND
19	•	(5) DIRECT RESPONDING FIRE PERSONNEL TO THE SMOKE/FIRE AREA.
20	(34)	SUBSECTION 1.7.17.5
21		ADD NEW SUBSECTION 1.7.17.5 AFTER SUBSECTION 1.7.17.4 AS FOLLOWS:
22		A PERSON FAILING TO PROVIDE APPROVED STANDBY FIRE PERSONNEL (FIRE WATCH)
23		OR FAILING TO CARRY OUT THE DUTIES OF STANDBY FIRE PERSONNEL IS GUILTY OF
24		A MISDEMEANOR AND, UPON CONVICTION, IS SUBJECT TO A FINE NOT EXCEEDING
25		\$1,000.00 or imprisonment not exceeding 30 days or both. Alternatively,
26		AND IN ADDITION TO AND CONCURRENT WITH ALL REMEDIES PROVIDED AT LAW OR
27		EQUITY, A FIRE OFFICIAL MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES
28		pursuant to title 24, "civil penalties," of the Howard County Code. A
29		VIOLATION OF THIS SECTION IS A CLASS A OFFENSE. EACH DAY THAT A VIOLATION
30		CONTINUES IS A SEPARATE OFFENSE.

1	(35)	SUBSECTION 1.8.1.1
2		ADD NEW SUBSECTION 1.8.1.1 AFTER SUBSECTION 1.8.1 AS FOLLOWS:
3		THE INCIDENT COMMANDER HAS ADDITIONAL POWERS SET FORTH IN SECTION
4		17.105 of the Howard County Code.
5	(36)	SECTION 1.9.3
6		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
7		Any suit brought against the AHJ or any other individual who the AHJ
8		HAS DELEGATED THE AUTHORITY TO ENFORCE THIS CODE BECAUSE OF AN ACT OR
9		OMISSION PERFORMED IN THE ENFORCEMENT OF THIS CODE OR OTHER PERTINENT
10		LAW IMPLEMENTED THROUGH THE ENFORCEMENT OF THIS CODE OR ENFORCED BY
11		THE AHJ SHALL BE DEFENDED BY HOWARD COUNTY IN ACCORDANCE WITH
12		Maryland law and the Howard County Code.
13	(37)	SECTION 1.10
14		DELETE THIS SECTION IN ITS ENTIRETY.
15	(38)	SECTION 1.11
16		DELETE THIS SECTION IN ITS ENTIRETY.
17	(39)	SUBSECTION 1.12.1.1
18		ADD SUBSECTION 1.12.1.1 AFTER SUBSECTION 1.12.1 AS FOLLOWS:
19		The AHJ may adopt regulations governing the issuance of any permit,
20		CERTIFICATE, OR APPROVAL REQUIRED BY LAW. A PERMIT REQUIRED BY A STATE OR
21		OTHER COUNTY AGENCY SHALL BE OBTAINED AND A PERMIT REQUIRED BY THE
22		HOWARD COUNTY DEPARTMENT OF INSPECTIONS, LICENSES AND PERMITS SHALL
23		BE OBTAINED FOR THE CONSTRUCTION, RENOVATION, OR ALTERATION OF ANY
24		BUILDING, STRUCTURE, AREA, OR FIRE PROTECTION EQUIPMENT.
25	(40)	Subsection 1.12.6.13
26		In the first line, delete "permits shall" and substitute "permits may".
27	(41)	SECTION 1.12.8
28		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
29		A PERMIT FOR A HAZARDOUS MATERIAL IS REQUIRED IN ACCORDANCE WITH TABLE
30		1.12.8(a) through Table $1.12.8$ (d), and for a hazardous material
31		IDENTIFIED IN SUBSECTION 60.1.1.1 OF THIS CODE.

1	(42)	SECTI	ON 1.13.2
2		In th	e section title, delete "Mandatory". In the first sentence, delete
3		"SHAI	LL" AND SUBSTITUTE "MAY".
4	(43)	SUBSI	ECTION 1.13.12.4
5		DELE	TE THIS SECTION.
6	(44)	SECTI	TON 1.14.1
7		DELE	TE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
8		WHE	N REQUESTED BY THE DEPARTMENT OF INSPECTIONS, LICENSES AND PERMITS
9		OR OT	THER GOVERNMENT AUTHORITIES, THE AHJ SHALL ASSIST IN THE PLAN
10		REVIE	W OF NEW CONSTRUCTION, MODIFICATIONS, ALTERATIONS, AND THE
11		INSTA	LLATION OF EQUIPMENT. THE AHJ MAY REQUIRE CONSTRUCTION
12		DOCU	MENTS AND SHOP DRAWINGS TO BE SUBMITTED, REVIEWED, AND APPROVED
13		BY TH	IE AHJ PRIOR TO THE START OF SUCH WORK.
14	(45)	SUBSI	ECTION 1.15.1.1
15		Add	NEW SUBSECTION 1.15.1.1 AFTER SUBSECTION 1.15.1 AS FOLLOWS:
16		Circu	JMSTANCES THAT MAY REQUIRE A THIRD-PARTY REVIEW INCLUDE BUT ARE
17		NOT L	IMITED TO:
18		(1)	A person requests an equivalent method, alternative, or
19			MODIFICATION TO A CODE REQUIREMENT; OR
20		(2)	THERE IS INSUFFICIENT EVIDENCE OF COMPLIANCE WITH THE CODE ON
21			TECHNICAL MATTERS, USES, OPERATIONS, OR EQUIPMENT.
22	(46)	SECTI	ON 1.16.1
23		DELE	TE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
24		Noth	IING IN THIS SECTION SHALL PREVENT ENFORCEMENT OF THIS CODE USING
25		ANY (OTHER MEANS PROVIDED BY LAW, INCLUDING EQUITABLE AND CRIMINAL
26		ENFO	RCEMENT. EXCEPT IN THE CASE OF A CLASS A OFFENSE AND AS SET FORTH IN
27		SUBSI	ection $1.16.2.1$ of this Code, if the AHJ determines that a violation of
28		THIS (Code exists, the AHJ shall issue a written notice of violation. Any
29		VIOLA	ATION THAT HAS NOT BEEN ABATED WITHIN THE TIME SPECIFIED BY THE $ m AHJ$
30		SHAL	L BE A CLASS A VIOLATION FOR FAILURE TO ABATE, PURSUANT TO
21		. CI IDCI	ECTION $17.104(c)(24)$ of this section

1	(47)	Subsection 1.1	16.1.1
2		ADD NEW SUBS	ECTION 1.16.1.1 AFTER SUBSECTION 1.16.1 AS FOLLOWS:
3		THE FIRE OFFIC	cial may issue a citation authorized by title 24 of the
4		Howard Coun	TY CODE WITHOUT ISSUING A NOTICE OF VIOLATION FIRST FOR ANY
5		CLASS A OFFEN	ISE. WITHOUT LIMITATION, A VIOLATION OF ANY OF THE FOLLOWING
6		PROVISIONS OF	this Code is a Class A offense:
7		(1) Section	n 1.7.7, Inspections;
8		(2) Section	n 1.7.9, Interference with enforcement;
9		(3) SECTION	n 1.7.10, Impersonation;
10		(4) Section	n 1.7.11, Investigation;
11		(5) SECTION	n 1.7.15, Stop work order;
12		(6) Section	n 1.7.16, Imminent dangers and evacuation;
13		(7) SECTION	n 1.7.17, Standby and fire watch personnel;
14		(8) SECTION	n 1.16.1, Failure to abate;
15		(9) SECTION	n 4.4.3, Means of egress;
16		(10) SECTION	n 10.2.8, Reckless endangerment;
17		(11) SECTION	ns 13.1.2, 13.1.6.1, 13.1.8, 13.1.9, and 13.1.15 Regarding fire
18		PROTEC	TION SYSTEMS;
19		(12) SECTION	n 14.4, Means of egress reliability;
20		(13) SECTION	n 18.2.3.6, Marking of fire apparatus access roads and fire
21		LANES;	
22		(14) SECTION	n 20.1.5.8.3, Regarding exceeding occupancy limits;
23		(15) SECTION	n 60.1, Hazmat permitting; or
24		(16) Снарте	er 65, Regarding explosives, fireworks, flame effects
25		BEFORE	AUDIENCE AND MODEL ROCKETRY.
26	(48)	SUBSECTION 1.	16.2.1
27		DELETE THIS SE	ECTION AND SUBSTITUTE WITH THE FOLLOWING:
28		WHERE A NOTIO	CE OF VIOLATION IS REQUIRED, IT MAY BE SERVED IN ONE OF THE
29		FOLLOWING ME	THODS:
30		(1) PERSON	JAL SERVICE;
31		(2) Electr	ONIC DELIVERY;

1		(3) CERTIFIED OR REGISTERED MAIL, RESTRICTED DELIVERY, RETURN RECEIPT
2		REQUESTED;
3		(4) First class mail to the last known address of the alleged
4		VIOLATOR; OR
5		(5) When service cannot be obtained by one of these methods, a copy
6		OF THE NOTICE OF VIOLATION MAY BE POSTED IN A CONSPICUOUS PLACE ON
7		THE PROPERTY.
8	(49)	Subsection 1.16.2.2
9		DELETE THIS SUBSECTION IN ITS ENTIRETY.
10	(50)	SUBSECTION 1.16.4.3
11		DELETE THIS SUBSECTION.
12	(51)	SECTION 1.16.6
13		ADD NEW SECTION 1.16.6 AFTER SECTION 1.16.5 AS FOLLOWS:
14		When there is any violation of this subtitle, this Code, or any action
15		TAKEN UNDER THIS CODE, THE FIRE OFFICIAL MAY INSTITUTE APPROPRIATE ACTION
16		TO PREVENT, ENJOIN, ABATE, OR REMOVE THE VIOLATION. ALTERNATIVELY, AND IN
17		ADDITION TO AND CONCURRENT WITH ALL OTHER REMEDIES PROVIDED BY LAW,
18		THE FIRE OFFICIAL MAY ENFORCE THIS SUBTITLE AND THIS CODE BY THE USE OF
19		civil penalties pursuant to title 24, "civil penalties," of the Howard
20		COUNTY CODE. A VIOLATION OF THIS CODE IS A CLASS C OFFENSE EXCEPT AS
21		OTHERWISE SPECIFIED IN THIS CODE.
22	(52)	Subsection 1.16.6.1
23		ADD NEW SUBSECTION 1.16.6.1 AFTER SECTION 1.16.6 AS FOLLOWS:
24		If a person refuses or fails to comply with any provision of this subtitle,
25		OR TO CORRECT A VIOLATION WITHIN THE TIME SPECIFIED IN THE NOTICE OF
26		VIOLATION, OR AN IMMINENT DANGER EXISTS, THE FIRE OFFICIAL MAY PETITION
27		THE COURT FOR AN ORDER PERMITTING ENTRY UPON THE PROPERTY TO ABATE THE
28		VIOLATION AT THE OWNER'S EXPENSE OR TO TAKE CUSTODY OF UNLAWFUL
29		HAZARDOUS MATERIALS.
30	(53)	SECTION 1.17
31		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:

1		AUTHORITY TO ADOPT FEES. THE COUNTY COUNCIL MAY ADOPT BY RESOLUTION A
2		SCHEDULE OF FEES FOR SERVICES PERFORMED BY THE AHJ INCLUDING, WITHOUT
3		LIMITATION, ISSUING PERMITS AND PERFORMING INSPECTIONS, AND FOR OTHER
4		SERVICES PERFORMED PURSUANT TO THIS CODE.
5	(54)	SECTION 2.1
6		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
7		GENERAL. THE DOCUMENTS LISTED IN THIS CHAPTER ARE REQUIREMENTS OF THIS
8		CODE AS IF THEY WERE FULLY SET FORTH IN THIS CODE, EXCEPT FOR THE:
9		(1) NFPA 5000, Building Construction and Safety Code 2021 Edition;
10		(2) NFPA 54, NATIONAL FUEL GAS CODE, 2021 EDITION; AND
11		(3) NFPA 70, NATIONAL ELECTRIC CODE, 2020 EDITION.
12	(55)	Section 2.1.1 and Subsections 2.1.1.1 and 2.1.1.2
13		AMEND EACH TO REPLACE "COMPLIANCE" WITH "WHERE PERMITTED BY THE AHJ,
14		COMPLIANCE".
15	(56)	SECTION 2.1.2
16		ADD NEW SECTION 2.1.2 AFTER SECTION 2.1.1 AS FOLLOWS:
17		EXCEPT FOR SPECIFIC TEXT EXTRACTED FROM NFPA 1, A REFERENCE IN THIS CODE
18		to "NFPA 5000, Building Construction and Safety Code 2021 Edition"
19		MEANS THE HOWARD COUNTY BUILDING CODE ADOPTED IN TITLE 3, SUBTITLE 1 OF
20		the Howard County Code.
21	(57)	SECTION 2.1.3
22		ADD NEW SECTION 2.1.3 AFTER SECTION 2.1.2 AS FOLLOWS:
23		EXCEPT FOR SPECIFIC TEXT EXTRACTED FROM NFPA 1, A REFERENCE IN THIS CODE
24		to "NFPA 54, National Fuel Gas Code, 2021 Edition" means the Howard
25		County Plumbing and Gasfitting Regulations adopted in title 3, subtitle
26		3 of the Howard County Code.
27	(58)	SECTION 2.1.4
28		ADD NEW SECTION 2.1.4 AFTER SECTION 2.1.3 AS FOLLOWS:
29		EXCEPT FOR SPECIFIC TEXT EXTRACTED FROM NFPA 1, A REFERENCE IN THIS CODE
30		to "NFPA 70, National Electrical Code, 2020 edition" means the Howard

1		County Electrical Code adopted in title 3, subtitle 2 of the Howard
2		COUNTY CODE.
3	(59)	SECTION 2.2
4		Delete the referenced publication NFPA 150 Standard on Fire and Life
5		SAFETY IN ANIMAL HOUSING FACILITIES, AS AMENDED.
6	(60)	SECTION 3.2.2
7		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
8		AUTHORITY HAVING JURISDICTION (AHJ). FOR THE PURPOSES OF THIS CODE THE
9		AUTHORITY HAVING JURISDICTION IS THE HOWARD COUNTY DEPARTMENT OF FIRE
10		AND RESCUE SERVICES.
11	(61)	Subsection 3.2.8.1
12		ADD NEW SUBSECTION 3.2.8.1 AFTER SECTION 3.2.8. AS FOLLOWS:
13		MAY. MAY IS PERMISSIVE AND DISCRETIONARY. WHEN THIS CODE STATES "THE
14		AHJ MAY REQUIRE" INDICATES A REQUIREMENT, PROVISION, OR PRACTICE THAT
15		can be mandated by the AHJ depending upon the situation or
16		CIRCUMSTANCES.
17	(62)	SECTION 3.3.2
18		AT THE END OF THIS SECTION, ADD THE FOLLOWING:
19		THE AHJ SHALL SPECIFY THE TYPE OF BOX, DEVICE, OR SYSTEM.
20	(63)	Subsection 3.3.14.10.1
21		ADD SUBSECTION 3.3.14.10.1 AFTER SUBSECTION 3.3.14.10:
22		Consumer fireworks retail sales area. The portion of a consumer
23		FIREWORKS RETAIL SALES FACILITY OR STORE, INCLUDING THE IMMEDIATELY
24		ADJACENT AISLES, WHERE CONSUMER FIREWORKS ARE LOCATED FOR THE PURPOSE
25		OR RETAIL DISPLAY AND SALE TO THE PUBLIC.
26	(64)	SECTION 3.3.19A
27		ADD NEW SECTION 3.3.19A AFTER SECTION 3.3.19 AS FOLLOWS:
28		BARBECUE GRILL. EQUIPMENT USED FOR OUTDOOR COOKING THAT USES
29		ELECTRICITY, CHARCOAL, LIQUID PROPANE GAS, NATURAL GAS, OR OTHER FUEL FOR
30		ITS HEAT SOURCE.
31	(65)	SECTION 3.3.34A

1		ADD NEW SECTION 3.3.34A AFTER SECTION 3.3.34 AS FOLLOWS:
2		BULKHEAD DOOR. A TYPE OF DOOR ASSEMBLY COVERING AN OPENING IN THE
3		GROUND THAT PROVIDES DIRECT ACCESS TO A BASEMENT, THE FLOOR OF WHICH IS
4		Not more than 8 feet below ground level. The door consists of either ${\tt A}$
5		SINGLE RIGID LEAF OR TWO OVERLAPPING RIGID LEAVES OR COVERS THAT NEED TO
6		BE PUSHED OR LIFTED UPWARD IN ORDER TO BE OPENED. AFTER OPENING THE
7		door, a person can walk up a series of steps to escape to the outside. ${ m A}$
8		BULKHEAD DOOR IS ALSO CALLED A HURRICANE DOOR.
9	(66)	Subsection 3.3.56.2
10		Delete "2.2" and substitute "2.1.4".
11	(67)	Subsection 3.3.56.3
12		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
13		A reference in this Code to the "Mechanical Code" means the
14		International Mechanical Code adopted pursuant to title 3, subtitle 1
15		of the Howard County Code.
16	(68)	Subsection 3.3.56.4
17		Delete "2.2" and substitute "2.1.3".
18	(69)	SECTION 3.3.125
19		AT THE END OF THIS SECTION ADD "A USE-IN-COMMON DRIVEWAY, ACCESS PLACE
20		ROAD, OR FIRE DEPARTMENT APPARATUS ACCESS ROAD SERVING MORE THAN ONE
21		SINGLE FAMILY DWELLING MAY BE CONSIDERED A FIRE APPARATUS ACCESS ROAD
22		OR FIRE LANE."
23	(70)	SECTION 3.3.131
24		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
25		FIRE LANE. A FIRE APPARATUS ACCESS ROAD, CURB, ROADWAY OR PORTION OF A
26		ROADWAY THAT IS DESIGNATED BY THE AHJ as required for access by
27		EMERGENCY VEHICLES AND THAT IS MARKED WITH APPROVED SIGNS OR OTHER
28		NOTICES IN ACCORDANCE WITH THIS CODE.
29	(71)	SECTION 3.3.136
30		Amend this section to add "and as referenced in Public Safety Article,
31		§10-101, Annotated Code of Maryland, or as determined by the AHJ."

1	(72)	SUBSECTION 3.3.136.1
2		Amend this subsection to add "and as referenced in Public Safety
3		ARTICLE, §10-101, ANNOTATED CODE OF MARYLAND, OR AS DETERMINED BY THE
4		АНЈ."
5	(73)	SECTION 3.3.166
6		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
7		Imminent danger. A condition, use, or practice in an occupancy,
8		STRUCTURE, SITE, OR AREA THAT POSES A HAZARD OR DANGER THAT COULD
9		REASONABLY BE EXPECTED TO CAUSE DEATH, PHYSICAL INJURY, OR DAMAGE TO
10		PROPERTY.
11	(74)	SECTION 3.3.175A
12		ADD NEW SECTION 3.3.175A AFTER SECTION 3.3.175 AS FOLLOWS:
13		LIFE SAFETY EVALUATION. A WRITTEN REVIEW DEALING WITH THE ADEQUACY OF
14		LIFE SAFETY FEATURES RELATIVE TO FIRE, STORM, COLLAPSE, CROWD BEHAVIOR,
15		AND OTHER RELATED SAFETY CONSIDERATIONS.
16	(75)	SECTION 3.3.178A
17		ADD NEW SECTION 3.3.178A AFTER SECTION 3.3.178 AS FOLLOWS:
18		LOCK-UP. EXCEPT IN A DETENTION OR CORRECTIONAL OCCUPANCY, AN AREA
19		WHERE OCCUPANTS ARE RESTRAINED AND MOSTLY INCAPABLE OF SELF-
20		PRESERVATION BECAUSE OF SECURITY MEASURES THAT ARE NOT UNDER THE
21		OCCUPANT'S CONTROL.
22	(76)	Subsection 3.3.199.6
23		DELETE THIS SUBSECTION.
24	(77)	Subsection 3.3.199.7
25		Delete "four or more".
26	(78)	Subsection 3.3.199.7.1
27		ADD NEW SUBSECTION 3.3.199.7.1 AFTER SUBSECTION 3.3.199.7 AS FOLLOWS:
28		Family day care home. A day care home, generally within a dwelling
29		unit, in which 8 or fewer clients receive care, maintenance, and
30		SUPERVISION BY AN INDIVIDUAL OTHER THAN A RELATIVE OR LEGAL GUARDIAN
31		for less than 24 hours per day.

1	(79)	SUBSECTION 3.3.199.7.2
2		ADD NEW SUBSECTION 3.3.199.7.2 AFTER SUBSECTION 3.3.199.7.1 AS FOLLOWS:
3		GROUP DAY CARE HOME. A DAY CARE HOME, GENERALLY WITHIN A DWELLING
4		unit, in which not less than 9 , but not more than 12 , clients receive care,
5		MAINTENANCE, AND SUPERVISION BY AN INDIVIDUAL OTHER THAN A RELATIVE OR
6		legal guardian for less than 24 hours per day.
7	(80)	SUBSECTION 3.3.199.7.3
8		ADD NEW SUBSECTION 3.3.199.7.3 AFTER SUBSECTION 3.3.199.7.2 AS FOLLOWS:
9		Day care center. A day care occupancy in which more than 12 clients
10		RECEIVE CARE, MAINTENANCE, AND SUPERVISION BY AN INDIVIDUAL OTHER THAN A
11		relative or legal guardian, for less than 24 hours per day.
12	(81)	SUBSECTION 3.3.199.17
13		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
14		LODGING OR ROOMING HOUSE. A BUILDING OR PORTION OF A BUILDING THAT:
15		(1) Does not qualify as a one- or two-family dwelling;
16		(2) Provides sleeping accommodations for 6 or more people but not
17		more than 16 people on a transient or permanent basis;
18		(3) Does not provide personal care services;
19		(4) MAY OR MAY NOT PROVIDE MEALS; AND
20		(5) Does not have separate cooking facilities for individual
21		OCCUPANTS.
22	(82)	Subsections 3.3.199.25 and 3.3.199.25.1
23		Amend these subsections to delete "three" and substitute "five" and
24		DELETE", IF ANY, ACCOMMODATED IN RENTED ROOMS".
25	(83)	SUBSECTION 3.3.199.28
26		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
27		RESIDENTIAL BOARD AND CARE OCCUPANCY. A BUILDING OR PORTION OF A
28		BUILDING THAT IS USED FOR LODGING AND BOARDING OF SIX OR MORE RESIDENTS,
29		NOT RELATED BY BLOOD OR MARRIAGE TO THE OWNER OR OPERATOR, FOR THE
30		PURPOSE OF PROVIDING PERSONAL CARE SERVICES.
31	(84)	SECTION 3.3.215A

1		ADD NEW SECTION 3.3.215A AFTER SECTION 3.3.215 AS FOLLOWS:
2		Person:
3		(1) AN INDIVIDUAL, CORPORATION, FIRM, PARTNERSHIP, ASSOCIATION,
4		ORGANIZATION, OR ANY OTHER GROUP ACTING AS A UNIT; OR
5		(2) AN EXECUTOR, ADMINISTRATOR, TRUSTEE, RECEIVER, OR OTHER
6		REPRESENTATIVE APPOINTED ACCORDING TO LAW.
7	(85)	SECTION 3.3.235
8		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
9		RECREATIONAL FIRE. THE OUTSIDE OPEN BURNING OF ANY MATERIAL FOR
10		PLEASURE, RELIGIOUS, CEREMONIAL, COOKING, OR SIMILAR PURPOSES THAT IS
11		SUBJECT TO THE RULES AND REGULATIONS SET FORTH BY THE AHJ.
12	(86)	SUBSECTION 4.4.3.1.4
13		ADD NEW SUBSECTION 4.4.3.1.4 AFTER SUBSECTION 4.4.3.1.3 AS FOLLOWS:
14		VISUAL OBSCURATION SYSTEMS ASSOCIATED WITH SECURITY OR BURGLAR ALARM
15		SYSTEMS ARE NOT PERMITTED.
16	(87)	SUBSECTION 4.5.8.1
17		AMEND THIS SECTION TO DELETE "FOR COMPLIANCE WITH THE PROVISIONS OF THIS
18		Code".
19	(88)	SUBSECTION 4.5.8.3
20		AMEND THIS SECTION TO DELETE "BY THE CODE".
21	(89)	SUBSECTION 6.1.8.1.1
22		AMEND THIS SECTION TO DELETE "THREE" AND SUBSTITUTE "FIVE" AND TO DELETE
23		", IF ANY ACCOMMODATED IN RENTED ROOMS".
24	(90)	Subsection 6.1.9.1
25		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
26		RESIDENTIAL BOARD AND CARE OCCUPANCY. A BUILDING OR PORTION OF A
27		BUILDING THAT IS USED FOR LODGING AND BOARDING OF SIX OR MORE RESIDENTS,
28		NOT RELATED BY BLOOD OR MARRIAGE TO THE OWNER OR OPERATOR, FOR THE
29		PURPOSE OF PROVIDING PERSONAL CARE SERVICES.
30	(91)	SECTION 10.1.2

1		Amend this section to add "except as amended by title 17 , subtitle 1 ,
2		Section 17.104 of the Howard County Code"
3	(92)	SUBSECTION 10.1.2.1
4		ADD NEW SUBSECTION $10.1.2.1$ AFTER SUBSECTION $10.1.2$ AS FOLLOWS:
5		When provisions of the Life Safety Code (NFPA 101) conflict with this
6		CODE, THE MORE RESTRICTIVE REQUIREMENTS SHALL APPLY.
7 .	(93)	SECTION 10.2.7
8		Delete this subsection as well as Table 10.2.7.1.
9	(94)	SECTION 10.2.8
10		ADD NEW SECTION 10.2.8 AFTER SECTION 10.2.7 AS FOLLOWS:
11		RECKLESS ENDANGERMENT. ANY PERSON WHO RECKLESSLY ENGAGES IN CONDUCT,
12		in violation of any provision of this Code, that creates a substantial
13		RISK OF DEATH OR SERIOUS PHYSICAL INJURY IS GUILTY OF A MISDEMEANOR AND,
14		upon conviction, is subject to a fine not exceeding $$1,000.00$ or
15		imprisonment not exceeding 30 days or both. Alternatively, or in
16		ADDITION TO AND CONCURRENT WITH ALL REMEDIES PROVIDED BY LAW OR EQUITY.
17		THE FIRE OFFICIAL MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES PURSUANT
18		TO TITLE 24 OF THE HOWARD COUNTY CODE. A VIOLATION OF EITHER SECTION IS A
19		CLASS A OFFENSE. EACH DAY THAT A VIOLATION CONTINUES IS A SEPARATE
20		OFFENSE.
21	(95)	SECTION 10.4.1
22		Delete section 10.4.1 and substitute the following:
23		Whenever a fire or emergency occurs in a building or there is a reason
24		TO BELIEVE A FIRE OR EMERGENCY EXISTS IN A BUILDING, THE BUILDING SHALL BE
25		IMMEDIATELY EVACUATED AND MAY NOT BE REOCCUPIED WITHOUT PERMISSION OF
26		THE FIRE OFFICIAL IN CHARGE. IF THE BUILDING IS PROVIDED WITH A MANUAL FIRE
27		WARNING SYSTEM, A PERSON WHO HAS KNOWLEDGE OF THE FIRE OR EMERGENCY
28		SHALL ACTIVATE THE MANUAL FIRE WARNING SYSTEM. COMPLETE EVACUATION IS
29		NOT REQUIRED WHEN ALTERNATIVE PROCEDURES HAVE BEEN DETAILED IN A FIRE
30		PLAN, INCLUDING A PLAN TO SHELTER IN PLACE THAT HAS BEEN APPROVED BY THE
31		АНЈ.

1	(96)	SECTION 10.4.2
2		Amend this subsection to delete "AHJ" and substitute "AHJ or incident
3		COMMANDER".
4	(97)	SECTION 10.9.5
5		ADD NEW SECTION 10.9.5 AFTER SECTION 10.9.4 AS FOLLOWS:
6		In addition to the requirements set forth in this section and
7		requirements for specific occupancies as set forth in this Code, the
8		REQUIREMENTS OF TITLE 12, SUBTITLE 6 OF THE HOWARD COUNTY CODE SHALL
9		APPLY.
10	(98)	SECTION 10.10.1
11		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
12		As allowed by the AHJ, all outdoor, open, recreational, cooking, and
13		similar fires shall meet the requirements of section 12.108 of the
14		HOWARD COUNTY CODE, AS WELL AS THE PROVISIONS OF THIS CHAPTER.
15	(99)	Subsection 10.10.1.1
16		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
17		Unless open flame devices or candles meet the following requirements,
18		A PERSON SHALL NOT USE OR ALLOW TO BE USED, OPEN FLAMES OR BURNING
19		CANDLES IN CONNECTION WITH ANY PUBLIC MEETING OR GATHERING FOR THE
20		PURPOSE OF DELIBERATION, ENTERTAINMENT, AMUSEMENT, INSTRUCTION,
21		EDUCATION, RECREATION, DISPLAY, OR SIMILAR PURPOSE IN ANY OCCUPANCY OPEN
22		TO THE PUBLIC, INCLUDING ASSEMBLY, BUSINESS, EDUCATIONAL, DAY CARE AND
23		OR MERCANTILE OCCUPANCIES. CANDLES OR OPEN FLAME DEVICES NOT MEETING
24		THE FOLLOWING REQUIREMENTS MAY BE USED IN CONNECTION WITH A WORSHIP
25		SERVICE IN ANY PLACE OF WORSHIP IF USED OR DISPOSED OF IN SUCH A MANNER AS
26		NOT TO CREATE A HAZARDOUS CONDITION, EMERGENCY, OR IMMINENT DANGER.
27		For a candle or device to be approved by the AHJ, the candle or device
28		SHALL MEET THE REQUIREMENTS SET FORTH BELOW AND ALL REFERENCED AND
29		APPLICABLE CODES.
30		(1) CANDLES, DISPOSABLE OR REFILLABLE FUEL CARTRIDGES, OR OTHER OPEN-
21		ELAME DECORATIVE LIGHTING SHALL NOT LISE CLASS I II OR III A LIOLUDS OR

1		LIQUEFIED PETROLEUM GASES (LPG). EXAMPLES INCLUDE, BUT ARE NOT
2		LIMITED TO THE FOLLOWING:
3		(A) CLASS I: GASOLINE, ALCOHOL, TURPENTINE;
4		(B) CLASS II: DIESEL FUEL, KEROSENE;
5		(C) CLASS IIIA: MINERAL OIL, LINSEED OIL, OIL BASED PAINTS; AND
6		(D) LIQUEFIED PETROLEUM GASES: PROPANE, BUTANE, BUTYLENES,
7		PROPYLENE.
8	(2)	EXCEPT FOR CANDLES, LIQUID OR SOLID FUELED LIGHTING DEVICES SHALL
9		HAVE A SELF-EXTINGUISHING CAPTIVE-FREE FLOATING SNUFFING DEVICE AND
10		SHALL NOT LEAK FUEL AT A RATE OF MORE THAN $\frac{1}{4}$ TEASPOON PER MINUTE IF
11		TIPPED OVER.
12	(3)	DEVICES OR HOLDERS SHALL BE CONSTRUCTED TO PREVENT THE SPILLING OF
13		LIQUID FUEL OR WAX AT THE RATE OF MORE THAN $\frac{1}{4}$ TEASPOON PER MINUTE
14		WHEN THE DEVICE OR HOLDER IS NOT IN AN UPRIGHT POSITION.
15	(4)	EXCEPT FOR UNITS THAT SELF-EXTINGUISH AND DO NOT SPILL FUEL OR WAX
16		At the rate of more than $\frac{1}{4}$ teaspoon per minute if tipped over,
17		DEVICES OR HOLDERS SHALL BE DESIGNED TO RETURN TO THE UPRIGHT
18		POSITION AFTER BEING TILTED TO AN ANGLE OF 45 DEGREES.
19	(5)	Except where openings on the sides are not more than $^3\!4$ of an inch in
20		DIAMETER, FLAMES OF CANDLES, DISPOSABLE OR REFILLABLE FUEL
21		CARTRIDGES, OR OTHER OPEN-FLAME DECORATIVE LIGHTING SHALL BE
22		ENCLOSED. THE OPENING ON THE TOP AND THE DISTANCE TO THE TOP SHALL
23		BE SUCH THAT A SINGLE LAYER OF TISSUE PAPER PLACED ON THE TOP WILL
24		Not ignite in $10\ \text{seconds}$ and the fuel container shall have no means
25		OF ADJUSTING THE HEIGHT OF THE FLAME.
26	(6)	EXCEPT WHERE AN OPEN FLAME DEVICE SELF-EXTINGUISHES IF THE DEVICE IS
27		TIPPED OVER, CHIMNEYS SHALL BE MADE OF NON-COMBUSTIBLE MATERIAL
28		AND SHALL BE SECURELY ATTACHED TO THE OPEN-FLAME DEVICE.
29	(7)	DISPOSABLE OR REFILLABLE LIQUID FUEL CARTRIDGES SHALL NOT BE UNDER
30		PRESSURE AND SHALL BE SAFELY SEALED FOR STORAGE. THE FUEL CONTAINER
31		SHALL BE SEALED SO THAT IT CANNOT BE REFILLED ON THE PREMISES AND SO

1		THAT THE BURNER ASSEMBLY CANNOT BE REMOVED FROM THE FUEL		
2		CONTAINER.		
3		(8) Chimney shades, if used, shall be made of non-combustible		
4		MATERIALS AND SECURELY ATTACHED TO THE OPEN-FLAME DEVICE HOLDER		
5		or chimney. The base, device, or holder and any decoration around		
6		OR NEAR THE BASE MUST BE NONCOMBUSTIBLE. DEVICES MUST BE LOCATED		
7		SO AS TO AVOID IGNITION OF ANY COMBUSTIBLES.		
8		(9) USED OR PREVIOUSLY BURNED CANDLES OR OTHER OPEN FLAME DEVICES		
9		MUST BE STORED OR DISPOSED OF IN A MANNER APPROVED BY THE AHJ. THIS		
10		INCLUDES, BUT IS NOT LIMITED TO, PLACING USED CANDLES STORED FOR		
11		FUTURE USE IN NON-COMBUSTIBLE STORAGE CONTAINERS AFTER THE CANDLE		
12		HAS COOLED. CANDLES BEING DISPOSED OF MUST BE PLACED IN NON-		
13		COMBUSTIBLE WASTE CONTAINERS.		
14	(100)	Subsections 10.10.1.2, 10.10.1.3 and 10.10.1.4		
15		DELETE THESE SUBSECTIONS.		
16	(101)	SECTION 10.10.2		
17		ADD "SKY LANTERNS," AFTER "CANDLES,"		
18	(102)	SECTION 10.10.4.1		
19		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:		
20		OPEN FIRES GREATER THAN 3 FT IN DIAMETER SHALL BE LOCATED NOT LESS THAN		
21		50 FT FROM ANY STRUCTURE AND MUST MEET ALL PROVISIONS SET FORTH BY THE		
22		AHJ. NO FIRES OVER 5 FT IN DIAMETER ARE ALLOWED UNLESS EXPRESS WRITTEN		
23		PERMISSION IS GRANTED BY THE AHJ AND THE HOWARD COUNTY BUREAU OF		
24		Environmental Health.		
25	(103)	SUBSECTION 10.10.4.3		
26		After "manner" insert " as referenced in 10.10.4.7".		
27	(104)	SUBSECTION 10.10.4.5		
28		ADD NEW SUBSECTION $10.10.4.5$ AFTER SUBSECTION $10.10.4.4$ AS FOLLOWS:		
29		FUEL FOR THE FIRE SHALL CONSIST ONLY OF SEASONED DRY FIREWOOD AND SHALL		
30		BE IGNITED WITH SOMETHING OTHER THAN A FLAMMABLE LIQUID SUCH AS A SMALL		
31		OUANTITY OF PAPER.		

1	(105)	SUBSECTION 10.10.4.6
2		Add new subsection $10.10.4.6$ after subsection $10.10.4.5$ as follows:
3		If severe winds are prevalent (greater than $10\mathrm{MPH}$), the fire may not be
4		IGNITED.
5	(106)	SUBSECTION 10.10.4.7
6		ADD NEW SUBSECTION 10.10.4.7 AFTER SUBSECTION 10.10.4.6 AS FOLLOWS:
7		Where the containment method as referenced in subsection 10.10.4.3 is
8		APPROVED BY THE AHJ, DEVICES INCLUDING, BUT NOT LIMITED TO, CHIMINEAS,
9		luminaries, and fire pits may be located no closer than 15 ft of any
10		STRUCTURE, BUT NOT ON ANY BALCONY OR UNDER ANY OVERHANGING PORTION.
11		While evaluating the specific device for approval of the reduced
12		distance, the AHJ shall determine whether subsections $10.10.4.5$ and
13		10.10.4.6 SHALL APPLY.
14	(107)	SUBSECTION 10.10.4.7.1
15		ADD NEW SUBSECTION 10.10.4.7.1 AFTER SUBSECTION 10.10.4.7 AS FOLLOWS:
16		Devices referenced in subsection $10.10.4.7$ that are part of the approved
17		ORIGINAL CONSTRUCTION SHALL BE EQUIPPED WITH SPARK ARRESTORS AND THE
18		FIRE AREA SHALL NOT EXCEED 3 FEET IN DIAMETER.
19	(108)	SUBSECTION 10.10.6.1
20		Amend this subsection and to delete " $10\mathrm{ft}$ " and substitute " $15\mathrm{ft}$ ".
21	(109)	SUBSECTION 10.10.6.1.1
22		ADD NEW SUBSECTION 10.10.6.1.1 AFTER SUBSECTION 10.10.6.1 AS FOLLOWS:
23		THE AHJ MAY APPROVE ELECTRIC GRILLS THAT DO NOT USE AN ALTERNATIVE
24		FUEL.
25	(110)	SECTION 10.10.7
26		DELETE THIS SECTION AND SUBSTITUTE:
27		Patio heaters with an open flame shall not be within 5 feet of an exit or
28		OPENING, OR USED IN A STRUCTURE OR ENCLOSED AREA. PATIO HEATERS WITH AN
29		OPEN FLAME SHALL BE SECURED, MAINTAINED, AND KEPT AWAY FROM
30		COMBUSTIBLES. THE USE OF ANY PATIO HEATER WITH AN OPEN FLAME SHALL BE IN

1		ACCO	RDANCE WITH MANUFACTURERS RECOMMENDATIONS. PROPANE FUELED		
2		PATIC	HEATERS SHALL ALSO MEET REQUIREMENTS IN 69.3.13 OF THE NFPA 1.		
3	(111)	SUBSE	SUBSECTION 10.11.1.1		
4		DELE	TE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:		
5		Тне с	OWNER OF A STRUCTURE SHALL DISPLAY ARABIC NUMBERS DESIGNATING THE		
6		ADDR	ess assigned to the structure by the Howard County Department of		
7		PLAN	NING AND ZONING.		
8		(1)	Numbers shall be at least four inches high for single-family		
9	•		DETACHED AND ATTACHED RESIDENCES AND SIX INCHES HIGH FOR		
10			COMMERCIAL, INDUSTRIAL, AND MULTI-FAMILY STRUCTURES.		
11		(2)	For new residential construction, where a common numeric		
12			ADDRESS IS USED FOR SEPARATE DWELLINGS IN A VERTICAL STACK OR		
13			COLUMN, AN ALPHABETIC IDENTIFIER MUST DESIGNATE EACH DWELLING OF		
14			THE STRUCTURE. THE LOWEST LEVEL OCCUPANCY SHALL ALWAYS BE		
15			ASSIGNED AS THE "A" UNIT. SUBSEQUENT OCCUPANCIES ABOVE SHALL		
16			PROCEED SEQUENTIALLY WITH ALPHABETIC DESIGNATIONS. ANY		
17			ALTERATION TO THIS CONFIGURATION MUST BE APPROVED IN WRITING BY		
18			тне АНЈ.		
19		(3)	In addition to the numbers required on a structure, where the		
20			STRUCTURE HAS MORE THAN ONE ADDRESS OR WHERE MORE THAN ONE		
21			STRUCTURE SHARE A COMMON ENTRY DRIVEWAY, NUMBERS SHALL		
22			DESIGNATE THE ADDRESSES IN SEQUENCE ON A SIGN POSTED AT THE ENTRY		
23			OR COMMON DRIVEWAY.		
24		(4)	The AHJ may require address identification to be located on more		
25			THAN ONE SIDE OF THE STRUCTURE.		
26		(5)	Address numbers at least 6 inches in height shall be installed on		
27			THE REAR ACCESS DOORS TO ALL COMMERCIAL ESTABLISHMENTS. THOSE		
28			DOORS WHICH ARE LOCATED INSIDE OF A MALL, OFFICE BUILDING OR		
29			SIMILAR SPACE WITH ASSIGNED SUITE NUMBERS SHALL HAVE THEIR SUITE		
30			Numbers posted with numerals or alphabet letters at least $2\frac{1}{2}$		
31			INCHES TALL.		

1		(6) WHERE NO ADDRESS HAS BEEN ASSIGNED BY THE HOWARD COUNTY
2		DEPARTMENT OF PLANNING AND ZONING, A PREMISES IDENTIFICATION
3		MEANS APPROVED BY THE AHJ SHALL BE USED FOR IDENTIFICATION
4		PURPOSES.
5		(7) IN ALL NEW RESIDENTIAL MULTI-FAMILY BUILDINGS HAVING TWO OR MORE
6		FLOORS, A UNIFORM NUMERIC SYSTEM SHALL BE UTILIZED TO IDENTIFY ALL
7		dwelling units with a number that is unique to only one unit. All
8		UNITS IN A VERTICAL STACK OR COLUMN SHALL BE UNIFORMLY NUMBERED
9		SUCH THAT THEY ALL SHARE A NUMERIC REFERENCE TO EACH OTHER IN
10		THAT STACK OR COLUMN, AS APPROVED BY THE AHJ. FOR EXAMPLE, UNIT
11	•	301 shall be directly over unit 201 , which is directly over unit
12		101. In the event an open or amenity space on any floor prevents
13		THIS UNIFORMITY, THE CORRESPONDING UNIT NUMBER SHALL BE OMITTED
14		RATHER THAN MOVED OUTSIDE OF THE NUMERICALLY UNIFORM COLUMN OF
15		STACK.
16	(112)	SUBSECTION 10.11.1.4
17		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
18		Where required by the AHJ, the assignment of addresses to buildings
19		SHALL BE IN ACCORDANCE WITH AN APPROVED METHOD.
20	(113)	SUBSECTION 10.11.1.5
21		AMEND THIS SUBSECTION TO DELETE "ADDRESS" AND SUBSTITUTE "WHERE
22		REQUIRED BY THE AHJ, ADDRESS".
23	(114)	SUBSECTION 10.11.1.7
24		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
25		Numbers shall be posted on a contrasting background and displayed in
26		A CONSPICUOUS PLACE THAT IS UNOBSTRUCTED AND CLEARLY VISIBLE FROM THE
27		STREET NAMED IN THE OFFICIAL ADDRESS OF THE STRUCTURE.
28	(115)	SUBSECTION 10.11.1.9
29		ADD NEW SUBSECTION 10.11.1.9 AFTER SUBSECTION 10.11.1.8 AS FOLLOWS:
30		Where required by the AHJ, symbols in compliance with NFPA 170
31		STANDARD FOR FIRE SAFETY AND EMERGENCY SYMBOLS SHALL BE USED.

1	(116)	Subsection 10.11.3.1
2		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
3		STAIRS SERVING THREE OR MORE STORIES SHALL COMPLY WITH 10.11.3.1.1
4		THROUGH 10.11.3.1.16.
5	(117)	SECTION 10.11.3.1.4
6		AMEND THIS SUBSECTION TO ADD "ALPHABETIC" BEFORE "IDENTIFICATION".
7	(118)	SECTION 10.11.3.1.4.1
8		ADD NEW SUBSECTION 10.11.3.1.4.1 AFTER SECTION 10.11.3.1.4 AS FOLLOWS:
9		AN ADDITIONAL AFFIXED SIGN SHALL BE PROVIDED ON THE EXTERIOR OF EACH
10		STAIRWELL DOOR AT THE GROUND LEVEL INDICATING THE ALPHABETIC
11		IDENTIFICATION OF THE STAIR ENCLOSURE PRECEDED BY THE WORD "STAIR".
12	(119)	SUBSECTION 10.12.2.1
13		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
14		Where the AHJ determines a life safety or other hazard exists, the AH.
15		MAY APPROVE FIRE PROTECTION AND FIRE ALARM SYSTEMS IN SEASONAL AND
16		VACANT BUILDINGS TO BE REMOVED FROM SERVICE. THIS APPROVAL SHALL BE IN
17		WRITING.
18	(120)	SECTION 10.12.4
19		ADD NEW SECTION 10.12.4 AFTER SECTION 10.12.3 AS FOLLOWS:
20		A BUILDING OR STRUCTURE IS A FIRE HAZARD IF THE BUILDING OR STRUCTURE OR
21		ANY PORTION OF THE BUILDING OR STRUCTURE IS VACANT AND UNSECURED.
22	(121)	SECTION 10.12.5
23		ADD NEW SECTION 10.12.5 AFTER SECTION 10.12.4 AS FOLLOWS:
24		THE AHJ MAY REQUIRE ALL UTILITIES TO BE DISCONNECTED IN A VACANT
25		BUILDING OR STRUCTURE.
26	(122)	SECTION 10.12.6
27		ADD NEW SECTION 10.12.6 AFTER SECTION 10.12.5 AS FOLLOWS:
28		THE AHJ MAY REQUIRE THE VACANT OR ABANDONED STRUCTURE TO BE MARKED
29		WITH SYMBOLS PROVIDED BY THE AHJ AT THE STRUCTURE'S FRONT DOOR THAT
30		SHALL INDICATE ONE OF THE FOLLOWING:
31		(1) VACANT—NORMAL STABILITY AT TIME OF MARKING;

1		(2) VAC	ANT—INTERIOR HAZARDS EXISTS TO SUCH A DEGREE THAT INTERIOR		
2		OPEF	RATIONS MAY BE CONDUCTED ONLY AFTER EXAMINATION, AND WITH		
3		EXT	REME CAUTION; OR		
4		(3) VAC	ANT—EVERY EFFORT MUST BE MADE TO CONDUCT OPERATIONS FROM		
5		THE	exterior. When absolutely necessary to enter the building,		
6		ADH	ERE TO THE FOLLOWING:		
7		(A)	Approval by the Officer in command is required;		
8		(B)	Examination must be conducted before unit is committed;		
9		(C)	OPERATING FORCE AND INTERIOR OPERATIONAL TIME TO BE KEPT TO		
10			A MINIMUM.		
11	(123)	SUBSECTION	10.13.2.1		
12		AFTER "HAZ	zard", insert ", in accordance with section 17.106 of the		
13		Howard Co	DUNTY CODE".		
14	(124)	SUBSECTION	10.14.1		
15		DELETE THI	DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:		
16		ALL SPECIA	ALL SPECIAL EVENTS SHALL COMPLY WITH THE REGULATIONS SET FORTH IN THE		
17		Howard Co	OUNTY CODE, TITLE 17, SUBTITLE 9. WHEN THE SPECIAL EVENT DOES		
18		NOT REQUIR	OT REQUIRE A PERMIT, AS SPECIFIED IN TITLE 17, SUBTITLE 9, THE ORGANIZER OR		
19		RESPONSIBL	e party shall notify the $A\mathrm{HJ}$ not less than twenty-one (21)		
20		DAYS PRIOR	TO THE EVENT FOR REVIEW OF COMPLIANCE WITH THIS CODE.		
21	(125)	SUBSECTION	10.14.12.2.6		
22		AMEND THIS	S SECTION TO DELETE "ANY VEHICLES" AND SUBSTITUTE "ANY		
23		VEHICLES, B	uildings,".		
24	(126)	SECTION 10.	15.5.1		
25		AMEND THIS	s section to delete "Portable" and substitute "Unless		
26		OTHERWISE	APPROVED BY THE AHJ, PORTABLE".		
27	(127)	SECTION 10.	16.1		
28		DELETE THI	S SECTION AND SUBSTITUTE THE FOLLOWING:		
29		OUTSIDE ST	ORAGE OF COMBUSTIBLE OR FLAMMABLE MATERIAL SHALL NOT BE		
30		LOCATED W	ithin 15 feet of a property line, building, structure, or		

1		ANYTI	hing determined as at risk by the AHJ. The volume of material shall		
2		NOT E	NOT EXCEED 2,500 CUBIC FEET.		
3	(128)	SUBSE	Subsection 10.16.1.1		
4		ADD N	NEW SUBSECTION 10.16.1.1 AFTER SECTION 10.16.1 AS FOLLOWS:		
5		THE A	.HJ may require the area of outside storage be enclosed by a		
6		SECUR	TITY FENCE AT LEAST SIX FEET IN HEIGHT.		
7	(129)	SUBSE	CCTION 10.16.1.2		
8		ADD N	NEW SUBSECTION $10.16.1.2$ AFTER SUBSECTION $10.16.1.1$ AS FOLLOWS:		
9		In Lim	IITED INSTANCES, OUTSIDE STORAGE OF FLAMMABLE MATERIAL WHICH		
10		EXCEE	ds $2{,}500$ cubic feet in volume may be permitted by the AHJ and shall		
11		MEET	THE REQUIREMENTS IN THIS CODE FOR THE STORAGE OF THE SPECIFIC		
12		MATEI	RIAL.		
13	(130)	SECTION	ON 10.16.2		
14		DELET	TE THIS SECTION.		
15	(131)	SECTIO	ON 10.16.3		
16		Add t	ADD THE FOLLOWING AT THE END OF THIS SECTION:		
17		THE S	THE SEPARATION DISTANCE MAY BE INCREASED WHERE THE AHJ DETERMINES		
18		THAT	A HAZARD TO THE ADJOINING PROPERTY EXISTS.		
19	(132)	SECTIO	ON 10.19.1		
20		DELET	TE THIS SECTION AND SUBSTITUTE THE FOLLOWING:		
21		Сомв	USTIBLE MATERIALS SHALL BE STORED IN THE FOLLOWING MANNER:		
22		(1)	Orderly;		
23		(2)	36 INCHES OR MORE FROM HEAT PRODUCING EQUIPMENT OR IN		
24			ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATION;		
25		(3)	SHALL NOT BE WITHIN 5 FEET OF AN OPENING TO THE BUILDING;		
26		(4)	When stored under a window, the window must contain approved		
27			FIRE GLASS;		
28		(5)	SHALL BE STORED IN PILES OR STACKS SMALLER THAN A CORD OF WOOD —		
29			4 FEET BY 4 FEET BY 8 FEET; AND		
30		(6)	SHALL NOT OBSTRUCT THE EXIT AND/OR THE EXIT DISCHARGE.		
31	(133)	SECTION	ON 10 10 7		

1		AFTER "	REPAIRED" INSERT "ON A BALCONY, UNDER ANY OVERHANGING PORTION,		
2		OR".			
3	(134)	SUBSECTION 11.1.1.1			
4		ADD NE	w subsection 11.1.1.1 after section 11.1.1 as follows:		
5		AN ELEC	TRICAL APPLIANCE, FIXTURE, OR CONSUMER PRODUCT SHALL NOT BE SOLD		
6		OR USED	UNLESS IT IS CLEARLY LABELED, MARKED, OR STAMPED WITH THE SYMBOL		
7		OF AN EI	ECTRICAL TESTING LABORATORY THAT IS CERTIFIED BY THE MARYLAND		
8		OFFICE (of the State Fire Marshal.		
9	(135)	SUBSECT	TION 11.1.1.2		
10		ADD NE	w subsection 11.1.1.2 after subsection 11.1.1.1 as follows:		
11		A MINIM	um clear space of 36 inches in width, 36 inches in depth, and 78		
12		INCHES I	N HEIGHT SHALL BE MAINTAINED IN FRONT OF ALL ELECTRICAL SERVICE		
13		EQUIPME	ENT. THE CLEAR SPACE SHALL BE MAINTAINED ON ALL SIDES OF THE		
14		EQUIPME	ENT IF ACCESS TO THESE AREAS IS REQUIRED. WHERE THE ELECTRICAL		
15		SERVICE	SERVICE EQUIPMENT IS WIDER THAN 36 INCHES, THE WORKING SPACE SHALL NOT BE		
16		LESS THA	less than the width of the equipment. Nothing shall be stored within		
17		DESIGNA	TED WORKING SPACES EXCEPT AS FOLLOWS:		
18		(1)	Where other dimensions are required or permitted by NFPA 70.		
19		(2) A	ACCESS OPENINGS IN ATTICS OR UNDER-FLOOR AREAS WHICH PROVIDE A		
20		N	minimum clear opening of 22 in by 30 in.		
21	(136)	SECTION	11.1.5.6		
22		DELETE	THIS SECTION AND SUBSTITUTE THE FOLLOWING:		
23		Extensi	ON CORDS SHALL NOT BE USED AS A SUBSTITUTE FOR PERMANENT WIRING.		
24	(137)	SUBSECT	TION 11.1.7.3.2		
25		ADD NEW SUBSECTION 11.1.7.3.2 AFTER SUBSECTION 11.1.7.3.1 AS FOLLOWS:			
26		Doors i	NTO ELECTRICAL CONTROL PANEL ROOMS SHALL BE MARKED WITH A		
27		PLAINLY	VISIBLE AND LEGIBLE SIGN STATING "ELECTRICAL ROOM" OR SIMILAR		
28		APPROVI	ED WORDING IN CONTRASTING LETTERS NOT LESS THAN 1 IN. (25 MM) HIGH		
29		AND NO	$_{\rm I}$ less than $^{1}\!\!/_{\! 4}$ in. (6.4 mm) in stroke width. The disconnecting means		
30		FOR EAC	H SERVICE, FEEDER, OR BRANCH CIRCUIT ORIGINATING ON A SWITCHBOARD		

1		OR PANEL BOARD SHALL BE LEGIBLY AND DURABLY MARKED TO INDICATE ITS
2		PURPOSE UNLESS SUCH PURPOSE IS CLEARLY EVIDENT.
3	(138)	SECTION 11.2.3
4		ADD NEW SUBSECTION 11.2.3 AFTER SUBSECTION 11.2.2 AS FOLLOWS:
5		ALL PUSH BUTTON TYPE HVAC SHUTOFFS SHALL BE BLUE IN COLOR AND SHALL
6		INCLUDE SIGNAGE TO INDICATE THE TYPE OF SHUTOFF.
7	(139)	SUBSECTION 11.3.6.1
8		Amend this section to add the following to the end: Keys for new
9		ELEVATORS SHALL BE CUT TO A UNIFORM KEY CODE TO COMPLY WITH THE
10		Maryland State Elevator Code.
11	(140)	SUBSECTION 11.3.6.3.1
12		Amend this subsection to add "or as determined by the AHJ" to the end.
13	(141)	SUBSECTION 11.3.6.3.1.3
14		Amend this subsection to add "or as determined by the AHJ " to the end.
15	(142)	SUBSECTION 11.3.6.3.1.5
16		Amend this subsection to delete the second "shall" and substitute
17		"MAY".
18	(143)	SUBSECTION 11.5.2.4
19		ADD NEW SUBSECTION 11.5.2.4 AFTER SUBSECTION 11.5.2.3 AS FOLLOWS:
20		KEROSENE HEATERS ARE PROHIBITED IN THE FOLLOWING OCCUPANCIES:
21		EDUCATIONAL, DAY CARE, HOTELS AND MOTELS, PLACES OF ASSEMBLY, HEALTH
22		CARE, BOARD AND CARE, ROOMING AND LODGING, MULTI-FAMILY RESIDENTIAL,
23		AND OTHER OCCUPANCIES OR SITUATIONS WHERE THE USE OR OPERATION OF
24		KEROSENE HEATERS COULD CREATE AN EMERGENCY OR IMMINENT DANGER.
25	(144)	SECTION 11.9.1
26		Amend this section to delete "approved by the Fire Department" and
27		SUBSTITUTE "APPROVED BY THE AHJ".
28	(145)	SECTION 11.10.11.1
29		AMEND THIS SECTION TO DELETE "SHALL BE CONDUCTED AS FOLLOWS:" AND
30		SUBSTITUTE "SHALL BE CONDUCTED AS FOLLOWS UNLESS OTHERWISE DIRECTED BY
31		THE AHI:"

1	(146)	SECTION 12.1		
2		ADD THE FOLLOWING TO THE END:		
3		This Code requires that the building construction, fire protection, and		
4		LIFE SAFETY FEATURES BE MAINTAINED BY THE OWNER TO FUNCTION AS INTENDED.		
5	(147)	SUBSECTION 12.3.3.1.1		
6		ADD NEW SUBSECTION 12.3.3.1.1 AFTER SUBSECTION 12.3.3.1 AS FOLLOWS:		
7		MISSING CEILING TILES SHALL BE REPLACED. PENETRATIONS, GAPS, HOLES, OR ANY		
8		OPENINGS IN CEILING, WALL, OR FLOOR ASSEMBLIES SHALL BE SEALED TO		
9		ELIMINATE THE POSSIBLE SPREAD OF SMOKE OR FIRE.		
10	(148)	Subsection 12.6.9.1.1		
11		AMEND THIS SUBSECTION TO:		
12		(1) Insert "Unless otherwise approved by the AHJ," at the beginning;		
13		AND		
14		(2) ADD THE FOLLOWING AFTER WITH: "THE GUIDELINES OF THE OFFICE OF THE		
15		Maryland State Fire Marshal, and".		
16	(149)	SUBSECTION 12.6.9.1.2		
17		ADD NEW SUBSECTION 12.6.9.1.2 AFTER SUBSECTION 12.6.9.1.1 AS FOLLOWS:		
18		THE AHJ SHALL BE PERMITTED TO: APPROVE THE PLACEMENT OF A NATURAL CUT		
19		OR BALLED TREE; LIMIT THE NUMBER OF NATURAL CUT OR BALLED TREES		
20		DISPLAYED; AND ORDER THE REMOVAL OF ANY TREE IF THE TREE POSSESSES A		
21		HAZARD TO LIFE OR SAFETY.		
22	(150)	SUBSECTION 12.6.9.5.3		
23		ADD NEW SUBSECTION 12.6.9.5.3 AFTER SUBSECTION 12.6.9.5.2 AS FOLLOWS:		
24		COMBUSTIBLE ARTIFICIAL DECORATIVE VEGETATION SHALL BE TESTED BY A		
25		LABORATORY RECOGNIZED BY THE OFFICE OF THE STATE FIRE MARSHAL.		
26	(151)	SUBSECTION 12.6.9.6.1		
27		Amend this section to delete " $\frac{1}{2}$ in. (13 mm)" and substitute "2 in. (50 mm)"		
28		AND ADD THE FOLLOWING SENTENCE: "A NATURAL CUT TREE SHALL NOT EXCEED		
29		$10\mathrm{FT.}$ (3 m) in height, excluding the tree stand."		
30	(152)	SECTION 13.1.2		
31		Before "testing" insert "installation,".		

1	(153)	SECTION 13.1.3.1
2		Amend this section to delete "by Chapters 11 through 43" and substitute
3		"by the AHJ and Chapters 11 through 43".
4	(154)	SECTION 13.1.3.2
5		Amend this section to delete "by $9.3.5$ " and substitute "by the AHJ or
6		9.3.5".
7	(155)	SECTION 13.1.5
8		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
9		EXCEPT FOR FIRE HYDRANTS IN A PUBLIC RIGHT-OF-WAY, A MINIMUM CLEAR SPACE
LO		OF 15 FEET IN DIAMETER (7.5 FEET ON ALL SIDES) SHALL BE MAINTAINED OUTSIDE
11		OF A BUILDING OR STRUCTURE TO PERMIT ACCESS TO AND OPERATION OF FIRE
.2		PROTECTION EQUIPMENT, FIRE DEPARTMENT INLET CONNECTIONS, OR FIRE
13		PROTECTION SYSTEM CONTROL VALVES. A MINIMUM CLEAR SPACE OF 3 FEET SHALL
.4		BE MAINTAINED ON INTERIOR VALVES AND EQUIPMENT. AN OBSTRUCTION OR
15		CONDITION THAT DETERS OR HINDERS ACCESS BY THE AHJ IS PROHIBITED.
.6	(156)	SUBSECTION 13.1.6.1
.7		ADD NEW SUBSECTION 13.1.6.1 AFTER SUBSECTION 13.1.6 AS FOLLOWS:
.8		EACH LICENSED COMPANY WORKING ON FIRE SAFETY EQUIPMENT SHALL FORWARD
.9		TO THE AHJ, ON THE PRESCRIBED FORM OR SYSTEM, A SEPARATE CERTIFICATE OF
20		INSPECTION, ALONG WITH THE APPROPRIATE FEES, FOR EACH FIRE SUPPRESSION
21		SYSTEM THAT THE LICENSED COMPANY MAY INSPECT, TEST OR MAINTAIN. THIS
22		CERTIFICATE OF INSPECTION SHALL BE SUBMITTED WITHIN 48 HOURS WHEN
23		CRITICAL DEFICIENCIES OR IMPAIRMENTS ARE FOUND, OR WITHIN FOURTEEN (14)
24		CALENDAR DAYS FOR ALL OTHER INSPECTION CLASSIFICATIONS. THE CERTIFICATE
25		SHALL VERIFY THAT THE AHJ STANDARDS AND SPECIFICATIONS REGARDING THE
16		INSPECTION, TESTING OR MAINTENANCE HAVE BEEN MET AND ANY DEFICIENCIES
27		NOTED AT THE TIME OF THE ANNUAL INSPECTION, TESTING OR MAINTENANCE SHALL
.8		BE NOTED, WITH ANY CORRECTIVE ACTION TAKEN.
.9	(157)	SECTION 13.1.14
10		ADD NEW SECTION 13 1 14 AFTER SECTION 13 1 13 AS FOLLOWS:

1		App	'EARANCE	E OF EQUIPMENT. THE AHJ SHALL BE PERMITTED TO PROHIBIT ANY		
2		DEV	ICE THAT HAS THE PHYSICAL APPEARANCE OF A LIFE SAFETY OR FIRE			
3		PRO	TECTION FUNCTION BUT DOES NOT PERFORM THAT LIFE SAFETY OR FIRE			
4		PRO	TECTION	FUNCTION.		
5	(158)	SEC	TION 13.1	7.15		
6		Adi	O NEW SU	BSECTION 13.1.15 AFTER SECTION 13.1.14 AS FOLLOWS:		
7		Exc	EPT FOR .	A PERSON PERFORMING INSTALLATION, MAINTENANCE, AND REPAIR, A		
8		PER	SON SHAL	L NOT TAMPER WITH OR RENDER INOPERABLE ANY FIRE PROTECTION		
9		OR I	LIFE SAFE	TY SYSTEM.		
10	(159)	SEC	TION 13.1	1.16		
11		Adi) NEW SU	BSECTION 13.1.16 AFTER SECTION 13.1.15 AS FOLLOWS:		
12		Uni	ESS OTHE	ERWISE APPROVED BY THE AHJ, THE FOLLOWING PROVISIONS SHALL		
13		APP	LY TO A F	IRE DEPARTMENT CONNECTION FOR FIRE PROTECTION SYSTEMS:		
14		(1)	A FIR	E DEPARTMENT CONNECTION FOR FIRE PROTECTION SYSTEMS SHALL		
15			BE:			
16			(A)	LOCATED ON THE SIDE OF THE STRUCTURE DISPLAYING THE		
17				ADDRESS CLEARLY VISIBLE TO RESPONDING FIRE DEPARTMENT		
18				UNITS;		
19			(B)	Marked in the manner required by this Code; and		
20			(C)	Located within 100 feet of a fire hydrant.		
21		(2)	THE APP	PROPRIATE SIGN SHALL BE MOUNTED ON THE BUILDING'S WALL		
22			BETWEE	in 8 and 12 feet above the fire department connection. If		
23			OBSTAC	LES OR CONDITIONS EXIST THAT HINDER THE VISIBILITY OF THE SIGN,		
24			тне АН	${ m J}$ may change the required mounting location.		
25		(3)	A FREE-	STANDING FIRE DEPARTMENT CONNECTION SHALL HAVE THE SIGN		
26			MOUNTE	ED ON A POLE DIRECTLY BEHIND THE CONNECTION APPROXIMATELY 6		
27			FEET HIC	эн.		
28		(4)	IF REQU	IRED BY THE AHJ, SIGNS SHALL HAVE A WHITE REFLECTIVE		
29			BACKGR	COUND WITH A RED REFLECTIVE BORDER, RED REFLECTIVE LETTERS		
30			AND A R	ED REFLECTIVE ARROW. THE BORDER SHALL HAVE A 3/8" STROKE. THE		
31			LETTERS	S SHALL READ "FDC" AND BE 6" HIGH WITH A 1" STROKE. THE ARROW		

1		SHALL HAVE A STROKE NOT LESS THAN 2". THE OVERALL SIGN
2		MEASUREMENTS SHALL BE 12" BY 18".
3		(5) Any obstruction or condition that deters or hinders access to a
4		FIRE DEPARTMENT CONNECTION IS PROHIBITED. A MINIMUM CLEAR SPACE OF
5		15 FEET (7.5 FEET ON ALL SIDES) SHALL BE MAINTAINED.
6	(160)	SECTION 13.1.17
7		ADD NEW SECTION 13.1.17 AFTER SECTION 13.1.16 AS FOLLOWS:
8		A VIOLATION OF EITHER SECTION 13.1.2, 13.1.6.1, 13.1.8, 13.1.9, OR 13.1.15 IS A
9		MISDEMEANOR AND, UPON CONVICTION, IS SUBJECT TO A FINE NOT EXCEEDING
10		\$1,000.00 or imprisonment not exceeding 30 days or both. Alternatively,
11		OR IN ADDITION TO AND CONCURRENT WITH ALL REMEDIES PROVIDED BY LAW OR
12		EQUITY, THE FIRE OFFICIAL MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES
13		PURSUANT TO TITLE 24 OF THE HOWARD COUNTY CODE. A VIOLATION OF EITHER
14		SECTION IS A CLASS A OFFENSE. EACH DAY THAT A VIOLATION CONTINUES IS A
15		SEPARATE OFFENSE.
16	(161)	SUBSECTION 13.2.2.1
17		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
18		Where required by this Code, the Building Code, or the referenced codes
19		AND STANDARDS LISTED IN CHAPTER 2, STANDPIPE SYSTEMS SHALL BE INSTALLED
20		IN ACCORDANCE WITH SECTION 13.2.1.
21	(162)	Subsection 13.2.2.2
22		ADD THE FOLLOWING AT THE END OF THIS SUBSECTION:
23		(6) In an automobile parking garage where the AHJ determines there
24		IS INADEQUATE FIRE SERVICE ACCESS.
25	(163)	SUBSECTION 13.2.3.1
26		ADD THE FOLLOWING AT THE END OF THIS SUBSECTION:
27		STANDPIPES DO NOT HAVE TO BE EQUIPPED WITH HOSE AND NOZZLE FOR FIRE
28		DEPARTMENT USE. HOWEVER, IF PROVIDED, THE HOSE AND NOZZLE SHALL BE
29		TESTED AND MAINTAINED.
30	(164)	SUBSECTION 13.3.1.1.1
31		ADD NEW SUBSECTION 13.3.1.1.1 AFTER SUBSECTION 13.3.1.1 AS FOLLOWS:

1		THE AHJ MAY REQUIRE A LIFE SAFETY EVALUATION TO BE COMPLETED AND
2		PERFORMED BY A QUALIFIED THIRD PARTY APPROVED BY THE AHJ.
3	(165)	SUBSECTION 13.3.1.2.1
4		ADD NEW SUBSECTION 13.3.1.2.1 AFTER SUBSECTION 13.3.1.2 AS FOLLOWS:
5		For new ceiling installations, drop-out ceilings as referenced in NFPA
6		13, subsections $9.2.16$ and $9.3.11$, shall be prohibited.
7	(166)	SUBSECTION 13.3.1.2.2
8		ADD NEW SUBSECTION 13.3.1.2.2 AFTER SUBSECTION 13.3.1.2.1 AS FOLLOWS:
9		The AHJ may require doors to sprinkler control rooms be marked in an
10		APPROVED MANNER.
11	(167)	SUBSECTION 13.3.2.2
12		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
13		In a new nonresidential building, a basement that is $2,500$ square feet or
14		MORE SHALL BE PROTECTED THROUGHOUT BY AN APPROVED AUTOMATIC
15		SPRINKLER SYSTEM. IN AN EXISTING NONRESIDENTIAL BUILDING, A BASEMENT
16		exceeding 2,500 square feet shall contain an automatic sprinkler
17		SYSTEM WHEN A LIFE SAFETY EVALUATION IS COMPLETED AND THE AHJ
18		DETERMINES, BASED ON THE LIFE SAFETY EVALUATION THAT AN IMMINENT DANGER
19		EXISTS.
20	(168)	SECTION 13.3.2.6.1
21		AMEND THIS SUBSECTION TO DELETE "THE FOLLOWING OCCUPANCIES" AND
22		substitute "The following occupancies having an occupant load of 100
23		or more persons, or $5,000$ or more square feet in area, or located on a
24		FLOOR OTHER THAN THE LEVEL OF EXIT DISCHARGE".
25	(169)	SUBSECTION 13.3.2.6.2
26		Delete "exceeds 300" and substitute "is 100 or more,".
27	(170)	SUBSECTION 13.3.2.6.3
28		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
29		The requirements of 13.3.2.6.2 shall not apply to the following:

1		(1)	AN AS	SSEMBLY OCCUPANCY AT THE LEVEL OF EXIT DISCHARGE THAT IS LESS
2			THAN	$5,\!000$ square feet in area and that has an occupant load of
3			LESS T	than 100 persons;
4		(2)	A GYN	MNASIUM, SKATING RINK, OR SWIMMING POOL THAT IS LESS THAN
5			5,000	SQUARE FEET IN AREA AND THAT IS USED EXCLUSIVELY FOR
6			PARTI	CIPANT SPORTS WITH AUDIENCE FACILITIES FOR LESS THAN 100
7			PERSC	ons;
8		(3)	In an	enclosed stadium or arena that is less than 5,000 square
9			FEET A	and that has an occupant load of less than 100 persons; or
10		(4)	In an	UNENCLOSED STADIUM OR ARENA:
11			(A)	In press boxes containing less than $1,000$ square feet in
12				AREA;
13			(B)	In storage facilities containing less than 1,000 square feet
14				In area if the area is enclosed with more than 1 -hour fire
15				RESISTANCE RATED CONSTRUCTION; OR
16			(C)	In enclosed areas underneath a grandstand if the area is
17				enclosed with more than 1 -hour fire resistance rated
18				CONSTRUCTION.
19	(171)	SUBSEC	TIONS	13.3.2.6.5.2 AND 13.3.2.6.5.3
20		DELETE	E THES	E SUBSECTIONS.
21	(172)	SUBSEC	TION I	3.3.2.7.1
22		DELETE	ETHIS	SUBSECTION AND SUBSTITUTE THE FOLLOWING:
23		WHERE	THE C	occupant load is 100 or more, the AHJ may require the
24		OCCUPA	ANCY I	PROTECTED THROUGHOUT BY AN APPROVED SUPERVISED AUTOMATIC
25		SPRINK	LER SY	STEM IN ACCORDANCE WITH NFPA 13.
26	(173)	SUBSEC	TION 1	3.3.2.7.2
27		DELETE	E "15,0	000" and substitute "5,000".
28	(174)	SUBSEC	TION I	3.3.2.7.5.4
29		ADD SU	BSECT	TION 13.3.2.7.5.4 AFTER SECTION 13.3.2.7.5.3 AS FOLLOWS:

1		THE AHJ MAY REQUIRE SPRINKLERS FOR EXISTING STAGES AND UNDER EXISTING
2		STAGES WHEN THE AHJ DETERMINES, BASED ON A LIFE SAFETY EVALUATION, THAT
3		AN IMMINENT DANGER EXISTS.
4	(175)	Subsection 13.3.2.8 through 13.3.2.17.7
5		DELETE THESE SUBSECTIONS AND SUBSTITUTE THE FOLLOWING:
6		Subsection 13.3.2.8. A new educational occupancy, health care facility,
7		DETENTION OR CORRECTIONAL FACILITY, HOTEL, DORMITORY, OR APARTMENT
8		BUILDING SHALL MEET THE REQUIREMENTS OF THE BUILDING CODE. THE AHJ MAY
9		REQUIRE INSTALLATION OF AN APPROVED AUTOMATIC SPRINKLER SYSTEM IN AN
10		EXISTING EDUCATIONAL OCCUPANCY, HEALTH CARE OCCUPANCY, DETENTION OR
11		CORRECTION FACILITY, HOTEL, DORMITORY, OR APARTMENT BUILDING WHEN:
12		(1) A LIFE SAFETY EVALUATION IS COMPLETED AND THE AHJ DETERMINES,
13		BASED ON THE LIFE SAFETY EVALUATION, THAT AN EMERGENCY, OR
14		IMMINENT DANGER EXISTS; OR
15		(2) REQUIRED BY NFPA 101, LIFE SAFETY CODE.
16	(176)	SUBSECTION 13.3.2.18.1
17		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
18		EXCEPT AS PROVIDED IN SUBSECTION 13.3.2.18.2, A NEW LODGING OR ROOMING
19		HOUSE SERVING SIX OR MORE RESIDENTS SHALL BE PROTECTED THROUGHOUT BY AN
20		APPROVED AUTOMATIC SPRINKLER SYSTEM. AN AUTOMATIC SPRINKLER SYSTEM
21		may be required in an existing lodging or rooming house serving 6 or
22		MORE RESIDENTS WHEN:
23		(1) A LIFE SAFETY EVALUATION IS COMPLETED AND THE AHJ DETERMINES,
24		BASED ON THE LIFE SAFETY EVALUATION, THAT AN EMERGENCY, OR
25		IMMINENT DANGER EXISTS; OR
26		(2) REQUIRED BY NFPA 101, LIFE SAFETY CODE.
27	(177)	SUBSECTION 13.3.2.18.2
28		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
29		In a building containing less than $5,000$ square feet in gross floor area
30		AND DESIGNED FOR FEWER THAN 6 RESIDENTS, AN AUTOMATIC SPRINKLER SYSTEM
31		IS NOT REQUIRED WHERE EVERY SLEEPING ROOM HAS A DOOR OPENING DIRECTLY:

1		(1) 10 THE OUTSIDE OF THE BUILDING AT STREET OR GROUND LEVEL; OR
2		(2) TO THE OUTSIDE LEADING TO AN EXTERIOR STAIRWAY.
3	(178)	SUBSECTION 13.3.2.19.1
4	•	Amend this section to add "the Howard County Building Code, and"
5		AFTER "IN ACCORDANCE WITH".
6	(179)	SUBSECTION 13.3.2.20.1.1
7		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
8		A building with an occupant load of 6 or more residents shall be
9		PROTECTED THROUGHOUT BY AN APPROVED AUTOMATIC SPRINKLER SYSTEM.
10	(180)	SUBSECTION 13.3.2.20.2.2
11		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
12		In a conversion, an automatic sprinkler system shall not be required in
13		A BOARD AND CARE HOME THAT SERVES 5 OR FEWER RESIDENTS WHEN ALL
14		OCCUPANTS HAVE THE ABILITY TO MOVE AS A GROUP TO A POINT OF SAFETY WITHIN
15		3 minutes.
16	(181)	SUBSECTION 13.3.2.21.1.1
17		ADD THE FOLLOWING AT THE END.
18		AN AUTOMATIC SPRINKLER SYSTEM MAY BE REQUIRED IN AN EXISTING FACILITY
19		WHEN A LIFE SAFETY EVALUATION IS COMPLETED AND THE AHJ DETERMINES,
20		BASED ON THE LIFE SAFETY EVALUATION, THAT AN IMMINENT DANGER EXISTS.
21	(182)	SUBSECTION 13.3.2.22.1(2)
22		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
23		Throughout a new mercantile occupancy exceeding $5,\!000$ square feet in
24		GROSS AREA.
25	(183)	Subsection 13.3.2.23.1(5)
26		ADD NEW PARAGRAPH (5) AT THE END AS FOLLOWS:
27		(5) The gross floor area is more than 5,000 square feet and has an
28		OCCUPANT LOAD OF 50 OR MORE PERSONS.
29	(184)	SUBSECTION 13.3.2.23.1(6)
30		ADD NEW PARAGRAPH (6) AS FOLLOWS:

1		(6) AN AUTOMATIC SPRINKLER SYSTEM MAY BE REQUIRED IN AN EXISTING
2		MERCANTILE OCCUPANCY WHEN A LIFE SAFETY EVALUATION IS COMPLETED
3		and the AHJ determines, based on the life safety evaluation that
4		AN IMMINENT DANGER EXISTS.
5	(185)	SUBSECTION 13.3.2.24.1
6		ADD NEW SUBSECTION 13.3.2.24.1 AFTER SUBSECTION 13.3.2.24 AS FOLLOWS:
7		An automatic sprinkler system may be required in an existing
8		UNDERGROUND OR WINDOWLESS STRUCTURE WHEN A LIFE SAFETY EVALUATION IS
9		COMPLETED AND THE AHJ DETERMINES, BASED ON THE LIFE SAFETY EVALUATION,
10		THAT AN IMMINENT DANGER EXISTS.
11	(186)	SUBSECTION 13.3.2.26
12		DELETE THE TITLE AND SUBSTITUTE "NEW AND EXISTING STORAGE
13		Occupancies".
14	(187)	SUBSECTION 13.3.2.26.2
15		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
16		GENERAL STORAGE. AN AUTOMATIC SPRINKLER SYSTEM SHALL BE INSTALLED
17		THROUGHOUT ALL NEW STORAGE OCCUPANCIES WITH A GROSS FLOOR AREA
18		Greater than 5,000 square feet.
19	(188)	SUBSECTION 13.3.2.26.2.1
20		ADD NEW SUBSECTION 13.3.2.26.2.1 AFTER SUBSECTION 13.3.2.26.2 AS FOLLOWS:
21		AN AUTOMATIC SPRINKLER SYSTEM MAY BE REQUIRED IN AN EXISTING STORAGE
22		OCCUPANCY WHEN A LIFE SAFETY EVALUATION IS COMPLETED AND THE \overline{AHJ}
23		DETERMINES, BASED ON THE LIFE SAFETY EVALUATION, THAT AN IMMINENT
24		DANGER EXISTS.
25	(189)	SUBSECTION 13.3.2.26.4
26		Delete "20,000" and substitute "2,500".
27	(190)	SUBSECTION 13.3.2.26.5
28		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
29		AN AUTOMATIC SPRINKLER SYSTEM SHALL BE INSTALLED THROUGHOUT ALL MINI-
30		Storage building fire areas greater than $2500\mathrm{SQUARE}$ feet and where
21		ANY OF THE INDIVIDUAL STORAGE UNITS ARE SEPARATED BY LESS THAN A 1-HOUR

1		FIRE RESISTANCE-RATED BARRIER. FIRE AREAS SHALL BE DEFINED BY APPROVED
2		FIRE BARRIERS HAVING A FIRE RESISTANCE RATING OF NOT LESS THAN 3-HOURS.
3	(191)	Subsection 13.3.2.28.1
4		ADD NEW SUBSECTION 13.3.2.28.1. AFTER SUBSECTION 13.3.2.28 AS FOLLOWS:
5		New and existing day care homes with 12 or fewer clients are not
6		REQUIRED TO BE PROTECTED BY AN AUTOMATIC SPRINKLER SYSTEM UNLESS
7		SPECIFICALLY MANDATED BY THE AHJ.
8	(192)	SUBSECTION 13.3.2.28.2
9		ADD NEW SUBSECTION 13.3.2.28.2 AFTER SUBSECTION 13.3.2.28.1 AS FOLLOWS:
10		A NEW DAY CARE OCCUPANCY WITH MORE THAN 12 CLIENTS SHALL BE PROTECTED
11		THROUGHOUT BY AN APPROVED AUTOMATIC SPRINKLER SYSTEM, REGARDLESS OF
12		WHETHER THERE ARE PROTECTED OPENINGS. AN EXISTING DAY CARE WITH 12 OR
13		FEWER CLIENTS THAT IS APPROVED TO INCREASE TO MORE THAN 12 CLIENTS SHALL
14		MEET THE PROVISIONS OF A NEW DAY CARE OCCUPANCY.
15	(193)	SUBSECTION 13.3.2.28.3
16		ADD NEW SUBSECTION 13.3.2.28.3 AFTER SUBSECTION 13.3.2.28.2 AS FOLLOWS:
17		AN AUTOMATIC SPRINKLER SYSTEM MAY BE REQUIRED IN ANY EXISTING DAY CARE
18		OCCUPANCY SERVING MORE THAN 12 CLIENTS WHEN A LIFE SAFETY EVALUATION IS
19		COMPLETED AND THE AHJ DETERMINES, BASED ON THE LIFE SAFETY EVALUATION,
20		THAT AN IMMINENT DANGER EXISTS.
21	(194)	Subsections 13.3.3.1 and 13.3.3.2
22		AMEND THIS SECTION TO DELETE "INSTALLED IN ACCORDANCE WITH THIS CODE"
23	(195)	SUBSECTION 13.3.3.3.1
24		ADD NEW SUBSECTION 13.3.3.3.1 AFTER SUBSECTION 13.3.3.3 AS FOLLOWS:
25		FOR NEW CEILING INSTALLATIONS, DROP-OUT CEILINGS AS REFERENCED IN NFPA
26		13, Subsections 9.2.16 and 9.3.11 are prohibited.
27	(196)	SUBSECTION 13.4.1.1.1
28		ADD NEW SUBSECTION 13.4.1.1.1 AFTER SUBSECTION 13.4.1.1 AS FOLLOWS:
29		NO FIRE PUMP COMPONENT, INCLUDING THE PUMP, DRIVER, OR CONTROLLER, SHALL
30		BE PERMITTED TO BE INSTALLED IN BELOW-GROUND VAULTS OR PITS UNLESS
31		OTHERWISE APPROVED BY THE AHJ.

1	(197)	SUBSECTION 13.6.1.1
2		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
3		Unless the AHJ approves an alternative feature or requirement that
4		PROVIDES THE SAME LEVEL OF PROTECTION OR FIRE SAFETY AS THIS CODE, THE
5		INSTALLATION, MAINTENANCE, SELECTION, AND DISTRIBUTION OF A PORTABLE FIRE
6		EXTINGUISHER SHALL BE IN ACCORDANCE WITH NFPA 10 , STANDARD FOR
7		PORTABLE FIRE EXTINGUISHERS, SECTION 13.6 AND THE PUBLIC SAFETY ARTICLE
8		OF THE ANNOTATED CODE OF MARYLAND.
9	(198)	SUBSECTION 13.6.1.2
LO		ADD THE FOLLOWING TO THE END: "UNLESS OTHERWISE PERMITTED BY THE AHJ".
11	(199)	SUBSECTION 13.6.4.1.2.1
12		Amend this subsection to delete "certified" and substitute "licensed as
13		REQUIRED BY THE AHJ".
L4	(200)	Subsections 13.6.4.1.2.1.1 through 13.6.4.1.2.1.6
L5		DELETE THESE SUBSECTIONS IN THEIR ENTIRETY.
16	(201)	SUBSECTION 13.6.4.1.2.3
17		AMEND THIS SUBSECTION TO DELETE "CERTIFIED" AND SUBSTITUTE "LICENSED".
18	(202)	SUBSECTION 13.7.1.7.6
L9		AMEND THIS SUBSECTION TO ADD THE FOLLOWING:
20		THIS PARAGRAPH DOES NOT PERMIT THE OMISSION OF MANUAL FIRE ALARM BOXES
21		IN ACCORDANCE WITH OTHER PROVISIONS OF THIS SUBSECTION UNLESS
22		SPECIFICALLY PERMITTED BY CHAPTERS 11 THROUGH 43.
23	(203)	SUBSECTION 13.7.1.7.7.1
24		ADD NEW SUBSECTION 13.7.1.7.7.1 AFTER SUBSECTION 13.7.1.7.7 AS FOLLOWS:
25		THE AHJ SHALL HAVE THE AUTHORITY TO APPROVE ANY DEVICE INSTALLED TO
26		PREVENT FALSE ALARMS THAT IS ADDED TO A MANUAL FIRE ALARM BOX OR PULL
27		STATION.
28	(204)	SUBSECTION 13.7.1.8.11
20		ADD NEW SUBSECTION 13 7 1 8 11 AFTER SUBSECTION 13 7 1 8 10 AS FOLLOWS:

1 .		A SINGLE STATION OR MULTIPLE STATION SMOKE ALARM SHALL MEET THE
2		REQUIREMENTS SET FORTH IN THE PUBLIC SAFETY ARTICLE OF THE ANNOTATED
3		CODE OF MARYLAND AND THE BUILDING CODE.
4	(205)	SUBSECTION 13.7.1.8.12
5		ADD NEW SUBSECTION 13.7.1.8.12 AFTER SUBSECTION 13.7.1.8.11 AS FOLLOWS:
6		ELECTRICAL INSTALLATION: SMOKE ALARMS SHALL BE INSTALLED AND
7		MAINTAINED IN ACCORDANCE WITH THE HOWARD COUNTY ELECTRICAL CODE AND
8		THE MOST RECENTLY ADOPTED EDITION OF NFPA STANDARD 72.
9	(206)	SUBSECTION 13.7.1.8.13
LO		ADD NEW SUBSECTION 13.7.1.8.13 AFTER SUBSECTION 13.7.1.8.12 AS FOLLOWS:
L1		THE OWNER OR OWNER'S AGENT SHALL INSTALL ALL SMOKE ALARMS AND SHALL
12		ANNUALLY INSPECT AND MAINTAIN ALL SMOKE ALARMS IN ACCORDANCE WITH THE
13		MANUFACTURER'S WARRANTY AND SUGGESTED MAINTENANCE. THE OWNER OR
L4		OWNER'S AGENT SHALL MAINTAIN A RECORD OF THE MAINTENANCE SCHEDULE.
L5		Upon notification by a tenant that a smoke alarm is missing or
16		INOPERATIVE, THE OWNER OR OWNER'S AGENT SHALL REPAIR OR REPLACE THE
L7		SMOKE ALARM. NOTIFICATION SHALL BE GIVEN BY CERTIFIED MAIL AND FIRST-
18		CLASS MAIL. IF THE TENANT PERSONALLY NOTIFIES THE OWNER OR THE OWNER'S
L9		AGENT OF A MECHANICAL FAILURE OF A SMOKE ALARM, THE OWNER OR OWNER'S
20		AGENT SHALL PROVIDE A WRITTEN, DATED RECEIPT ACKNOWLEDGING THE
21		NOTIFICATION.
22	(207)	SUBSECTION 13.7.1.8.14
23		ADD NEW SUBSECTION 13.7.1.8.14 AFTER SUBSECTION 13.7.1.8.13 AS FOLLOWS:
24		Where a smoke alarm is required, a person shall not remove or render
25		ANY SMOKE ALARM INOPERATIVE.
26	(208)	SUBSECTION 13.7.1.8.15
27		ADD NEW SUBSECTION 13.7.1.8.15 AFTER SUBSECTION 13.7.1.8.14 AS FOLLOWS:
28		EXCEPT FOR SMOKE ALARMS IN A HOTEL OR MOTEL, AN OWNER OR OWNER'S AGENT
29		MAY REQUIRE A TENANT TO PAY A REFUNDABLE DEPOSIT FOR SMOKE ALARMS, NOT
30		TO EXCEED THE VALUE OF THE SMOKE ALARM.
01	(200)	Surgection 13 7 1 8 16

1		ADD NEW SUBSECTION 13.7.1.8.16 AFTER SUBSECTION 13.7.1.8.15 AS FOLLOWS:
2		A DWELLING UNIT OCCUPIED BY A PERSON WHO IS DEAF OR HEARING IMPAIRED
3		SHALL BE EQUIPPED WITH A SMOKE ALARM THAT, WHEN ACTIVATED, SHALL
4		PROVIDE A SIGNAL THAT IS APPROVED BY A NATIONALLY RECOGNIZED TESTING
5		LABORATORY FOR ELECTRICAL APPLIANCES AND IS SUFFICIENT TO WARN A DEAF OR
6		HEARING-IMPAIRED PERSON. AN OWNER OR THEIR AGENT SHALL PROVIDE THIS
7		TYPE OF SMOKE ALARM UPON THE WRITTEN REQUEST OF THE DEAF OR HEARING-
8		IMPAIRED TENANT.
9	(210)	SUBSECTION 13.7.1.8.17
10		ADD NEW SUBSECTION 13.7.1.8.17 AFTER SUBSECTION 13.7.1.8.16 AS FOLLOWS:
11		ANY BATTERY-OPERATED SMOKE ALARM THAT IS REPLACED IS REQUIRED TO BE A
12		LONG-LIFE TYPE ALARM WITH A SEALED BATTERY, OR AS OTHERWISE APPROVED BY
13		тне АНЈ.
14	(211)	SUBSECTION 13.7.1.10.6
15		ADD NEW SUBSECTION 13.7.1.10.6 AFTER SUBSECTION 13.7.1.10.5 AS FOLLOWS:
16		WHERE THE FIRE ALARM SYSTEM DOES NOT PROVIDE FOR EMERGENCY FORCES
17		NOTIFICATION IN ACCORDANCE WITH SUBSECTION 13.7.1.10 APPROVED SIGNS TO
18		PROVIDE INSTRUCTION FOR EMERGENCY FORCES NOTIFICATION SHALL BE PROVIDED
19		AND PERMANENTLY AFFIXED AND MAINTAINED AT EACH MANUAL FIRE ALARM BOX.
20	(212)	SUBSECTION 13.7.2.5.6.4
21		Amend this subsection to add the following:
22		For compliance with NFPA 101, Paragraph 43.7.2.1(2), approved battery-
23		POWERED SMOKE ALARMS, RATHER THAN HOUSE ELECTRICAL SERVICE-POWERED
24		SMOKE ALARMS SHALL BE PERMITTED WHERE THE FACILITY HAS TESTING,
25		MAINTENANCE, AND SMOKE ALARM REPLACEMENT PROGRAMS THAT ENSURE
26		RELIABILITY OF POWER TO THE SMOKE ALARMS.
27	(213)	SUBSECTION 13.7.2.6.6.5
28		AMEND THIS SUBSECTION TO DELETE "EXISTING" AND REPLACE "BATTERY" WITH
29		"SMOKE ALARM".
30	(214)	SUBSECTION 13.7.2.13.1.3
31		AT THE END OF THE SUBSECTION ADD THE FOLLOWING:

1		STANDARDS GOVERNING SMOKE ALARMS SHALL BE IN ACCORDANCE WITH TITLE 9,
2		SUBTITLE 1 OF THE PUBLIC SAFETY ARTICLE OF THE ANNOTATED CODE OF
3		Maryland.
4	(215)	SUBSECTION 13.7.2.14.5.3
5		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
6		In lodging and rooming houses built prior to July 1, 1990, smoke alarms
7		SHALL BE HARD WIRED TO THE BUILDING'S POWER SUPPLY. IN LODGING AND
8		rooming houses built after July 1, 1990, smoke alarms shall have an
9		INTEGRAL BATTERY BACKUP POWER SUPPLY OR AN APPROVED EMERGENCY POWER
10		SUPPLY.
11	(216)	SUBSECTION 13.7.2.14.5.4
12		ADD NEW SUBSECTION 13.7.2.14.5.4 AFTER SUBSECTION 13.7.2.14.5.3 AS
13	FOL	LOWS:
14		EXCEPT IN A BUILDING PROTECTED BY AN AUTOMATIC SPRINKLER SYSTEM, SMOKE
15		ALARMS ARE REQUIRED IN AN INTERIOR CORRIDOR SERVING ROOMS OF LODGING
16		AND ROOMING HOUSES. THESE ALARMS SHALL BE CONNECTED TO THE BUILDING
17		FIRE ALARM.
18	(217)	SUBSECTION 13.7.2.16.1
19		ADD THE FOLLOWING AT THE END OF THIS SUBSECTION:
20		SINGLE STATION SMOKE ALARMS SHALL BE HARD-WIRED DIRECTLY TO THE
21		BUILDING'S POWER SUPPLY. INDIVIDUAL GUESTROOM ALARMS SHALL NOT BE
22		CONNECTED TO THE BUILDING ALARM SYSTEM.
23	(218)	SUBSECTION 13.7.2.16.5.2
24		AMEND THIS SECTION AS FOLLOWS:
25		(1) AFTER "PERMITTED" INSERT "IN HOTELS AND DORMITORIES BUILT PRIOR TO
26		July 1, 1990"; and
27		(2) AT THE END OF THIS SUBSECTION ADD "IN A HOTEL, MOTEL, OR DORMITORY
28		built after July 1, 1990, smoke alarms shall have an integral
29		BATTERY BACKUP POWER SUPPLY OR AN APPROVED EMERGENCY POWER
30		SUPPLY."
31	(219)	SUBSECTION 13.7.2.16.5.3

1		ADD NEW SUBSECTION 13.7.2.16.5.3 AFTER SUBSECTION 13.7.2.16.5.2 AS
2		FOLLOWS:
3		EXCEPT IN A BUILDING PROTECTED BY AN AUTOMATIC SPRINKLER SYSTEM, SMOKE
4		ALARMS ARE REQUIRED IN AN INTERIOR CORRIDOR SERVING A GUESTROOM OF A
5		HOTEL, MOTEL, OR DORMITORY. THESE ALARMS SHALL BE CONNECTED TO THE
6		BUILDING ALARM SYSTEM.
7	(220)	SUBSECTION 13.7.2.16.5.4
8		ADD NEW SUBSECTION 13.7.2.16.5.4 AFTER SUBSECTION 13.7.2.16.5.3 AS
9		FOLLOWS:
10		SINGLE STATION SMOKE ALARMS SHALL BE INSTALLED IN EACH SLEEPING AREA OF
11		A HOTEL, MOTEL, OR DORMITORY. SINGLE-STATION SMOKE DETECTORS SHALL BE
12		HARD-WIRED DIRECTLY TO THE BUILDING'S POWER SUPPLY. SMOKE ALARMS SHALL
13		BE INSTALLED IN EVERY ROOM THROUGH WHICH A PERSON MUST PASS TO GET FROM
14		THE SLEEPING AREA TO THE DOOR LEADING FROM THE GUESTROOM OR SUITE.
15		Individual guestroom alarms shall not be connected to the building's
16		ALARM SYSTEM.
17	(221)	SUBSECTION 13.7.2.16.5.5
18		ADD NEW SUBSECTION 13.7.2.16.5.5 AFTER SUBSECTION 13.7.2.16.5.4 AS
19		FOLLOWS:
20		A HOTEL OR MOTEL SHALL HAVE AVAILABLE AT LEAST ONE SMOKE ALARM FOR THE
21		deaf or hearing-impaired for each 50 units (or portion thereof). The
22		OWNER OR OWNER'S AGENT OF THE HOTEL OR MOTEL MAY REQUIRE A REFUNDABLE
23		DEPOSIT, NOT TO EXCEED THE COST OF THE SMOKE ALARM, FOR THE USE OF A DEAF
24		OR HEARING-IMPAIRED SMOKE ALARM. THE OWNER OR OWNER'S AGENT OF A HOTEL
25		OR MOTEL SHALL POST, IN A CONSPICUOUS PLACE AT THE REGISTRATION DESK OR
26		COUNTER, A PERMANENT SIGN STATING THE AVAILABILITY OF SMOKE ALARMS FOR
27		THE HEARING IMPAIRED.
28	(222)	SUBSECTION 13.7.2.18.1.3
29		ADD NEW SUBSECTION 13.7.2.18.1.3 AFTER SUBSECTION 13.7.2.18.1.2 AS
30		FOLLOWS:

Т		A DWELLING UNIT IN A MULTIFAMILY RESIDENTIAL BUILDING SHALL MEET THE
2		FOLLOWING REQUIREMENTS:
3		(1) A UNIT BUILT BEFORE JANUARY 1, 1989, SHALL HAVE SMOKE ALARMS
4		HARD-WIRED TO THE BUILDING'S POWER SUPPLY.
5		(2) A UNIT BUILT BETWEEN JANUARY 1, 1989 AND JULY 1, 1990, SHALL MEET
6		THE REQUIREMENTS OF PARAGRAPH 1, AND, EXCEPT IN AN ATTIC, SMOKE
7		ALARMS SHALL BE INSTALLED ON EACH LEVEL OF A MULTILEVEL
8		INDIVIDUAL DWELLING UNIT, INCLUDING IN A BASEMENT. ALL SMOKE
9		ALARMS SHALL BE INTERCONNECTED SO THAT ALL WILL SOUND IF ONE
10		SMOKE ALARM IS ACTIVATED.
11		(3) A Unit built after July 1, 1990, shall meet the requirements of
12		paragraph 1 and 2 and smoke alarms shall have an integral
13		BATTERY BACKUP POWER SUPPLY.
14		(4) A UNIT BUILT AFTER OCTOBER 10, 2001, SHALL MEET THE REQUIREMENTS
15		of paragraph $1, 2$, and 3 and smoke alarms shall be placed in each
16		SLEEPING AREA.
17	(223)	SUBSECTION 13.7.2.22.8.1
18		Amend this subsection to delete "13.7.2.22.8.2 and".
19	(224)	SUBSECTION 13.7.2.22.8.2
20		DELETE THIS SUBSECTION.
21	(225)	Subsection 13.7.2.28.1.2 and 13.7.2.28.1.3
22		AMEND THESE SUBSECTIONS TO DELETE "STORAGE OCCUPANCIES" AND
23		SUBSTITUTE "STORAGE OCCUPANCIES LESS THAN THREE STORIES".
24	(226)	Subsection $14.5.3.1.1(3)(E)$
25		ADD NEW SUBSECTION $14.5.3.1.1(3)(E)$ AFTER SUBSECTION $14.5.3.1.1(3)(D)$ AS
26		FOLLOWS:
27		The request to increase the delay from 15 seconds to 30 seconds must be
28		SUBMITTED TO THE AHJ IN WRITING.
29	(227)	SUBSECTION 14.5.3.4.1(11)
30		ADD THE FOLLOWING AT THE END:
31		THE CENTRAL CONTROL POINT SHALL BE APPROVED BY THE AHJ.

1	(228)	SUBSECTION 14.5.3.5.6
2		ADD NEW SUBSECTION 14.5.3.5.6 AFTER SUBSECTION 14.5.3.5.5 AS FOLLOWS:
3		In lockups, as referenced in section 22.4.6 of NFPA 101 Life Safety Code,
4		THE RELEASE TIME FOR DOORS OR OTHER PHYSICAL RESTRAINTS SHALL NOT
5		exceed 30 seconds.
6	(229)	SUBSECTION 14.13.1.2
7		AMEND THIS SECTION TO DELETE "ONLY" IN THE FIRST SENTENCE AND SUBSTITUTE
8		", BUT NOT BE LIMITED TO,".
9	(230)	SUBSECTION 16.1.6
10		ADD NEW SUBSECTION 16.1.6 AFTER SECTION 16.1.5 AS FOLLOWS:
11		TEMPORARY SIGNAGE CLEARLY INDICATING THE ADDRESS OF THE STRUCTURE
12		SHALL BE CONSPICUOUSLY POSTED AT EVERY ENTRANCE, AS WELL AS OUTSIDE AN
13		SUPERVISORY LOCATIONS OR FIELD OFFICES ON THE CONSTRUCTION SITE. THESE
14		SIGNS MUST BE MAINTAINED THROUGH THE DURATION OF THE CONSTRUCTION.
15	(231)	SUBSECTION 16.2.1.15
16		ADD NEW SUBSECTION 16.2.1.15 AFTER SUBSECTION 16.2.1.14 AS FOLLOWS:
17		Whenever liquified petroleum gas (LP-gas) is used for temporary
18		HEATING, THE AHJ MAY REQUIRE A TEMPORARY HEATING PLAN TO BE PROVIDED
19		for approval. This plan shall address how each provision of $16.2.1$ is
20		BEING ACCOMPLISHED, AS WELL AS TO PROVIDE A GRAPHICAL DEPICTION OF TANK
21		LOCATION AND PROTECTION MEASURES.
22	(232)	SUBSECTION 16.2.3.2
23		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
24		Trash, debris, rubbish, and building materials shall not be burned on
25		THE PREMISES.
26	(233)	SUBSECTION 16.4.1.2(4)
27		AMEND THIS SUBSECTION TO ADD ", AND APPROVED BY THE AHJ" AFTER
28		"APPLICABLE".
29	(234)	SUBSECTION 16.4.2
30		Amend this section to delete "Fire Protection" and substitute "a Fire
31		SAFETY PROGRAM".

1	(235)	Subsection 16.4.4.2.1
2		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
3		THE AHJ SHALL HAVE THE AUTHORITY TO REQUIRE AN ACCESS BOX OR BOXES OR
4		OTHER ACCESS SYSTEM TO BE INSTALLED IN AN ACCESSIBLE LOCATION WHERE
5		ACCESS TO OR WITHIN A STRUCTURE OR AREA IS DEEMED DIFFICULT BY THE AHJ.
6		THE TYPE OF ACCESS BOX OR SYSTEM SHALL BE SPECIFIED BY THE AHJ.
7	(236)	SUBSECTION 16.4.4.2.3
8		ADD SUBSECTION 16.4.4.2.3 AFTER SUBSECTION 16.4.4.2.2 AS FOLLOWS:
9		THE ACCESS SYSTEM SHALL BE AN APPROVED TYPE AND SHALL BE INSTALLED AND
10		UTILIZED AS DIRECTED BY THE AHJ.
11	(237)	SUBSECTION 16.4.4.3.1
12		Amend this subsection to add:
13		THE AHJ MAY REQUIRE ANY PLANNED STAIRWELL TO BE FUNCTIONAL DURING
14		CONSTRUCTION AT THE LEVEL NECESSARY FOR ACCESS OR EGRESS FROM THE
15		HIGHEST LEVEL WHERE WORK IS BEING PERFORMED.
16	(238)	Subsection 16.4.4.3.1.1
17		ADD NEW SUBSECTION 16.4.4.3.1.1 AFTER SUBSECTION 16.4.4.3.1 AS FOLLOWS:
18		Where the AHJ determines that more than one planned stairwell is not
19		REQUIRED, AN APPROVED TEMPORARY SECONDARY MEANS OF ACCESS OR EGRESS
20		SHALL BE MAINTAINED IN CONFORMITY WITH THE PROGRESS OF BUILDING
21		CONSTRUCTION IN SUCH MANNER THAT IT IS ALWAYS READY FOR USE.
22	(239)	SUBSECTION 18.2.2.1
23		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
24		THE AHJ SHALL HAVE THE AUTHORITY TO REQUIRE AN ACCESS BOX OR BOXES OR
25		OTHER ACCESS SYSTEM TO BE INSTALLED IN AN ACCESSIBLE LOCATION WHERE
26		ACCESS TO OR WITHIN A STRUCTURE OR AREA IS DEEMED DIFFICULT BY THE AHJ.
27		THE TYPE OF ACCESS BOX OR SYSTEM SHALL BE SPECIFIED BY THE AHJ.
28	(240)	SUBSECTION 18.2.3.2.1
29		AMEND THIS SUBSECTION TO DELETE "EXTERIOR DOOR" AND SUBSTITUTE
30		"EXTERIOR DOOR ACCEPTABLE TO THE AHJ".
31	(241)	Subsection 18.2.3.2.1.1

1		DELETE THIS SUBSECTION.
2	(242)	SUBSECTION 18.2.3.2.2.1
3		DELETE THIS SUBSECTION.
4	(243)	SUBSECTION 18.2.3.3.1
5		ADD NEW SUBSECTION 18.2.3.3.1 AFTER SUBSECTION 18.2.3.3 AS FOLLOWS:
6		Multiple fire apparatus access roads may be required when a
7		DEVELOPMENT CONTAINS 100 OR MORE RESIDENTIAL UNITS.
8	(244)	SUBSECTION 18.2.3.4
9		AMEND THIS SUBSECTION TO DELETE "SHALL" AND SUBSTITUTE "MAY BE REQUIRED
10		ву тне АНЈ то".
11	(245)	SUBSECTION 18.2.3.5.1.1
12		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
13		EXCEPT FOR USE-IN-COMMON DRIVEWAYS, FIRE APPARATUS ACCESS ROADS SHALL
14		have an unobstructed width of not less than 20 feet, unless approved in
15		WRITING BY THE AHJ. USE-IN-COMMON DRIVEWAYS SHALL COMPLY WITH THE
16		HOWARD COUNTY DESIGN MANUAL.
17	(246)	SUBSECTION 18.2.3.5.1.3
18		ADD NEW SUBSECTION 18.2.3.5.1.3 AFTER SUBSECTION 18.2.3.5.1.2 AS FOLLOWS:
19		FIRE APPARATUS ACCESS ROADS LEADING TO ALL GROUND-BASED SOLAR
20		FACILITIES SHALL HAVE AN IMPROVED SURFACE APPROVED BY THE $A\mathrm{HJ}$, and an
21		unobstructed width of 16 feet. When conditions allow, the AHJ may
22		approve a reduced width of no less than 12 feet where additional pull-
23		OFFS AND AN ADEQUATE TURNAROUND ARE PROVIDED.
24	(247)	SUBSECTION 18.2.3.5.2
25		ADD THE FOLLOWING TO THE END OF THE SUBSECTION:
26		THE ACCESS ROAD SURFACE MUST BE APPROVED BY THE AHJ.
27	(248)	SUBSECTION 18.2.3.5.2.1
28		ADD NEW SUBSECTION 18.2.3.5.2.1 AFTER SUBSECTION 18.2.3.5.2 AS FOLLOWS:
29		WHEN THE SURFACE WILL BE DESIGNED OF A PERMEABLE SUBSTANCE INCLUDING
30		BUT NOT LIMITED TO GRASS PAVERS AND GRASS HONEYCOMB SYSTEMS, WRITTEN
31		CERTIFICATION MUST BE PROVIDED BY A QUALIFIED PROFESSIONAL ENGINEER TO

1		THE AHJ DEMONSTRATING THE PRODUCT WAS INSTALLED ACCORDING TO			
2		MANUFACTURER SPECIFICATIONS PRIOR TO ACCEPTANCE AND/OR BUILDING			
3		OCCUPANCY.			
4	(249)	SUBSECTION 18.2.3.5.2.2			
5		ADD NEW SUBSECTION 18.2.3.5.2.2 AFTER SUBSECTION 18.2.3.5.2.1 AS FOLLOWS:			
6		Unpaved surfaces shall be limited to a maximum 5% longitudinal slope			
7		AND 2% Cross slope but shall not be steeper than that specified by the			
8		MANUFACTURER. CLEAR EDGE DELINEATION IN A MANNER APPROVED BY THE AHJ			
9		IS REQUIRED.			
10	(250)	SUBSECTION 18.2.3.5.4.1			
11		ADD NEW SUBSECTION 18.2.3.5.4.1 AFTER SUBSECTION 18.2.3.5.4 AS FOLLOWS:			
12		THE AHJ MAY APPROVE IN WRITING AN EXCEPTION TO THE REQUIREMENTS OF			
13		Subsection 18.2.3.5.4 for a dead-end fire apparatus access road serving			
14		A SINGLE RESIDENTIAL STRUCTURE.			
15	(251)	SUBSECTION 18.2.3.5.6.1			
16		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:			
17		Grade. The maximum allowable grade is 15% with the durable and			
18		Sustained grade of 8% . The transition from the road to the driveway			
19		SHALL NOT EXCEED 8%.			
20	(252)	SUBSECTION 18.2.3.6.3			
21		ADD NEW SUBSECTION 18.2.3.6.3 AFTER SUBSECTION 18.2.3.6.2 AS FOLLOWS:			
22		THE AHJ MAY:			
23		(1) DESIGNATE PART OF ANY PUBLIC OR PRIVATE ROADWAY, DRIVEWAY, OR			
24		CURB AS A FIRE LANE; AND			
25		(2) DESIGNATE HOW THE FIRE LANE SHALL BE MARKED OR ESTABLISHED.			
26	(253)	Subsection 18.2.3.6.4			
27		ADD NEW SUBSECTION 18.2.3.6.4 AFTER SUBSECTION 18.2.3.6.3 AS FOLLOWS:			
28		In determining where and how a fire lane shall be established, the AHJ			
29		SHALL CONSIDER THE FOLLOWING:			
30		(1) THE WIDTH OF THE ROADWAY OR DRIVEWAY;			

1		(2)	THE ABILITY OF ANY NECESSARY EMERGENCY EQUIPMENT TO HAVE INGRESS
2			AND/OR EGRESS TO THE OCCUPANCY OR PROPERTY;
3		(3)	The size and turn radius of any necessary emergency vehicle or
4			EQUIPMENT;
5		(4)	ACCESS TO FIRE HYDRANTS, FIRE CONNECTIONS, AND FIRE EXITS;
6		(5)	LOCATION OF BUILDINGS OR STRUCTURES; AND
7		(6)	THE POTENTIAL OR LIKELIHOOD THAT A PERSON WOULD PARK A VEHICLE IN
8		THE AF	REA.
9	(254)	SUBSE	CTION 18.2.3.6.5
10		ADD N	NEW SUBSECTION 18.2.3.6.5 AFTER SUBSECTION 18.2.3.6.4 AS FOLLOWS:
11		REGAF	RDING FIRE LANE DESIGNATION:
12		(1)	THE AHJ MAY CONDUCT A SITE VISIT OF THE PROPERTY TO DETERMINE
13			WHETHER AND/OR HOW A FIRE LANE SHOULD BE DESIGNATED; AND
14		(2)	The $A\mathrm{HJ}$ may require a fire lane to be designated by the placement
15			OF FIRE LANE SIGNS, A RED PAINTED CURB, A RED HATCHED PATTERN, OR
16			ANY COMBINATION THEREOF.
17		(3)	NO CURBS SHALL BE PAINTED RED OR OTHERWISE RESEMBLE A FIRE LANE IN
18			ANY WAY UNLESS THEY HAVE BEEN DESIGNATED AS SUCH BY THE AHJ.
19	(255)	Subse	CCTION 18.2.3.6.6
20		ADD N	NEW SUBSECTION 18.2.3.6.6 AFTER SUBSECTION 18.2.3.6.5 AS FOLLOWS:
21		FOR A	ny fire lane that the AHJ determines shall be marked with fire
22		LANE S	SIGNS:
23		(1)	ALL SIGNS SHALL COMPLY WITH THE MOST RECENTLY ADOPTED STATE
24			HIGHWAY ADMINISTRATION STANDARD SIGN BOOK;
25		(2)	SIGNS SHALL BE PLACED AT THE TERMINATION POINTS OF THE FIRE LANE;
26		(3)	Signs shall be placed at least every 200 feet; and
27		(4)	SIGNS SHALL BE PLACED IN SUCH A WAY AND IN A LOCATION SO THAT THE
28			SIGNS SHALL NOT INTERFERE WITH PEDESTRIAN OR TRAFFIC MOVEMENT.
29	(256)	SUBSE	CCTION 18.2.3.6.7
30		ADDN	JEW SUBSECTION 18 2.3.6.7 AFTER SUBSECTION 18.2.3.6.6 AS FOLLOWS:

1		FOR A	NY FIRE LANE THAT THE AHJ DETERMINES SHALL BE MARKED BY A PAINTED
2		CURB:	
3		(1)	ALL CURBS SHALL BE PAINTED WITH RED TRAFFIC PAINT;
4		(2)	THE RED PAINTED MARKING SHALL BE AT LEAST 6 INCHES WIDE; AND
5		(3)	LETTERS STATING "NO PARKING FIRE LANE" SHALL BE STENCILED
6			ONTO THE RED PAINTED MARKING AT EACH END AND EVERY $20\mathrm{feet}$ of the
7			PAINTED AREA. THE LETTERS SHALL BE STENCILED USING WHITE PAINT AND
8			SHALL BE THREE INCHES HIGH AND LOCATED ON THE TOP SURFACE OF THE
9			CURB AS DESIGNATED BY THE AHJ.
10	(257)	SUBSE	CTION 18.2.3.6.8
11		ADD N	IEW SUBSECTION 18.2.3.6.8 AFTER SUBSECTION 18.2.3.6.7 AS FOLLOWS:
12		For A	ny fire lane that the AHJ determines shall be marked by a red
13		PAINTE	ED CROSS-HATCHING PATTERN:
14		(1)	THE AREA SHALL BE MARKED BY RED PAINT APPLIED IN A HATCH PATTERN
15			composed of parallel diagonal stripes running at a 30 to 60 -
16			DEGREE ANGLE ACROSS THE WIDTH OF THE FIRE LANE;
17		(2)	THE STRIPING USED TO CREATE THE CROSS-HATCH PATTERN SHALL BE AT
18			least 6 inches wide and the stripes placed at a maximum of 72
19			INCHES APART; AND
20		(3)	LETTERS STATING "NO PARKING FIRE LANE" SHALL BE STENCILED
21			USING WHITE PAINT WITHIN THE CROSS-HATCH PATTERN; AND
22		(4)	The size of the letters may vary depending on the size of the fire
23			LANE MARKING.
24	(258)	SUBSE	CTION 18.2.3.6.9
25		Add n	EW SUBSECTION 18.2.3.6.9 AFTER SUBSECTION 18.2.3.6.8 AS FOLLOWS:
26		THE A	HJ shall notify a property owner that a particular area is to be
27		DESIGN	NATED AS A FIRE LANE. THE PROPERTY OWNER SHALL, WITHIN 30 DAYS OF
28		RECEIP	T OF NOTIFICATION FROM THE AHJ , INSTALL FIRE LANE MARKINGS OR SIGNS
29		IN THE	LOCATION AND BY THE METHOD DIRECTED BY THE AHJ.
30	(259)	SUBSE	CTION 18.2.3.6.10
31		ADD N	EW SUBSECTION 18.2.3.6.10 AFTER SUBSECTION 18.2.3.6.9 AS FOLLOWS:

1		A PROPERTY OWNER WHO FAILS TO INSTALL OR MAINTAIN FIRE LANES, FIRE LANE
2		MARKINGS OR SIGNS, OR BOTH MARKINGS AND SIGNS, IN ACCORDANCE WITH THIS
3		SECTION IS GUILTY OF A MISDEMEANOR, AND UPON CONVICTION IS SUBJECT TO A
4		Fine of up to $$1,000.00$. Alternatively, and in addition to and concurrent
5		WITH ALL REMEDIES PROVIDED AT LAW OR EQUITY, A FIRE OFFICIAL MAY ENFORCE
6		THE PROVISIONS OF THIS SECTION WITH CIVIL PENALTIES PURSUANT TO TITLE 24,
7		"CIVIL PENALTIES," OF THE HOWARD COUNTY CODE. EACH DAY THAT A VIOLATION
8		CONTINUES IS A SEPARATE OFFENSE.
9	(260)	SUBSECTION 18.2.4.1.4
10		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
11		Entrances to fire apparatus access roads, whether or not closed with
12		gates and barriers in accordance with $18.2.4.2.1$, shall not be
13		OBSTRUCTED BY PARKED VEHICLES, OBJECTS, PILED SNOW, OR ANY OTHER
14		OBSTRUCTION HINDERING ACCESS TO THE ROAD. SIGNS DELINEATING FIRE
15		APPARATUS ACCESS ROADS APPROVED IN WRITING BY THE AHJ MUST BE PLACED AT
16		BOTH ENDS OR ALL ENTRANCES TO THE ACCESS ROAD.
17	(261)	SUBSECTION 18.2.4.1.4.1
18		ADD NEW SUBSECTION 18.2.4.1.4.1 AFTER SUBSECTION 18.2.4.1.4 AS FOLLOWS:
19		GATES, BOLLARDS, BARRIERS, OR ANY OTHER SIMILAR DEVICE INSTALLED AS A
20		CLOSURE TO A FIRE APPARATUS ACCESS ROAD MUST BE APPROVED BY THE AHJ.
21	(262)	SUBSECTION 18.2.4.2.2
22		AMEND THIS SECTION TO ADD THE FOLLOWING TO THE END:
23		ACCESS THROUGH AN ELECTRIC GATE SHALL BE PROVIDED IN A MANNER APPROVED
24		ву тне АНЈ.
25	(263)	SUBSECTION 18.3.1.2
26		ADD NEW SUBSECTION 18.3.1.2 AFTER SUBSECTION 18.3.1.1 AS FOLLOWS:
27		Any proposed subdivision outside of the Public Service Area (PSA), of 10
28		or more dwellings may be required to provide a 0.141 -acre parcel, with
29		dimensions of 100 feet in length by 50 feet in width, on public or
30		EMERGENCY ACCESS ROAD FRONTAGE APPROVED BY THE AHJ; FOR THE PURPOSE
31		OF INSTALLING A RURAL WATER SUPPLY CISTERN. THE ENTIRE FRONTAGE OF THE

1		CONCRETE PAD FOR THE RURAL WATER SUPPLY CISTERN SHALL BE DESIGNATED AS
2		A FIRE LANE.
3	(264)	SUBSECTION 18.5.1.1.1
4		ADD NEW SUBSECTION 18.5.1.1.1 AFTER SUBSECTION 18.5.1.1 AS FOLLOWS:
5		ALL NEW FIRE HYDRANTS SHALL BE PUBLIC UNLESS THE AHJ APPROVES THE USE OF
6		PRIVATE FIRE HYDRANTS.
7	(265)	SUBSECTION 18.5.2(2)
8		Delete "800 feet" and substitute "500 feet".
9	(266)	SUBSECTION 18.5.3(2)
10		Delete "500 feet" and substitute "350 feet".
11	(267)	SUBSECTION 18.5.5.1.1
12		ADD NEW SUBSECTION 18.5.5.1.1 AFTER SUBSECTION 18.5.5.1 AS FOLLOWS:
13		Any replacement private fire hydrants must meet Howard County
14		STANDARDS AS CONTAINED IN THE HOWARD COUNTY DESIGN MANUAL.
15	(268)	SUBSECTION 18.5.7.1
16		Delete "36 in" and substitute "60 in".
17	(269)	Subsection 18.5.10.3.1
18		ADD NEW SUBSECTION 18.5.10.3.1 AFTER SUBSECTION 18.5.10.3 AS FOLLOWS:
19		PRIVATE FIRE HYDRANTS SHALL BE PAINTED YELLOW, RECLAIMED WATER
20		HYDRANTS SHALL BE PAINTED PURPLE, HIGH PRESSURE HYDRANTS SHALL BE
21		PAINTED SILVER, AND GRAY WATER HYDRANTS SHALL BE PAINTED GREEN.
22	(270)	SUBSECTION 19.2.1.4
23		Amend this section to (1) delete "with an individual capacity of $1.5~{ m yard}^3$
24		or more" and (2) delete " 10 feet" and substitute " 15 feet".
25	(271)	SUBSECTION 20.1.4.7
26		ADD NEW SUBSECTION $20.1.4.7$ AFTER SUBSECTION $20.1.4.6$ AS FOLLOWS:
27		A TEMPORARY SPECIAL AMUSEMENT OCCUPANCY OR ATTRACTION THAT IS
28		occupied for less than 60 days, including, but not limited to, a haunted
29		HOUSE, MAZE, OR SPECIAL AMUSEMENT, SHALL MEET THE STANDARDS SET FORTH
30		BY THE AHJ AND THIS CODE.
31	(272)	SUBSECTION 20.1.5.2.4(3)

1		DELE	TE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING.			
2		CAND	CANDLES SHALL COMPLY WITH SECTION 10.10.1.1 OF THIS CODE.			
3	(273)	SUBSE	Subsection 20.1.5.2.4(6)			
4		Inser	Insert new subsection 20.1.5.2.4(6) after subsection 20.1.5.2.4(5) as			
5		FOLLO	OWS:			
6		(A)	ALL DEVICES IN CONNECTION WITH THE PREPARATION OF FOOD SHALL BE			
7			INSTALLED AND OPERATED TO AVOID HAZARD TO THE SAFETY OF			
8			OCCUPANTS. THESE DEVICES SHALL BE OF AN APPROVED TYPE AND SHALL			
9			BE INSTALLED IN AN APPROVED MANNER.			
10		(B)	IT IS RECOMMENDED THAT ONLY ELECTRIC DEVICES BE UTILIZED.			
11		(C)	CHAFING DISHES USING AN OPEN FLAME MUST BE DESIGNED FOR FOOD			
12			WARMING OPERATIONS ONLY. ONLY DEVICES (SUCH AS STERNO CANS)			
13			designed for use with chafing dishes shall be used. Chafing dish			
14			CONTAINERS FOR THE DEVICES MUST BE IN PLACE. A SNUFFING DEVICE			
15			DESIGNED FOR USE WITH THE CHAFING DISH CONTAINER SHALL BE KEPT IN			
16			CLOSE PROXIMITY TO THE SERVING AREA.			
17		(D)	Extra fuel containers shall be kept at a location remote from			
18			THE SERVING AREA.			
19		(E)	COMBUSTIBLE MATERIALS OR DECORATIONS SHALL NOT BE USED NEAR THE			
20			SERVING DISHES.			
21		(F)	${ m A}$ responsible person shall be identified to ensure the devices are			
22			COMPLETELY EXTINGUISHED AT THE END OF THE EVENT PRIOR TO DISPOSAL			
23			DEVICES SHALL NOT BE DISPOSED OF UNTIL COOL TO TOUCH.			
24		(G)	A "FLAMING SWORD" OR OTHER EQUIPMENT INVOLVING OPEN FLAMES AND			
25			FLAMED DISHES SHALL COMPLY WITH THIS SECTION.			
26	(274)	SUBS	EECTION 20.1.5.3(7)			
27		Inse	RT NEW SUBSECTION $20.1.5.3(7)$ AFTER SUBSECTION $20.1.5.3(6)$ AS FOLLOWS:			
28		(7)	OPEN FLAME DEVICES USED FOR COOKING AND PYROTECHNIC DISPLAYS			
29			SHALL BE APPROVED BY THE AHJ. A PERMIT FOR PYROTECHNIC DISPLAYS			
30			SHALL BE OBTAINED FROM THE OFFICE OF THE STATE FIRE MARSHAL.			
31	(275)	SUBS	SECTION 20.1.5.5.4.12			

1		AMEND THIS SUBSECTION TO DELETE "20.1.5.5.4.12.5" AND SUBSTITUTE
2		"20.1.5.5.4.12.10".
3	(276)	Subsection 20.1.5.5.4.12.6
4		ADD NEW SUBSECTION 20.1.5.5.4.12.6 AFTER SUBSECTION 20.1.5.5.4.12.5 AS
5		FOLLOWS:
6		THE PERSON WHO CAUSED THE VEHICLE TO BE DISPLAYED SHALL PROVIDE A NAME
7		AND A 24-HOUR TELEPHONE NUMBER FOR A RESPONSIBLE PERSON FOR THE
8		VEHICLE. THIS INFORMATION SHALL BE KEPT WITH THE VEHICLE, THE SECURITY
9		OFFICE AND THE MANAGEMENT OFFICE.
10	(277)	Subsection 20.1.5.5.4.12.7
11		ADD NEW SUBSECTION 20.1.5.5.4.12.7 AFTER SUBSECTION 20.1.5.5.4.12.6 AS
12		FOLLOWS:
13		AN IGNITION KEY AND DOOR KEY SHALL BE MADE AVAILABLE AND MAY BE KEPT
14		WITH THE SECURITY OFFICE OR THE MANAGEMENT OFFICE.
15	(278)	Subsection 20.1.5.5.4.12.8
16		ADD NEW SUBSECTION $20.1.5.5.4.12.8$ AFTER SUBSECTION $20.1.5.5.4.12.7$ AS
17		FOLLOWS:
18		AT NO TIME SHALL THE PLACEMENT OF THE VEHICLE IMPEDE OR OTHERWISE BLOCK
19		ANY EXIT OR EXIT ACCESS.
20	(279)	Subsection 20.1.5.5.4.12.9
21		ADD NEW SUBSECTION 20.1.5.5.4.12.9 AFTER SUBSECTION 20.1.5.5.4.12.8 AS
22		FOLLOWS:
23		ELECTRIC AND HYBRID VEHICLES FOLLOW THE SAME REQUIREMENTS AS THIS
24		SECTION.
25	(280)	SUBSECTION 20.1.5.5.4.12.10
26		ADD NEW SUBSECTION 20.1.5.5.4.12.10 AFTER SUBSECTION 20.1.5.5.4.12.9 AS
27		FOLLOWS:
28		LNG and LPG vehicles using compressed flammable gases are not
29		ALLOWED. THE OFFICE OF THE FIRE MARSHAL MAY PERMIT LIMITED USE OF
30		FLAMMABLE GASES UNDER AHJ APPROVAL.
31	(281)	SUBSECTION 20.1.5.6.2

1		DELET	E THIS S	SUBSECTION AND SUBSTITUTE THE FOLLOWING:		
2		Тне ср	THE CROWD MANAGER SHALL RECEIVE TRAINING, APPROVED BY THE AHJ, IN			
3		CROWI	CROWD MANAGEMENT TECHNIQUES.			
4	(282)	SUBSEC	SUBSECTION 20.1.5.8.3			
5		DELET	E THIS	SECTION AND SUBSTITUTE THE FOLLOWING:		
6		WHEN	THE CO	DE OFFICIAL FINDS AN OVERCROWDED CONDITION, OBSTRUCTION IN		
7		OR TO	ГНЕ МЕ	ANS OF EGRESS, A LOCKED EXIT DOOR, OR ANY OTHER HAZARD TO		
8		LIFE SA	FETY,	THE EVENT SHALL BE STOPPED UNTIL THE SITUATION IS CORRECTED.		
9		Тне ср	ROWD M	1ANAGER, SUPERVISOR, AND OWNER SHALL ENSURE THAT THE		
10		NUMBE	R OF PA	ATRONS IN THE OCCUPANCY (BUILDING, STRUCTURE, SITE, OR AREA)		
11		DOES N	OT EXC	CEED THE POSTED OCCUPANT LOAD. THE RESPONSIBLE PERSON IN		
12		CHARG	E OF TH	HE ASSEMBLY OCCUPANCY SHALL:		
13		(1)	IMMEI	DIATELY PRIOR TO THE BEGINNING OF THE EVENT POINT OUT THE		
14			NUMB	ER AND LOCATION OF EXITS;		
15		(2)	STATE	OR DISPLAY THE FOLLOWING: "NOTICE. FOR YOUR SAFETY, LOOK		
16			FOR Y	OUR NEAREST EXIT. IN CASE OF AN EMERGENCY—WALK, DO NOT		
17			RUN, 7	TO THAT EXIT" WHICH SHALL BE STATED OR DISPLAYED IN ONE OF THE		
18			FOLLO	WING METHODS:		
19			(A)	AN ORAL ANNOUNCEMENT AT THE BEGINNING OF THE EVENT;		
20			(B)	SHOWING THE NOTICE ON THE MOTION PICTURE SCREEN;		
21			(C)	Printing the notice in bold letters not less than $^{1}\!\!/_{4}$ inch in		
22				HEIGHT ON THE BACK OF THE EVENT PROGRAM (NOTHING BUT THE		
23				NOTICE SHALL BE PLACED ON THE BACK OF THE PROGRAM); OR		
24			(D)	HAVING A FIXED SIGN OR SIGNS DISPLAYING THE NOTICE THAT CAN		
25				BE EASILY READ FROM EACH POINT IN THE ASSEMBLY ROOM;		
26		(3)	Make	E AN INSPECTION BEFORE THE EVENT TO VERIFY THAT THE DOORS ARE		
27			UNLO	CKED AND THAT THE MEANS OF EGRESS ARE FREE OF OBSTRUCTIONS;		
28		(4)	Corr	ECT ANY DEFICIENCIES FOUND PRIOR TO THE START OF THE EVENT;		
29			AND			
30		(5)	PREV	ENT OVERCROWDING BY BLOCKING ADMITTANCE OF ANY PERSON		
31			BEYO	ND THE POSTED OCCUPANT LOAD.		

1	(283)	Subsection 20.1.5.9.1
2		DELETE THIS SECTION AND SUBSTITUTE:
3		Smoking shall meet the requirements in title 12 , subtitle 6 of the
4		HOWARD COUNTY CODE.
5	(284)	SUBSECTION 20.1.5.9.2
6		DELETE THIS SUBSECTION AND SUBSTITUTE:
7		In rooms or areas where smoking is prohibited, signage shall meet the
8		REQUIREMENTS IN TITLE 12, SUBTITLE 6 OF THE HOWARD COUNTY CODE.
9	(285)	SUBSECTION 20.1.5.10.1.1
10		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
11		Seats in assembly occupancies with $200\mathrm{or}$ more chairs shall be securely
12		FASTENED TO THE FLOOR, EXCEPT WHERE FASTENED TOGETHER IN GROUPS OF NOT
13		Less than three, and as permitted by $20.1.5.10.1.2$ and $20.1.5.10.2$.
14	(286)	SUBSECTION 20.1.5.10.4.1
15		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
16		Where required by the AHJ, A room or space shall be posted with an
17		APPROVED LEGIBLE SIGN IN CONTRASTING COLORS AND CONSPICUOUSLY LOCATED
18		NEAR THE MAIN EXIT FROM THE ROOM OR SPACE STATING THE MAXIMUM NUMBER
19		OF OCCUPANTS PERMITTED WITHIN THE SPACE. THE POSTING LOCATION SHALL BE
20		DETERMINED BY THE AHJ. THE MAXIMUM NUMBER OF OCCUPANTS SHALL BE
21		DETERMINED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE
22		NFPA LIFE SAFETY CODE. A ROOM OR SPACE WHICH HAS A MULTIPLE-USE
23		CAPACITY, SHALL BE POSTED FOR ALL USES. THE OWNER OR MANAGER OF THE
24		OCCUPANCY SHALL INSTALL AND MAINTAIN THE SIGNS. SIGNS SHALL BE SUPPLIED
25		BY THE AHJ.
26	(287)	Subsection 20.1.5.10.4.2
27		DELETE THIS SUBSECTION.
28	(288)	SUBSECTION 20.1.5.10.4.3
29		DELETE THIS SUBSECTION.
30	(289)	SUBSECTION 20.2.4.2.3
31		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:

1		FIREE	MERGE	NCY EGI	RESS DRILLS SHALL BE CONDUCTED AS FOLLOWS:
2		(1)	Not l	ESS THA	AN ONE FIRE EMERGENCY EGRESS DRILL SHALL BE CONDUCTED
3			EVERY	MONT!	H THE FACILITY IS IN SESSION, UNLESS THE FOLLOWING
4			CRITE	RIA ARE	EMET:
5			(A)	In cli	MATES WHERE THE WEATHER IS SEVERE, THE MONTHLY FIRE
6				EMER	GENCY EGRESS DRILLS SHALL BE PERMITTED TO BE DEFERRED;
7				AND	
8			(B)	In edu	UCATIONAL OCCUPANCIES WHICH ARE:
9				I.	FULLY PROTECTED BY AN AUTOMATIC SPRINKLER SYSTEM,
10					THE TOTAL NUMBER OF ANNUAL FIRE EMERGENCY EGRESS
11					DRILLS SHALL BE FIVE, WITH AT LEAST TWO OF THE
12					REQUIRED DRILLS CONDUCTED IN THE FIRST FOUR MONTHS
13					OF THE SCHOOL YEAR; OR
14				II.	NOT FULLY PROTECTED BY AN AUTOMATIC SPRINKLER
15					SYSTEM, THE TOTAL NUMBER OF ANNUAL FIRE EMERGENCY
16					EGRESS DRILLS SHALL BE EIGHT, WITH AT LEAST THREE OF
17					THE REQUIRED DRILLS CONDUCTED IN THE FIRST FOUR
18					MONTHS OF THE SCHOOL YEAR.
19		(2)	ALL O	CCUPA	NTS OF THE BUILDING SHALL PARTICIPATE IN THE FIRE
20			EMER	GENCY I	EGRESS DRILL.
21		(3)	One f	IRE EMI	ERGENCY EGRESS DRILL, OTHER THAN FOR EDUCATIONAL
22			OCCUI	PANCIES	S THAT ARE OPEN ON A YEAR-ROUND BASIS, SHALL BE
23			REQUI	RED WI	THIN THE FIRST 30 DAYS OF OPERATION.
24	(290)	SUBSE	CTION 2	20.2.4.2	.3.1
25		Add s	UBSECT	tion 20.	.2.4.2.3.1 AFTER SUBSECTION 20.2.4.2.3 AS FOLLOWS:
26		Тне А	HJ SHA	LL HAV	E THE AUTHORITY TO REQUIRE ADDITIONAL EGRESS DRILLS
27		THROU	JGHOUT	THE YE	EAR.
28	(291)	SUBSE	CTION 2	20.3.4.1	.1
29		DELET	E THIS	SUBSEC	TION AND SUBSTITUTE THE FOLLOWING:
30		A FAM	ILY DA	Y CARE	HOME SHALL MEET THE FOLLOWING REQUIREMENTS:
31		(1)	THE F	AMILY I	DAY CARE HOME SHALL NOT SERVE MORE THAN 8 CLIENTS;

1		(2)	A CHI	LD SHALL BE COUNTED AS A CLIENT SERVED IF THE CHILD:
2			(A)	Is under the age of 2 years; and
3			(B)	Is the child of the day care home owner or operator, or of
4				AN EMPLOYEE OF THE FAMILY DAY CARE HOME;
5		(3)	THER	e shall not be more than 4 children under the age of 2 years:
6			AND	
7		(4)	For c	CHILDREN UNDER THE AGE OF 2 YEARS, AN ADULT TO CHILD RATIO OF
8			AT LE	ast 1 adult to every 2 children shall be maintained at all
9			TIMES	3.
10	(292)	SUBSE	CTION 2	20.3.4.1.1.1
11		Add n	EW SU	BSECTION 20.3.4.1.1.1 AFTER SUBSECTION 20.3.4.1.1 AS FOLLOWS:
12		A GRO	UP DAY	CARE HOME SHALL MEET THE FOLLOWING REQUIREMENTS:
13		(1)	THE H	IOME SHALL NOT SERVE MORE THAN 12 CLIENTS;
14		(2)	А сні	LD SHALL BE COUNTED AS A CLIENT SERVED IF THE CHILD:
15			(A)	Is under the age of 2 years; and
16			(B)	Is the child of the day care home owner or operator, or of
17				AN EMPLOYEE OF THE GROUP DAY CARE HOME;
18		(3)	THER	e shall not be more than 4 children under the age of 2 years:
19		(4)	THE N	MINIMUM STAFF TO CLIENT RATIO SHALL NOT BE LESS THAN 2 STAFF
20			FOR U	p to 12 clients or 1 adult for every 6 children; and
21		(5)	For c	CHILDREN UNDER THE AGE OF 2 YEARS, AN ADULT TO CHILD RATIO OF
22			AT LE	ast 1 adult to every 2 children shall be maintained at all
23			TIMES	3.
24	(293)	SUBSE	CTION 2	20.3.4.1.2
25		DELET	E THIS	SUBSECTION.
26	(294)	Subse	CTION 2	20.3.4.1.7
27		ADD N	EW SUI	SSECTION 20.3.4.1.7 AFTER SUBSECTION 20.3.4.1.6 AS FOLLOWS:
28		A DAY	CARE	CENTER IS GOVERNED BY THE REQUIREMENTS FOR AN EDUCATIONAL
29		OCCUF	'ANCY I	F THE DAY CARE CENTER PROVIDES DAY CARE FOR SCHOOL-AGE
30		CHILD	REN BE	FORE AND AFTER SCHOOL HOURS AND PROVIDES CARE IN A BUILDING
31		WHICH	I IS IN I	ISE AS A PUBLIC OR PRIVATE SCHOOL.

1	(295)	SUBSE	ECTION 20.3.4.2.3.4.1
2		Addi	NEW SUBSECTION $20.3.4.2.3.4.1$ AFTER SUBSECTION $20.3.4.2.3.4$ AS FOLLOWS:
3		A BUI	LKHEAD DOOR SHALL NOT BE A PRIMARY MEANS OF EMERGENCY EGRESS.
4	(296)	SUBSE	ECTION 20.3.4.2.3.4.2
5		ADD	NEW SUBSECTION $20.3.4.2.3.4.2$ AFTER SUBSECTION $20.3.4.2.3.4.1$ AS
6		FOLLO	OWS: A SLIDING DOOR USED AS A REQUIRED MEANS OF EGRESS SHALL MEET
7		THE F	OLLOWING REQUIREMENTS:
8		(1)	The sliding door shall have only one, easily operated locking
9			DEVICE THAT DOES NOT REQUIRE SPECIAL KNOWLEDGE, EFFORT, OR TOOLS
10			TO OPERATE;
11		(2)	THERE SHALL NOT BE DRAPERIES, SCREENS, OR STORM DOORS THAT COULD
12			IMPEDE EGRESS;
13		(3)	The sill or track height may not exceed $lac{1}{2}$ inch above the interior
14			FINISH FLOOR;
15		(4)	THE SURFACE ONTO WHICH AN EXIT IS MADE SHALL BE AN ALL-WEATHER
16			SURFACE, SUCH AS A DECK, PATIO, OR SIDEWALK;
17		(5)	THE FLOOR LEVEL OUTSIDE THE DOOR MAY BE ONE STEP LOWER THAN THE
18			INSIDE, PROVIDED THAT THIS STEP MEETS THE REQUIREMENTS IN THE
19			BUILDING CODE;
20		(6)	The sliding door shall open to a clear open width of at least 28
21			INCHES;
22		(7)	EACH DAY BEFORE DAY CARE USE, THE SLIDING DOOR SHALL BE UNLOCKED
23			AND TESTED TO THE FULL REQUIRED WIDTH; AND
24		(8)	During periods of snow or freezing rain, the door track shall be
25			KEPT CLEAR OF SNOW OR FREEZING RAIN AND THE DOOR OPENED
26			PERIODICALLY THROUGHOUT THE DAY IN ORDER TO ENSURE PROPER
27			OPERATION.
28	(297)	SUBSI	ECTION 20.3.4.2.3.4.3
29		ADD	NEW SUBSECTION 20.3.4.2.3.4.3 AFTER SUBSECTION 20.3.4.2.3.4.2 AS
30		FOLL	OWS:

1		IF A DEADBOLT LOCK IS PROVIDED WITH AN APPROVED INTERIOR LATCH, THE
2		DEADBOLT LOCK SHALL BE OF A CAPTURED KEY DESIGN FROM WHICH THE KEY
3		CANNOT BE REMOVED FROM THE INTERIOR SIDE OF THE LOCK WHEN IN THE LOCKED
4		POSITION. THE LOCK SHALL BE UNLOCKED AT ALL TIMES WHEN THE HOME IS
5		OCCUPIED FOR THE FAMILY DAY CARE USE. A DOUBLE KEYED, DEADBOLT LOCK
6		MAY BE USED ON THE SECONDARY MEANS OF EGRESS IF THE KEY IS READILY
7		ACCESSIBLE WHEN THE DAY CARE IS IN OPERATION.
8	(298)	SUBSECTION 20.3.4.2.3.6
9		AMEND THIS SUBSECTION TO ADD "EXCEPT IN DAY CARE HOMES WITH THREE OR
10		FEWER CLIENTS FOR OVERNIGHT LODGING" AFTER "PRESENT".
11	(299)	SUBSECTION 25.1.3.6.
12		ADD NEW SUBSECTION 25.1.3.6 AFTER SUBSECTION 25.1.3.5 AS FOLLOWS:
13		IF ARTIFICIAL LIGHTING IS REQUIRED FOR VISIBILITY IN THE TENT, THEN
14		EMERGENCY LIGHTING IS REQUIRED IN THE EVENT THAT THE ARTIFICIAL LIGHTING
15		FAILS.
16	(300)	SUBSECTION 25.1.3.7
17		ADD NEW SUBSECTION 25.1.3.7 AFTER SUBSECTION 25.1.3.6 AS FOLLOWS:
18		A TENT SHALL NOT BLOCK ANY EXIT FROM A STRUCTURE OR CREATE A SITUATION
19		WHERE THE BUILDING OCCUPANTS WILL EXIT THROUGH THE TENT TO GET TO A SAFE
20		AREA.
21	(301)	SUBSECTION 25.1.3.8
22		ADD NEW SUBSECTION 25.1.3.8 AFTER SUBSECTION 25.1.3.7 AS FOLLOWS:
23		ALL TENTS SHALL HAVE A MINIMUM OF ONE EXIT. TENTS WITH A CAPACITY OF
24		GREATER THAN 49 PERSONS SHALL HAVE TWO EXITS. EGRESS DOORS SHALL BE OF
25		CONTRASTING COLOR. EXIT SIGNS SHALL BE PROVIDED. DRAPERIES, HANGINGS OR
26		CURTAINS USED ON EXITS SHALL COMPLY WITH NFPA 1 SECTION 14.10.2.
27	(302)	SUBSECTION 25.1.5.3
28		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
29		HAY, STRAW, SHAVINGS OR SIMILAR COMBUSTIBLE MATERIAL SHALL NOT BE
30		PERMITTED WITHIN THE STRUCTURE UNLESS APPROVED IN WRITING BY THE AHJ.
31	(303)	SUBSECTION 25.1.9.3.1

1		ADD NEW SUBSECTION 25.1.9.3.1 AFTER SUBSECTION 25.1.9.3 AS FOLLOWS:
2		PORTABLE DISTRIBUTION OR TERMINATION BOXES SHALL BE DESIGNED SO NO LIVE
3		WIRES ARE EXPOSED. WHERE INSTALLED OUTDOORS, THE BOXES SHALL BE
4		WEATHERPROOF AND MOUNTED NOT LESS THAN SIX INCHES ABOVE THE GROUND.
5	(304)	SUBSECTION 25.1.9.4
6		ADD NEW SUBSECTION 25.1.9.4 AFTER SUBSECTION 25.1.9.3 AS FOLLOWS:
7		IF REQUIRED BY THE DEPARTMENT OF INSPECTIONS, LICENSES AND PERMITS, ALL
8		ELECTRICAL DEVICES, WIRING, AND GENERATORS MAY BE USED IF INSPECTED AND
9		ISSUED A PERMIT PRIOR TO USE.
10	(305)	SUBSECTION 25.1.10.1.3.1
11		ADD NEW SUBSECTION 25.1.10.1.3.1 AFTER SUBSECTION 25.1.10.1.3 AS FOLLOWS:
12		FUEL FIRED DEVICES SHALL BE LOCATED ON THE EXTERIOR OF THE TENT AND AIR
13		DUCTED TO THE TENT.
14	(306)	SUBSECTION 25.1.10.1.6
15		Amend subsection $25.1.10.1.6$ to delete "installed" and substitute
16		"LOCATED".
17	(307)	SUBSECTION 25.1.10.2.3
18		AMEND THIS SECTION TO ADD THE FOLLOWING:
19		ELECTRIC HEATERS CANNOT BE USED INSIDE A TENT UNLESS APPROVED BY THE
20		AHJ FOR EACH USE.
21	(308)	SUBSECTION 25.2.1.3
22		ADD NEW SUBSECTION 25.2.1.3 AFTER SUBSECTION 25.2.1.2 AS FOLLOWS:
23		Any tent over $120\mathrm{feet}^2\mathrm{requires}$ a permit from Howard County
24		DEPARTMENT OF INSPECTION, LICENSE AND PERMITS. TENTS AND CANOPIES USED
25		for food service require a permit from the Howard County Health
26		DEPARTMENT. TENTS SHALL BE PERMITTED ON A TEMPORARY BASIS.
27	(309)	SUBSECTION 25.2.1.4
28		ADD NEW SUBSECTION 25.2.1.4 AFTER SUBSECTION 25.2.1.3 AS FOLLOWS:
29		TENTS, CANOPIES, OR MEMBRANE STRUCTURES SHALL NOT BE SET UP INSIDE A
30		BUILDING UNLESS APPROVED IN WRITING BY THE AHJ.
31	(310)	SUBSECTION 25, 2, 2, 1

1		AMEND SUBSECTION 25.2.2.1 TO ADD ", OR APPROVED BY THE AHJ" TO THE END.
2	(311)	SUBSECTION 25.2.2.2(3)
3		ADD NEW SUBSECTION 25.2.2.2(3) AFTER SUBSECTION 25.2.2.2(2) AS FOLLOWS:
4		(3) THE TENT OR CANOPY SHALL HAVE A LABEL AFFIXED STATING THAT THE
5		TENT COMPLIES WITH NFPA 701 OR EQUIVALENT TESTING STANDARD
6		APPROVED BY THE AHJ. NON-FIXED CERTIFICATION MAY BE ACCEPTABLE
7		PROVIDING IT IDENTIFIES THE MAKE AND MODEL OF THE TENT.
8	(312)	SUBSECTION 25.2.3.4
9		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
10		A separation of 10 feet is required after every 100 feet of tents. A
11		separation of 10 feet shall be maintained between rows of tents. A row
12		of tents shall not be wider than 40 feet.
13	(313)	SUBSECTION 26.1.6.2
14		ADD NEW SUBSECTION 26.1.6.2 AFTER SUBSECTION 26.1.6.1 AS FOLLOWS:
15		When the AHJ requires a hazard assessment, the assessment shall be
16		CONDUCTED BY A TECHNICALLY QUALIFIED PERSON ACCEPTABLE TO THE AHJ.
17	(314)	SUBSECTION 26.1.6.3
18		ADD NEW SUBSECTION 26.1.6.3 AFTER SUBSECTION 26.1.6.2 AS FOLLOWS:
19		When the AHJ requires a hazard assessment, the assessment shall
20		INCLUDE A COMPLETED HAZARDOUS MATERIALS INVENTORY STATEMENT FOR THE
21		CHEMICALS USED IN EACH LABORATORY. THIS STATEMENT SHALL COMPLY WITH
22		THE HAZARDOUS MATERIALS PERMITTING PROCESS SET FORTH IN THIS CODE.
23	(315)	SUBSECTION 26.1.6.4
24		ADD NEW SUBSECTION 26.1.6.4 AFTER SUBSECTION 26.1.6.3 AS FOLLOWS:
25		NEW LABORATORIES, OR LABORATORIES WHERE THE NFPA 45 LABORATORY
26		HAZARD CLASSIFICATION CHANGES, SHALL POST AN INFORMATIONAL PLACARD
27		NEAR THE MAIN ENTRANCE TO THE LABORATORY. THE PLACARD SHALL STATE THE
28		BUILDING NAME OR ADDRESS, ROOM NUMBER, NFPA 45 LABORATORY HAZARD
29		CLASSIFICATION, MAXIMUM ALLOWABLE QUANTITIES OF FLAMMABLE LIQUIDS
30		BOTH INSIDE A STORAGE CABINET AND OPEN USE, AND MAXIMUM QUANTITIES OF
31		FLAMMABLE GASES PERMITTED WITHIN THE LABORATORY.

1	(316)	SECTION 27.2
2		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
3		THE FIRE SAFETY REQUIREMENTS FOR THE INSTALLATION OF A MANUFACTURED
4		HOME AND A MANUFACTURED HOME SITE, INCLUDING AN ACCESSORY BUILDING,
5		STRUCTURE, AND COMMUNITY, SHALL COMPLY WITH NFPA 501A, STANDARD FOR
6		FIRE SAFETY CRITERIA FOR MANUFACTURED HOME INSTALLATIONS, SITE, AND
7		Communities, Section 27.1 of this Code, and title 16 , subtitle 5 of the
8		HOWARD COUNTY CODE.
9	(317)	SECTION 31.2.1
10		ADD NEW SECTION 31.2.1 AFTER SECTION 31.2 AS FOLLOWS:
11		(1) A COPY OF THE FACILITY'S NATURAL WOOD WASTE RECYCLING FACILITY
12		or composting permit application, including the Operations Plan
13		and the Emergency Preparedness Manual, shall be sent to the
14		AHJ for review and recommendations to the Department of
15		Planning and Zoning.
16		(2) A copy of the information required by paragraph (1) of this
17		subsection shall be submitted to the AHJ with each S tate permit
18		renewal (5 year renewals).
19	(318)	SUBSECTION 31.3.4.3.2.1
20		ADD NEW SUBSECTION 31.3.4.3.2.1 AFTER SUBSECTION 31.3.4.3.2 AS FOLLOWS:
21		THE PRIMARY ROAD SHALL:
22		(1) BE KEPT ADEQUATELY CLEAR IN ORDER TO PROVIDE ACCESS TO THE
23		PROCESSING/STORAGE AREA; AND
24		(2) BE PAVED OR CONSTRUCTED SO AS TO PROVIDE ALL WEATHER, YEAR-
25		round, access by fire apparatus with a weight of $80,\!000\mathrm{GVW}$.
26	(319)	SUBSECTION 31.3.6.2.2
27		ADD NEW PARAGRAPH (9) AFTER PARAGRAPH (8) AS FOLLOWS:
28		(9) A PILE CONTAINING LEAVES AND OTHER EXTRANEOUS OR HOGGED
29		MATERIAL, SUCH AS A WHOLE TREE CHIP PILE, SHALL BE TURNED OR
30		RECLAIMED EVERY THREE MONTHS.
31	(320)	SUBSECTION 31.3.6.3.2

1		DELET	E THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
2		PILES	may not exceed 18 feet in height, 50 feet in width, and 350 feet in
3		LENGT	TH. TWO PILES SHALL BE DIVIDED BY A FIRE LANE HAVING AT LEAST 30 FEET
4		OF CLE	EAR SPACE AT THE BASE OF THE PILE.
5	(321)	SUBSE	CTION 31.3.6.3.2.1 THROUGH 31.3.6.3.2.3
6		DELET	E THESE SUBSECTIONS.
7	(322)	SUBSE	CTION 31.3.6.3.5.1
8		ADD N	IEW SUBSECTION 31.3.6.3.5.1 AFTER SUBSECTION 31.3.6.3.5 AS FOLLOWS:
9		IF THE	OPERATION IS LOCATED OUTSIDE OF A MUNICIPAL WATER SUPPLY THE
10		FOLLO	WING WILL APPLY:
11		(1)	THE AHJ WILL REQUIRE A RELIABLE CERTIFIED WATER SUPPLY SYSTEM
12			WITH THE CAPABILITY TO SUPPLY 1,000 GALLONS PER EVERY 10,000 CUBIC
13			FEET OF PILE. THE SUPPLY SYSTEM MUST BE CAPABLE OF PRODUCING A
14			MINIMUM OF 250 GPM (PREFERRED IS 500 GPM) FOR AT LEAST 2 HOURS.
15		(2)	THE MULCH/WOOD PROCESSING OPERATION SHALL HAVE A FIRE STATION
16			LOCATED WITHIN 5 TRAVEL MILES OF THE LOCATION.
17		(3)	IF THE WATER SUPPLY IS STATIC IT IS TO BE CERTIFIED BY AN ENGINEER AND
18			CAPABLE TO SUPPLY THE AMOUNT REQUIRED BY PARAGRAPH (1) OF THIS
19			SUBSECTION. IF THE WATER SUPPLY IS BELOW THE MINIMUM AMOUNT, THEN
20			The supply must be capable of at least $30,\!000$ gallons at all times.
21			THE MAXIMUM SIZE OF WATER SUPPLY NEEDED MAY BE BASED ON THE
22			PROPOSED OPERATION AND APPROVED BY THE AHJ.
23		(4)	Based on the amount of material on site, other provisions such as
24			SPRINKLERS, PRE-PIPED SYSTEMS, OR CONSTANT MONITORING OF THE PILE
25			MAY BE REQUIRED.
26	(323)	SECTIO	DN 33.1.2
27		DELET	E THIS SECTION AND SUBSTITUTE THE FOLLOWING:
28		WHER	E REQUIRED, A PERMIT FOR OUTSIDE STORAGE SHALL BE OBTAINED FROM THE
29		MARY	LAND DEPARTMENT OF THE ENVIRONMENT. A PERMIT FROM THE AHJ IS
30		REQUIE	RED FOR THE STORAGE OF 500 TIRES OR MORE. A PERSON MAY NOT STORE
31		MORE '	THAN 5.000 TIRES.

1	(324)	SECTION 33.1.12		
2		ADD NEW SECTION 33.1.12 AFTER SECTION 33.1.11 AS FOLLOWS:		
3		The AHJ may require a security fence around the tire storage area.		
4	(325)	SECTION 33.1.13		
5		ADD NEW SECTION 33.1.13 AFTER SECTION 33.1.12 AS FOLLOWS:		
6		The storage of fewer than 500 tires shall meet the following		
7		REQUIREMENTS:		
8		(1) TIRES SHALL NOT BE STORED IN SINGULAR VERTICAL STACKS;		
9		(2) STORAGE PILES SHALL NOT EXCEED 10 FEET IN HEIGHT;		
10		(3) STORAGE PILES SHALL NOT BE LARGER THAN 1,250 CUBIC FEET; AND		
11		(4) TIRES SHALL BE SEPARATED FROM THE PROPERTY LINE, BUILDINGS,		
12		STRUCTURES, OR ANYTHING DETERMINED AS AT RISK BY THE AHJ, BY A		
13		MINIMUM OF 25 FEET.		
14	(326)	SUBSECTION 33.2.2.3		
15		Delete "20 ft (6m)" and substitute "10 ft".		
16	(327)	SUBSECTION 34.1.3		
17		AMEND THIS SUBSECTION TO REPLACE "AN APPROVED STORAGE" WITH "WHERE		
18		REQUIRED BY THE AHJ, AN APPROVED STORAGE".		
19	(328)	Chapter 35		
20		DELETE THIS CHAPTER IN ITS ENTIRETY.		
21	(329)	SUBSECTION 42.7.5.5		
22		AMEND THIS SUBSECTION TO ADD THE FOLLOWING:		
23		THE FOLLOWING INFORMATION SHALL BE CONSPICUOUSLY POSTED IN THIS AREA:		
24		(1) THE EXACT ADDRESS OF THE UNATTENDED SELF-SERVICE FACILITY; AND		
25		(2) THE TELEPHONE NUMBER OF THE OWNER OR OPERATOR OF THE		
26		UNATTENDED SELF-SERVICE FACILITY.		
27	(330)	SUBSECTION 42.7.5.7		
28		ADD NEW SUBSECTION 42.7.5.7 AFTER SUBSECTION 42.7.5.6 AS FOLLOWS:		
29		An owner, manager, or employee shall conduct a daily site visit to		
30		ENSURE THAT ALL EQUIPMENT IS OPERATING PROPERLY.		
31	(331)	Subsection 42.7.5.8		

1		ADD NEW SUBSECTION 42.7.5.8 AFTER SUBSECTION 42.7.5.7 AS FOLLOWS:			
2		AN OWNER, MANAGER, OR EMPLOYEE SHALL CONDUCT INSPECTIONS AND			
3		MAINTENANCE OF EQUIPMENT AT REGULAR INTERVALS AND IN ACCORDANCE WITH			
4		THE MANUFACTURER'S INSTRUCTIONS.			
5	(332)	SUBSECTION 42.7.5.9			
6		ADD NEW SUBSECTION 42.7.5.9 AFTER SUBSECTION 42.7.5.8 AS FOLLOWS:			
7		FUEL DISPENSING EQUIPMENT SHALL COMPLY WITH ONE OF THE FOLLOWING:			
8		(1) THE AMOUNT OF FUEL BEING DISPENSED IS LIMITED IN QUANTITY BY A PRE-			
9		PROGRAMMED CARD; OR			
10		(2) THE DISPENSING DEVICE SHALL BE PROGRAMMED OR SET TO LIMIT			
11		Uninterrupted fuel delivery of not more than 25 gallons and			
12		SHALL REQUIRE MANUAL ACTION TO RESUME CONTINUED DELIVERY.			
13	(333)	SUBSECTION 50.1.3			
14		Amend this subsection to insert, "under a canopy" after "tents" and to			
15		INSERT "AND THIS CHAPTER" TO THE END.			
16	(334)	SUBSECTION 50.2.1.2			
17		AMEND THIS SECTION TO INSERT "THE AHJ AND" AFTER "REQUIREMENTS OF".			
18	(335)	SECTION 50.4.1			
19		AMEND THIS SUBSECTION TO DELETE "AHJ" AND SUBSTITUTE "DEPARTMENT OF			
20		Inspections, Licenses, and Permits".			
21	(336)	Subsection 50.8.1.2			
22		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:			
23		ALL MOBILE FOOD VENDING PLATFORMS SHALL BE INSPECTED BY THE AHJ. FOR			
24		PURPOSES OF THIS CODE, MOBILE FOOD VENDING PLATFORM MEANS ANY			
25		PUSHCART, TRAILER, ENCLOSED TRAILER, OR ENCLOSED TRUCK THAT USES			
26		PROPANE OR ANY OTHER HEAT SOURCE TO PREPARE FOOD OR BEVERAGE FOR SALE.			
27	(337)	SUBSECTION 50.8.1.2.1			
28		ADD NEW SUBSECTION 50.8.1.2.1 AFTER SUBSECTION 50.8.1.2 AS FOLLOWS:			
29		LICENSING REQUIREMENTS. THE OWNER OR OPERATOR OF A MOBILE FOOD VENDING			
30		PLATFORM SHALL, BEFORE BEGINNING OPERATIONS, OBTAIN AN INSPECTION AND			
31		INSPECTION STICKER FROM THE AHJ AS FOLLOWS:			

1	(1)	THE C	OWNER OR OPERATOR OF A MOBILE FOOD VENDING PLATFORM SHALL
2		PROV	IDE THE FOLLOWING INFORMATION TO THE AHJ:
3		(A)	EVIDENCE OF A CURRENT HOWARD COUNTY HEALTH INSPECTION;
4		(B)	A VALID DRIVER'S LICENSE OR GOVERNMENT ISSUED ID;
5		(C)	Current vehicle registration;
6		(D)	CURRENT VEHICLE INSPECTION STICKER/PAPERWORK; AND
7		(E)	CURRENT VEHICLE STATE INSPECTION.
8	(2)	Inspe	CTIONS OF MOBILE FOOD VENDING PLATFORMS. THE AHJ MAY
9		COND	OUCT INSPECTIONS AT ANY TIME AS DEEMED NECESSARY TO ENSURE
10		COMP	LIANCE WITH THE PROVISIONS OF THIS CODE.
11		(A)	An inspection is required for any mobile food vending
12			PLATFORM THAT ESTABLISHES BUSINESS FOR ANY LENGTH OF TIME
13			IN HOWARD COUNTY. THE OWNER OR OPERATOR SHALL REQUEST
14			an annual or one-day inspection sticker at least $10\mathrm{days}$
15			PRIOR TO CONDUCTING BUSINESS IN HOWARD COUNTY.
16		(B)	THE AHJ SHALL DESIGNATE A LOCATION TO CONDUCT INSPECTIONS
17			Inspections or re-inspections shall be at designated times
18			EACH MONTH OR MAY BE ARRANGED BY APPOINTMENT.
19		(C)	Once the inspection is satisfactorily completed, the AHJ
20			SHALL ISSUE AN INSPECTION STICKER. EXCEPT FOR A ONE-DAY
21			INSPECTION STICKER, THE INSPECTION STICKER IS VALID FOR ONE
22			CALENDAR YEAR FROM THE LAST INSPECTION.
23		(D)	Mobile food vending platforms that fail the inspection
24			MAY NOT OPERATE.
25		(E)	ANY CHANGES TO ITEMS, PROCESSES, STORAGE OR CONFIGURATION
26			WITHIN THE SCOPE OF THE INSPECTION MUST BE APPROVED BY THE
27			AHJ in order to maintain the validity of an inspection
28			STICKER.
29		(F)	PROPANE CYLINDERS MUST BE IN COMPLIANCE WITH HYDROSTATIC
30			TEST DATES.
31	(3)	THE	OWNER OR OPERATOR OF A MOBILE FOOD VENDING PLATFORM SHALL:

1			(A)	OBTAIN ANY OTHER PERMITS AS REQUIRED, INCLUDING A
2				HAZARDOUS MATERIALS PERMIT WHERE APPLICABLE;
3			(B)	PAY ANY OTHER FEES AS REQUIRED BY LAW;
4			(C)	DISPLAY A VALID ANNUAL OR ONE-DAY INSPECTION STICKER; AND
5			(D)	COMPLETE A DAILY CHECKLIST APPROVED BY THE AHJ.
6	(338)	SUBSE	CTION 5	0.8.1.2.2
7		ADDN	IEW SUB	SECTION 50.8.1.2.2 AFTER SUBSECTION 50.8.1.2.1 AS FOLLOWS:
8		FEES F	RELATED	TO MOBILE FOOD VENDING PLATFORMS.
9		(1)	Тне А	HJ MAY CHARGE A FEE FOR AN INSPECTION OR RE-INSPECTION OF A
10			MOBIL	E FOOD VENDING PLATFORM.
11		(2)	Тне С	OUNTY COUNCIL MAY ADOPT BY RESOLUTION FEES FOR THE
12			INSPEC	TION AND RE-INSPECTION OF MOBILE FOOD VENDING PLATFORMS.
13		(3)	An ins	PECTION SHALL NOT BE PERFORMED WHERE AN OPERATOR HAS
14			FAILED	TO PAY INSPECTION FEES.
15	(339)	SUBSE	CTION 5	9.8.1.6
16		DELET	E THIS S	SUBSECTION AND SUBSTITUTE THE FOLLOWING:
17		Hazai	RDOUS M	MATERIALS AND STORAGE OF FLAMMABLE LIQUIDS FOR MOBILE FOOD
18		VENDI	NG PLAT	FORMS. THE STORAGE AND USE OF FLAMMABLE LIQUIDS SHALL
19		COMPI	Y WITH	NFPA 1, AND THE FOLLOWING:
20		(1)	Indivi	DUAL CONTAINERS, CARTONS, OR PACKAGES SHALL BE
21			CONSP	CUOUSLY MARKED OR LABELED IN AN APPROVED MANNER.
22		(2)	HAZAF	DOUS MATERIALS OR LIQUIDS SHALL BE DISPOSED OF IN THE PROPER
23			MANNE	ER AND SHALL NOT BE RELEASED INTO ANY SEWER, STORM DRAIN,
24			DITCH,	DRAINAGE CANAL, CREEK, STREAM, RIVER, LAKE OR TIDAL WATER
25			OR ON	THE GROUND, SIDEWALK, STREET, HIGHWAY, OR INTO THE
26			ATMOS	PHERE.
27	(340)	SUBSE	CTION 50	9.8.1.7
28		ADD N	EW SUB	SECTION 50.8.1.7 AFTER SUBSECTION 50.8.1.6 AS FOLLOWS:
29		Сомм	IERCIAL	OUTDOOR COOKING OPERATIONS. THESE REQUIREMENTS APPLY TO
30		COMM	ERCIAL	OUTDOOR COOKING OPERATIONS SUCH AS THOSE THAT TYPICALLY
31		TAKE	PLACE U	NDER A CANOPY OR TENT-TYPE STRUCTURE AT FAIRS, FESTIVALS

1		AND CARNIVALS. THIS INCLUDES, BUT IS NOT LIMITED TO, DEEP FRYING, SAUTEING,
2		AND GRILLING OPERATIONS.
3	(341)	SUBSECTION 50.8.1.7.1
4		Add new subsection $50.8.1.7.1$ after subsection $50.8.1.7$ as follows:
5		Tent and Canopy Requirements
6	(342)	SUBSECTION 50.8.1.7.1.1
7		ADD NEW SUBSECTION 50.8.1.7.1.1 AFTER SUBSECTION 50.8.1.7.1 AS FOLLOWS:
8		TENTS OR CANOPIES WHERE COOKING EQUIPMENT NOT PROTECTED IN ACCORDANCE
9		WITH NFPA 96 IS LOCATED SHALL NOT BE OCCUPIED BY THE PUBLIC AND SHALL BE
10		SEPARATED FROM OTHER TENTS, CANOPIES, STRUCTURES, OR VEHICLES BY A
11		minimum of 10 ft. unless otherwise approved in writing by the AHJ.
12	(343)	SUBSECTION 50.8.1.7.1.2
13		ADD NEW SUBSECTION 50.8.1.7.1.2 AFTER SUBSECTION 50.8.1.7.1.1 AS FOLLOWS:
14		ALL TENT AND CANOPY MATERIAL SHALL COMPLY WITH THE FLAME RESISTANCE
15		REQUIREMENTS OF SECTION 25.2.2.
16	(344)	SUBSECTION 50.8.1.7.2
17		ADD NEW SUBSECTION 50.8.1.7.2 AFTER SUBSECTION 50.8.1.7.1 AS FOLLOWS:
18		LP Gas Fuel Requirements
19		
20	(345)	SUBSECTION 50.8.1.7.2.1
21		ADD NEW SUBSECTION 50.8.1.7.2.1 AFTER SUBSECTION 50.8.1.7.2 AS FOLLOWS:
22		LP gas tank size shall be limited to 60 pounds. The total amount of LP
23		gas on site shall not exceed 60 pounds for each appliance that is rated
24		NOT MORE THAN $80,\!000$ BTU/HR AND 120 POUNDS FOR EACH APPLIANCE RATED
25		more than 80,000 btu/hr.
26	(346)	SUBSECTION 50.8.1.7.2.2
27		ADD NEW SUBSECTION 50.8.1.7.2.2 AFTER SUBSECTION 50.8.1.7.2.1 AS FOLLOWS:
28		TANKS SHALL BE MAINTAINED IN GOOD PHYSICAL CONDITION AND SHALL HAVE A
29		VALID HYDROSTATIC DATE STAMP.
30	(347)	SUBSECTION 50.8.1.7.2.3
21		ADD NEW SUBSECTION 50.8.1.7.2.3 AFTER SUBSECTION 50.8.1.7.2.2 AS FOLLOWS:

1		TANKS SHALL BE SECURED IN THEIR UPRIGHT POSITION WITH A CHAIN, STRAP, OR
2		OTHER APPROVED METHOD THAT PREVENTS THE TANK FROM TIPPING OVER.
3	(348)	SUBSECTION 50.8.1.7.2.4
4		ADD NEW SUBSECTION $50.8.1.7.2.4$ AFTER SUBSECTION $50.8.1.7.2.3$ AS FOLLOWS:
5		TANKS SHALL BE LOCATED SO THAT THEY ARE NOT ACCESSIBLE TO THE PUBLIC. LP
6		GAS TANKS SHALL BE LOCATED AT LEAST 5 FEET FROM ANY COOKING OR HEATING
7		EQUIPMENT, OR ANY FLAME DEVICE.
8	(349)	SUBSECTION 50.8.1.7.2.5
9		ADD NEW SUBSECTION 50.8.1.7.2.5 AFTER SUBSECTION 50.8.1.7.2.4 AS FOLLOWS:
10		ALL LP GAS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND COMPLY WITH THE
11		REQUIREMENTS OF NFPA 58.
12	(350)	SUBSECTION 50.8.1.7.2.6
13		ADD NEW SUBSECTION $50.8.1.7.2.6$ AFTER SUBSECTION $50.8.1.7.2.5$ AS FOLLOWS:
14		REGULATORS. SINGLE-STAGE REGULATORS MAY NOT SUPPLY EQUIPMENT THAT IS
15		rated more than 100,000 btu/hr rating. Two-stage regulators shall be
16		used with equipment that is rated more than $100,\!000$ btu/hr.
17	(351)	SUBSECTION 50.8.1.7.2.7
18		ADD NEW SUBSECTION $50.8.1.7.2.7$ AFTER SUBSECTION $50.8.1.7.2.6$ AS FOLLOWS:
19		A "NO SMOKING" SIGN NEXT TO OR DIRECTLY ABOVE THE GAS CONTAINER AND
20		VISIBLE TO THE PUBLIC SHALL BE INSTALLED. THE SIGN SHALL BE POSTED WITH A
21		MINIMUM OF 2 -INCH LETTERING AND MEET THE REQUIREMENTS SET FORTH IN THE
22		HOWARD COUNTY CODE, TITLE 12, SUBTITLE 6.
23	(352)	SUBSECTION 50.8.1.7.2.8
24		ADD NEW SUBSECTION 50.8.1.7.2.8 AFTER SUBSECTION 50.8.1.7.2.7 AS FOLLOWS:
25		PROPANE AND NATURAL GAS TANKS SHALL BE SHUT OFF WHILE THE MOBILE FOOD
26		VENDING PLATFORM IS IN MOTION, UNATTENDED, OR IN OVERNIGHT STORAGE.
27	(353)	Subsection 50.8.1.7.3
28		ADD NEW SUBSECTION 50.8.1.7.3 AFTER SUBSECTION 50.8.1.7.2 AS FOLLOWS:
29		GENERAL SAFETY REQUIREMENTS.
30	(354)	Subsection 50.8.1.7.3.1
21		ADD NEW SUBSECTION 50 & 1.7.3.1 APTED SUBSECTION 50 & 1.7.3 AS FOLLOWS:

1		ALL E	ELECTRICAL CORDS SHALL BE MAINTAINED IN A SAFE CONDITION AND SHALL	
2		BE SE	CURED TO PREVENT DAMAGE.	
3	(355)	Subsection 50.8.1.7.3.2		
4		ADD 1	NEW SUBSECTION 50.8.1.7.3.2 AFTER SUBSECTION 50.8.1.7.3.1 AS FOLLOWS;	
5		Mov	ABLE COOKING EQUIPMENT SHALL HAVE WHEELS REMOVED OR SHALL BE	
6		PLACI	ED ON BLOCKS OR OTHERWISE SECURED TO PREVENT MOVEMENT OF THE	
7		APPLI	ANCE DURING OPERATION.	
8	(356)	SUBSE	ECTION 50.8.1.7.3.3	
9		ADD	NEW SUBSECTION 50.8.1.7.3.3 AFTER SUBSECTION 50.8.1.7.3.2 AS FOLLOWS:	
10		PORT	ABLE FIRE EXTINGUISHERS SHALL BE PROVIDED IN ACCORDANCE WITH NFPA	
11		1, sec	CTION 13.6, THE AHJ, AND SHALL BE SPECIFICALLY LISTED FOR SUCH USE.	
12	(357)	SUBSI	ECTION 50.8.1.7.3.3.1	
13		ADD	new subsection $50.8.1.7.3.3.1$ after subsection $50.8.1.7.3.3$ as follows:	
14		FIRE I	EXTINGUISHERS ARE REQUIRED FOR ALL MOBILE FOOD VENDING PLATFORM AS	
15		FOLLOWS:		
16		(1)	ALL FIRE EXTINGUISHERS SHALL BE MAINTAINED AND INSPECTED ON AN	
17			annual basis. A fire extinguisher (minimum size of $2A\ 40\ BC$) is	
18			required in addition to any Class K extinguisher. If deep fat	
19			fryers are used operators shall have and maintain a Class ${ m K}$	
20			PORTABLE FIRE EXTINGUISHER.	
21		(2)	PORTABLE FIRE EXTINGUISHERS SHALL BE LOCATED IN CONSPICUOUS	
22			LOCATIONS WHERE THEY ARE READILY ACCESSIBLE AND IMMEDIATELY	
23			AVAILABLE FOR USE.	
24		(3)	If the platform is a towed trailer, the fire extinguisher shall be	
25			KEPT IN THE TRAILER, WHEN THE TRAILER IS OPERATING.	
26		(4)	FIRE EXTINGUISHERS SHALL BEAR A CURRENT INSPECTION TAG VALIDATED	
27			WITHIN THE PAST TWELVE MONTHS OR A RECEIPT OF PURCHASE WITHIN THE	
28			LAST TWELVE MONTHS SHALL BE AVAILABLE FOR INSPECTION.	
29	(358)	SUBSI	ECTION 50.8.1.8	
30		Add	NEW SUBSECTION 50.8.1.8 AFTER SUBSECTION 50.8.1.7 AS FOLLOWS:	

1		THERE SHALL BE NO OBSTRUCTIONS OR IMPEDIMENTS TO IMMEDIATE ESCAPE FROM
2		VEHICLES OR OTHER MOBILE UNITS USED FOR COOKING OPERATIONS.
3	(359)	SUBSECTION 50.8.7.4.4
4		AMEND THIS SUBSECTION TO REPLACE "NOT BE TRANSPORTED OR STORED INSIDE
5		THE VEHICLE" WITH "BE SECURED IN AN UPRIGHT POSITION DURING TRANSPORT
6		AND STORAGE."
7	(360)	SUBSECTION 50.8.8.4
8		ADD NEW SUBSECTION 50.8.8.4 AFTER SUBSECTION 50.8.8.3 AS FOLLOWS:
9		ELECTRICAL REQUIREMENTS. THE ELECTRICAL EQUIPMENT ON A MOBILE FOOD
10		VENDOR PLATFORM SHALL BE IN COMPLIANCE WITH THE HOWARD COUNTY
11		ELECTRICAL CODE
12	(361)	Subsection 60.1.1.1
13		ADD NEW SUBSECTION $60.1.1.1$, AFTER SECTION $60.1.1$ AS FOLLOWS:
14		HAZMAT PERMITTING. NOTWITHSTANDING ANY OTHER PROVISION OF THIS CODE,
15		An annual permit issued by the AHJ is required for any facility that
16		STORES, RECEIVES, DISPENSES, USES, OR HANDLES ANY HAZARDOUS MATERIALS
17		IDENTIFIED IN SUBSECTION $60.1.1.1(1)$ of this Code. For the purposes of this
18		SECTION, THE TERM "HAZARDOUS MATERIAL" IS EQUIVALENT TO "HAZARDOUS
19		SUBSTANCE" AND "HAZARDOUS CHEMICAL".
20		(1) THERE ARE FIVE TYPES OF HAZARDOUS MATERIAL PERMITS BASED ON THE
21		TYPE AND QUANTITY OF HAZARDOUS MATERIAL:
22		(A) Type I permits are required for hazardous chemicals
23		identified in $40~\mathrm{CFR}$ part 370 , subject to the Threshold
24		PLANNING QUANTITY ("TPQ") WHERE APPLICABLE THEREIN.
25		(B) Type II, Type III, and Type IV permits are required for
26		EXTREMELY HAZARDOUS SUBSTANCES, AS DEFINED IN 40 CFR PART
27		355, that have a TPQ of 10 pounds or less, that do not
28		OTHERWISE REQUIRE A TYPE I PERMIT, AS FOLLOWS:
29		(I) Type II permits are required for 5 pounds or more, up
30		to 10 pounds.

1			(II)	Type III permits are required for 1 pound or more, up
2				TO 5 POUNDS.
3			(III)	Type IV permits are required for amounts less than A
4				POUND
5		(C)	Түре	m V hazardous materials permits are required for any
6			SUBST	CANCE, IN ACCORDANCE WITH SECTION 1.12.8 OF THIS CODE,
7			THAT	does not otherwise require a Type I, II, III, or IV permit
8	(2)	A PER	MIT APF	PLICATION WILL NOT BE ACCEPTED UNLESS THE FOLLOWING
9		ITEMS	ARE SU	BMITTED WITH THE PERMIT APPLICATION:
10		(A)	A GEN	ieral site plan is required for Type I, II, and III
11			FACIL	ITIES. A GENERAL SITE PLAN SHALL BE DRAWN AT A LEGIBLE
12			SCALE	E AND SHALL INCLUDE THE LOCATION OF BUILDINGS, EXTERIOR
13			STORA	AGE FACILITIES, PERMANENT ACCESS WAYS, EVACUATION
14			ROUT	ES, PARKING LOTS, INTERNAL ROADS, CHEMICAL LOADING
15			AREA	S, EQUIPMENT CLEANING AREAS, STORM AND SANITARY SEWEF
16			ACCE	SSES, EMERGENCY EQUIPMENT, AND ADJACENT PROPERTY
17			USES.	
18		(B)	A bui	lding floor plan is required for Type I, II, and III
19			FACIL	ITIES. A BUILDING FLOOR PLAN SHALL BE DRAWN TO A
20			LEGIB	LE SCALE THAT SHALL INCLUDE THE IDENTITY OF EACH
21			HAZA	RDOUS MATERIALS STORAGE AREA WITHIN THE BUILDING AND
22			SHAL	L INDICATE ROOMS, DOORWAYS, CORRIDORS, MEANS OF
23			EGRE	SS, AND EVACUATION ROUTES.
24		(C)	An A	HJ approved hazardous materials inventory
25			STATI	ement (HMIS) is required for all facilities. The
26			INVEN	NTORY STATEMENT SHALL INCLUDE: HAZARD CLASS, COMMON
27			OR TR	ADE NAME, CHEMICAL NAME, MAJOR CONSTITUENTS, AND
28			CONC	entrations if a mixture. If the hazardous material is
29			WAST	E, THE WASTE CATEGORY, CHEMICAL ABSTRACT SERVICE
30			NUME	BER (CAS NUMBER) FOUND IN TITLE 29 OF THE CODE OF
31			FEDE	RAL REGULATIONS (CFR), WHETHER THE MATERIAL IS PURE

1			OR A MIXTURE, AND WHETHER THE MATERIAL IS A SOLID, LIQUID, OR
2			GAS, STORAGE CONDITIONS RELATED TO THE STORAGE TYPE,
3			TEMPERATURE, AND PRESSURE.
4		(D)	SAFETY DATA SHEETS (SDS) ARE REQUIRED FOR ALL FACILITIES
5			AND FOR ALL CHEMICALS LISTED ON THE APPLICATION.
6		(E)	Type I, II, and III facilities are required to provide a copy of
7			A CONTRACT WITH A DISPOSAL/CLEAN-UP COMPANY OR A PLAN TO
8			DISPOSE OF CHEMICALS OR CLEAN-UP SPILLS OR LEAKS.
9	(3)	Any	AMENDMENTS TO THE HAZARDOUS MATERIALS INVENTORY
10		STAT	ements shall be provided to the AHJ within $30 ext{days}$ of the
11		STOR	AGE OF ANY HAZARDOUS MATERIALS THAT EITHER:
12		(A)	Changes or adds a hazard class; or
13		(B)	That causes a 5% increase in the amount of any one hazard
14			CLASS.
15	(4)	THE	business shall notify the AHJ in writing $30\mathrm{days}$ prior to
16		VACA	ATING THE PROPERTY OR AREA WHERE HAZARDOUS MATERIALS ARE
17		LOCA	TED. THE AHJ SHALL CONDUCT AN INSPECTION ON THE LAST DAY
18		THAT	THE BUSINESS OCCUPIES THE PROPERTY OR AREA TO CONFIRM THAT
19		ALL F	HAZARDOUS MATERIALS HAVE BEEN REMOVED FROM THE PROPERTY OR
20		AREA	. A VIOLATION OF THIS SUBSECTION IS A CLASS A OFFENSE. EACH DAY
21		ТНАТ	A VIOLATION CONTINUES IS A SEPARATE OFFENSE.
22	(5)	APPL	ICATIONS FOR A HAZARDOUS MATERIAL PERMIT SHALL BE SUBMITTED
23		ANNU	JALLY BY THE FOLLOWING DATES:
24		(A)	Type I — Filing date: March 1^{st}
25		(B)	Type II — Filing date: August 1 st
26		(C)	Type III — Filing date: September $1^{\rm st}$
27		(D)	Type IV — Filing date May 1 st
28		(E)	Type V — Filing date: June 1^{st}
29		FAIL	URE TO APPLY FOR A HAZARDOUS MATERIALS PERMIT IS A $\operatorname{CLASS} A$
30		OFFE	NSE. EACH DAY THAT A VIOLATION CONTINUES IS A SEPARATE
31		OFFE	NSF

1		(6) A VIOLATION OF THIS SECTION IS A CLASS A OFFENSE. EACH DAY THAT A
2		VIOLATION CONTINUES IS A SEPARATE OFFENSE.
3	(362)	Subsection 60.1.1.1.1
4		Add new subsection $60.1.1.1.1$ after subsection $60.1.1.1$ as follows:
5		In addition to this Code, applicable requirements of the Public Safety
6		ARTICLE OF THE ANNOTATED CODE OF MARYLAND, SHALL APPLY. WHEN A PERMIT
7		CONFLICTS WITH A PROVISION OF THIS CODE, THE MORE STRINGENT REQUIREMENT
8		APPLIES.
9	(363)	SECTION 60.1.2
10		AMEND THIS SECTION TO DELETE THE FIRST PARAGRAPH AND SUBSTITUTE THE
11	FOL	LOWING:
12		EXCEPT FOR HAZARDOUS MATERIALS PERMIT REQUIREMENTS, BUILDINGS, AND
13		PORTIONS THEREOF, CONTAINING HIGH HAZARD CONTENTS LIMITED TO ANY OF THE
14		FOLLOWING ARE NOT REQUIRED TO COMPLY WITH THIS CHAPTER.
15	(364)	Subsection 63.1.1.1.1
16		ADD NEW SUBSECTION 63.1.1.1.1 AFTER SUBSECTION 63.1.1.1 AS FOLLOWS:
17		CARBON DIOXIDE (CO2) BEVERAGE SYSTEMS SHALL COMPLY WITH NFPA 55 AS
18		AMENDED.
19	(365)	SECTION 65.1.1
20		DELETE THIS SECTION AND SUBSTITUTE THE FOLLOWING:
21		Except as provided in subsections $65.1.1.1$, $65.1.3$, $65.1.4$, and $65.1.5$ of this
22		CODE, THE STORAGE, USE, AND HANDLING OF EXPLOSIVES, FIREWORKS, OR MODEL
23		ROCKETRY SHALL COMPLY WITH THE REQUIREMENTS OF THIS CHAPTER, NFPA
24		STANDARDS REFERENCED WITHIN THIS CHAPTER, SECTION 60.1 AND SECTION 60.2
25		of this Code, and the requirements set for forth in the Public Safety
26		ARTICLE OF THE ANNOTATED CODE OF MARYLAND.
27	(366)	SUBSECTION 65.1.1.1
28		ADD NEW SUBSECTION 65.1.1.1 AFTER SUBSECTION 65.1.1 AS FOLLOWS:
29		Unless the possession or discharge of the device is conducted under a
30		STATE FIRE MARSHAL PERMIT AND IS SUBJECT TO INSPECTION BY THE AHJ, A
31		PERSON SHALL NOT POSSESS, STORE, OFFER FOR SALE, EXPOSE FOR SALE, SELL, USE,

1		BURN, DISCHARGE, OR EXPLODE A GROUND-BASED SPARKLING DEVICE, INCLUDING
2		BUT NOT LIMITED TO, NON-AERIAL, NON-EXPLOSIVE CONE FOUNTAINS, AND
3		CYLINDRICAL FOUNTAINS.
4	(367)	SECTION 65.1.3
5		ADD NEW SECTION 65.1.3 AFTER SECTION 65.1.2 AS FOLLOWS:
6		In addition to the AHJ, the Howard County Department of Police May
7		ENFORCE SECTION 65.1.1.1 OF THIS CODE.
8	(368)	SECTION 65.1.4
9		ADD NEW SECTION 65.1.4 AFTER SECTION 65.1.3 AS FOLLOWS:
10		A PERSON POSSESSING, SELLING, OR DISCHARGING ILLEGAL FIREWORKS,
11		EXPLOSIVES, OR MODEL ROCKETRY OR UNLAWFULLY STORED HAZARDOUS
12		materials , or model rocketry shall forfeit the same to the AHJ. The
13		AHJ MAY SEIZE ILLEGAL FIREWORKS, EXPLOSIVES, OR MODEL ROCKETRY OR
14		UNLAWFULLY STORED HAZARDOUS MATERIALS , AND MODEL ROCKETRY.
15	(369)	SECTION 65.1.5
16		ADD NEW SECTION 65.1.5 AFTER SECTION 65.1.4 AS FOLLOWS:
17		A VIOLATION OF THIS CHAPTER IS A CLASS A OFFENSE. A PERSON WHO POSSESS,
18		SELLS, OR DISCHARGES ILLEGAL FIREWORKS, EXPLOSIVES, OR MODEL ROCKETRY OR
19		UNLAWFULLY STORED HAZARDOUS MATERIALS , OR MODEL ROCKETRY , OR WHO
20		FAILS TO SURRENDER ILLEGAL FIREWORKS, EXPLOSIVES, OR MODEL ROCKETRY TO
21		THE AHJ, OR WHO FAILS TO GET APPROVAL OR FOLLOW THE REGULATION SET
22		FORTH FOR FLAME EFFECTS IS GUILTY OF A MISDEMEANOR AND, UPON CONVICTION,
23		is subject to a fine not exceeding $\$1,\!000.00$ or imprisonment not
24		EXCEEDING 30 DAYS OR BOTH. ALTERNATIVELY, AND IN ADDITION TO AND
25		CONCURRENT WITH ALL REMEDIES PROVIDED AT LAW OR EQUITY, A FIRE OFFICIAL
26		MAY ENFORCE THIS SECTION WITH CIVIL PENALTIES PURSUANT TO TITLE 24, "CIVIL
27		PENALTIES," OF THE HOWARD COUNTY CODE. A VIOLATION OF THIS SUBSECTION IS
28		A CLASS A OFFENSE. EACH DAY THAT A VIOLATION CONTINUES IS A SEPARATE
29		OFFENSE.
30	(370)	SUBSECTION 66.23.5
31		ADD NEW SUBSECTION 66.23.5 AFTER SUBSECTION 66.23.4 AS FOLLOWS:

1		A PERSON SHALL OBTAIN APPROVAL BY THE MARYLAND DEPARTMENT OF THE
2		Environment and the Department of Inspections, Licenses and Permits to
3		REMOVE AN UNDERGROUND TANK. REMOVED TANKS SHALL BE TAKEN AWAY FROM
4		THE SITE WITHIN 24 HOURS.
5	(371)	SUBSECTION 69.1.1.4
6		ADD NEW SUBSECTION 69.1.1.4 AFTER SUBSECTION 69.1.1.3 AS FOLLOWS:
7		Cylinders connected to a temporary heating device in a building under
8		CONSTRUCTION OR BEING RENOVATED SHALL BE LOCATED OUTSIDE THE BUILDING,
9		SECURED IN A MANNER APPROVED BY THE AHJ, AND IN ACCORDANCE WITH
10		SUBSECTION 16.2.1.15 OF THIS CODE. ANY EXTRA CYLINDERS STORED ON A
11		CONSTRUCTION SITE SHALL BE SECURED IN A MANNER APPROVED BY THE AHJ.
12	(372)	SUBSECTION 69.3.13.1.3
13		DELETE THIS SUBSECTION AND SUBSTITUTE THE FOLLOWING:
14	•	EXCEPT FOR ONE- AND TWO-FAMILY DWELLINGS, PATIO HEATERS SHALL NOT BE
15		LOCATED WITHIN 5 FEET OF AN EXIT OR OPENING OF ANY BUILDING.
16	(373)	Subsection 69.5.3.2.4
17		ADD NEW SUBSECTION 69.5.3.2.4 AFTER SUBSECTION 69.5.3.2.3 AS FOLLOWS:
18		EXCEPT FOR CLASS A MERCANTILE OCCUPANCIES, IN MERCANTILE OCCUPANCIES
19		The total weight of all cylinders shall not exceed $10\mathrm{lbs}.$
20		
21	Section 2. An	ad Be It Further Enacted by the County Council of Howard County, Maryland that
22	this Act shall	become effective 61 days after its enactment.

BY THE COUNCIL

This Bill, having been approved by the Executive and returned to the Council, stands enacted on 2021. Michelle Harrod, Administrator to the County Council
BY THE COUNCIL
This Bill, having been passed by the yeas and nays of two-thirds of the members of the Council notwithstanding the objections of the Executive, stands enacted on
Michelle Harrod, Administrator to the County Council
BY THE COUNCIL
This Bill, having received neither the approval nor the disapproval of the Executive within ten days of its presentation, stands enacted on
Michelle Harrod, Administrator to the County Council
BY THE COUNCIL
This Bill, not having been considered on final reading within the time required by Charter, stands failed for want of consideration on
Michelle Harrod, Administrator to the County Council
BY THE COUNCIL
This Bill, having been disapproved by the Executive and having failed on passage upon consideration by the Council stands failed on
Michelle Harrod, Administrator to the County Council
BY THE COUNCIL
This Bill, the withdrawal of which received a vote of two-thirds (2/3) of the members of the Council, is withdrawn from further consideration on, 2021.
Michelle Harrod, Administrator to the County Council